

Product data sheet

Specifications



APC Replacement Battery Cartridge, VRLA battery, 7Ah, 12VDC, 2-year warranty

APCRBC110

Overview

Lead time Usually in Stock

Main

Product or Component Type Replacement battery cartridge

Battery Type Lead-Acid battery

Provided Equipment
All required connectors
Battery recycling guide
Reusable packaging
Installation guide

Batteries & Runtime

Included Battery Modules 0

Device mounting Enclosed battery cabinet

Battery Voltage 12 V

RBC Quantity 1

Physical

Color Black

Height 4.1 in (105 mm)

Width 5.9 in (151 mm)

Depth 2.6 in (65 mm)

Product Weight 4.9 lb(US) (2.2 kg)

Mounting Mode Not rack-mountable

USB compatible No

Output

Battery Capacity 7.0 Ah

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Operating altitude 0...10000 ft

Relative Humidity 0...95 %

Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)

Storage altitude 0...50000 ft (0...15240 m)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Storage Relative Humidity	0...95 %
---------------------------	----------

Ordering and shipping details

GTIN	731304248217
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	3.228 in (8.200 cm)
------------------	---------------------

Package 1 Width	6.890 in (17.500 cm)
-----------------	----------------------

Package 1 Length	8.268 in (21.000 cm)
------------------	----------------------

Package weight(Lbs)	5.150 lb(US) (2.336 kg)
---------------------	-------------------------

Unit Type of Package 2	P12
------------------------	-----

Number of Units in Package 2	150
------------------------------	-----

Package 2 Height	38.189 in (97.000 cm)
------------------	-----------------------

Package 2 Width	31.496 in (80.000 cm)
-----------------	-----------------------

Package 2 Length	47.244 in (120.000 cm)
------------------	------------------------

Package 2 Weight	803.365 lb(US) (364.400 kg)
------------------	-----------------------------

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	16 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	8 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.4 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.2 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.8 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	1
Circularity Profile	End of Life Information
Removable battery	No
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

