

Product data sheet

Specifications



APC Replacement Battery Cartridge #116 with 2 Year Warranty

APCRBC116

Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Lead time Usually in Stock

Main

Product or Component Type Replacement battery cartridge
Battery Type Lead-Acid battery
Range of Product Replacement Battery Cartridges

Batteries & Runtime

Battery Placement Internal Battery
Battery Slots Empty 0
Included Battery Modules 0
Device mounting Enclosed battery cartridge
Battery Voltage 48V
RBC Quantity 1

Physical

Color Black
Height 3.5 in (89 mm)
Width 6.5 in (165 mm)
Depth 16.5 in (419 mm)
Product Weight 23.04 lb(US) (10.45 kg)
Mounting Mode Not rack-mountable

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)
Operating altitude 0...10000 ft
Relative Humidity 0...95 %
Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)
Storage altitude 0...50000 ft (0...15240 m)

Ordering and shipping details

Category 11309-APC RESALE PRODUCTS
Discount Schedule APC1

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

GTIN	731304281696
Returnability	No
Country of origin	VN

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	7.5 in (19 cm)
Package 1 Width	11.5 in (29.2 cm)
Package 1 Length	21.5 in (54.6 cm)
Package weight(Lbs)	25.04 lb(US) (11.36 kg)
SCC14	731304281696

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	73 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	39 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.9 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0.8 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	30 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	1
Circularity Profile	End of Life Information
Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

