

# Product data sheet

Specifications



## APC Replacement Battery Cartridge # 136 with 2 Year Warranty

APCRBC136

**Product availability: Non-Stock - Not normally stocked in distribution facility**

### Overview

Lead time Usually in Stock

### Main

Product or Component Type Replacement battery cartridge

Battery Type Lead-Acid battery

Provided Equipment Installation guide

### Batteries & Runtime

Battery Placement Internal Battery

Battery blocks per string 2

Battery Slots Empty 0

Included Battery Modules 0

Device mounting Stand alone battery stack

Battery Voltage 24 V

RBC Quantity 1

### Physical

Height 4.2 in (107 mm)

Width 4.2 in (107 mm)

Depth 5.7 in (144 mm)

Product Weight 7.3 lb(US) (3.3 kg)

Mounting Mode Not rack-mountable

### Output

Battery Capacity 4.5 Ah

### Environmental

Ambient Air Temperature for Operation 32...122 °F (0...50 °C)

Operating altitude 0...10000 ft

Relative Humidity 0...95 %

Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)

Storage altitude 0...50000 ft (0...15240 m)

Storage Relative Humidity 0...95 %

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Ordering and shipping details

Category	09305-INDUSTRIAL UPS
Discount Schedule	IUPS
GTIN	731304293361
Returnability	No

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.02 in (22.9 cm)
Package 1 Width	9.02 in (22.9 cm)
Package 1 Length	9.02 in (22.9 cm)
Package weight(Lbs)	8.27 lb(US) (3.75 kg)

## Contractual warranty

Warranty (in months)	24
----------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	24 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	12 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.5 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.3 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	10 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	25764278-9ac2-4c03-941a-d133167ad10f
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

### Use Longer



### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture

Recyclability potential, in %	1
Circularity Profile	<a href="#">End of Life Information</a>
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---

