

Product data sheet

Specifications



Compatible with RBC17 APC Battery

BATT17-1209

Overview

Lead time Usually in Stock

Main

Product or Component Type	Battery
Number of cables	1
Battery Type	Lead-Acid battery
Provided Equipment	All required connectors Battery recycling guide Reusable packaging Installation guide
Range of Product	Smart-UPS Battery Systems

Batteries & Runtime

Battery Placement	Internal Battery
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
RBC Quantity	1

Physical

Color	Black
Height	2.6 in (65 mm)
Width	3.7 in (94 mm)
Depth	5.9 in (151 mm)
Product Weight	5.71 lb(US) (2.59 kg)
Mounting Mode	Not rack-mountable
USB compatible	No

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Storage Relative Humidity	0...95 %
---------------------------	----------

Ordering and shipping details

GTIN	731304338642
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	3.5 in (8.9 cm)
------------------	-----------------

Package 1 Width	8.4 in (21.3 cm)
-----------------	------------------

Package 1 Length	6.9 in (17.5 cm)
------------------	------------------

Package weight(Lbs)	6.31 lb(US) (2.86 kg)
---------------------	-----------------------

Contractual warranty

Warranty (in months)	12
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	13 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	11 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0.8 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	10 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	48
Circularity Profile	End of Life Information
Take-back	No