

# Product data sheet

Specifications



## APC Service Bypass PDU, 120V 20AMP W/ (8) NEMA 5-15R AND (2) 5-20R

SBP2200RM

Product availability: Stock - Normally stocked in distribution facility

### Overview

Lead time Usually in Stock

### Main

|                           |                                       |
|---------------------------|---------------------------------------|
| Main Input Voltage        | 120 V                                 |
| Product or Component Type | Bypass kit                            |
| Main Output Voltage       | 120 V                                 |
| Input Connection Type     | NEMA 5-20P                            |
| Number of rack unit       | 2U                                    |
| Cable length              | 7.9 ft (2.4 m)                        |
| Number of cables          | 1                                     |
| Provided Equipment        | User Manual<br>Rack Mounting brackets |
| Range of Product          | Maintenance Bypass Panels             |

### Physical

|                     |                       |
|---------------------|-----------------------|
| Color               | Black                 |
| Height              | 3.5 in (89 mm)        |
| Width               | 17.008 in (432 mm)    |
| Depth               | 3.0 in (76 mm)        |
| Product Weight      | 6.50 lb(US) (2.95 kg) |
| Mounting Location   | Front                 |
| Mounting preference | No preference         |
| Mounting Mode       | Rack-mounted          |

### Input

|                      |             |
|----------------------|-------------|
| Input Frequency      | 50/60 Hz    |
| permissible voltage  | 100...125 V |
| Max line current     | 20 A        |
| Input current limits | 20 A        |
| Load Capacity        | 2200 VA     |
| Power factor         | 0...1       |

### Output

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

|                                      |                              |
|--------------------------------------|------------------------------|
| Maximum Total Current Draw per Phase | 20 A                         |
| Number of power socket outlets       | 8 NEMA 5-15R<br>2 NEMA 5-20R |
| Number of power socket outlets       | 10                           |
| Protection Type                      | Circuit breaker              |
| Cord Length                          | 4 ft (1.2 m)                 |
| Efficiency                           | 99 %                         |

## Conformance

|                        |     |
|------------------------|-----|
| Product Certifications | TÜV |
|------------------------|-----|

## Environmental

|                                       |                            |
|---------------------------------------|----------------------------|
| Ambient Air Temperature for Operation | 32...104 °F (0...40 °C)    |
| Relative Humidity                     | 0...95 %                   |
| Operating altitude                    | 0...15000 ft               |
| Ambient Air Temperature for Storage   | 5...113 °F (-15...45 °C)   |
| Storage Relative Humidity             | 0...95 %                   |
| Storage altitude                      | 0...50000 ft (0...15240 m) |

## Ordering and shipping details

|                   |                        |
|-------------------|------------------------|
| Category          | 80230-IG SEBA TO SEUSA |
| Discount Schedule | BMS1                   |
| GTIN              | 731304266754           |
| Returnability     | No                     |
| Country of origin | PH                     |

## Packing Units

|                        |                     |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE                 |
| Nbr. of units in pkg.  | 1                   |
| Package 1 Height       | 5.9 in (15.1 cm)    |
| Package 1 Width        | 11.6 in (29.5 cm)   |
| Package 1 Length       | 18.2 in (46.3 cm)   |
| Package weight(Lbs)    | 8.4 lb(US) (3.8 kg) |

## Contractual warranty

|                      |    |
|----------------------|----|
| Warranty (in months) | 24 |
|----------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better



#### Materials and Substances

|  |   |
|--|---|
| Packaging made with recycled cardboard | Yes   |
| Packaging without single use plastic   | No  |
| SCIP Number                            | 31346aed-552c-4a16-81d9-e683a383b6da  |
| EU RoHS Directive                      | <a href="#">Compliant</a>   |
| REACH Regulation                       | <a href="#">Free of Substances of Very High Concern above the threshold</a> |

### Use Longer



#### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

### Use Again



#### Repack and remanufacture


|            |  |
|------------|--|
| Take-back  | Yes  |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Image of product / Alternate images

Alternative

---

