

Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 500VA, Lithium-ion, Rackmount 1U, 230V, 4x IEC C13 outlets, Short Depth

SCL500RMI1U

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

Main

Main Input Voltage	230 V AC 1 phase
Input Connection Type	IEC 60320 C14
Input protection type	Circuit breaker
Efficiency at full load	208...253 V
Input Frequency	50/60 Hz +/- 3 Hz auto sensing
Output voltage	230 V AC 1 phase
Rated power in W	400 W
rated power in VA	500 VA
output connection type	4 IEC 60320 C13
Harmonic distortion	Less than 5%
Maximum configurable power in VA	500 VA
Max Configurable Power (Watts)	400 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 1 Hz sync to mains

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery Size	Li-Ion (Lithium Ion) internal included
Control panel	LED status display with On Line : On Battery : Replace Battery and Building Wiring Fault
Free slots	0
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

UPS connectivity	Serial port USB port
Surge energy rating	510 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Number of rack unit	1U
color	Black with silver front bezel
Height	1.7 in (44 mm)
Width	17.008 in (432 mm)
Depth	9.1 in (232 mm)
Product Weight	8.95 lb(US) (4.06 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted
USB compatible	Yes
Mounting mode	Rack-mounted
Provided equipment	Installation guide Rack Mounting support rails USB cable
Redundant	No
Range of Product	Smart-UPS
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	CE EAC RCM
Equipment protection policy	Lifetime : \$150000
Standards	EN/IEC 62040-2:2006/AC:2006 EN/IEC 62040-2:2018
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...25000 ft (0...7620 m)
IP degree of protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	45 dBA
Online Thermal Dissipation	41.61 Btu/h
Operating altitude	0...10000 ft

Batteries & Runtime

Battery Type	Li-Ion (Lithium Ion)
Battery graph comments	This graph is based on actual measured runtime data. All measurements were taken with new, fully charged batteries and a balanced resistive load (PF = 1.0). Actual runtimes may vary from the values of this graph. Actual runtimes are dependent on several variables including battery age, battery charge level, environmental conditions and characteristics of the connected load.

Extendable Run Time	0
----------------------------	---

Battery design life	8...10 year(s)
----------------------------	----------------

Battery Charge Power (Watts)	10 W rated
-------------------------------------	------------

Ordering and shipping details

GTIN	731304402572
-------------	--------------

Country of origin	PH
--------------------------	----

Packing Units

Unit Type of Package 1	PCE
-------------------------------	-----

Nbr. of units in pkg.	1
------------------------------	---

Package 1 Height	6.6 in (16.8 cm)
-------------------------	------------------

Package 1 Width	23.2 in (59 cm)
------------------------	-----------------

Package 1 Length	13.3 in (33.7 cm)
-------------------------	-------------------

Package weight(Lbs)	13.2 lb(US) (6 kg)
----------------------------	--------------------

Contractual warranty

Warranty (in months)	60
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Environmental footprint

[Environmental Disclosure](#)

[Product Environmental Profile](#)

Use Better

Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

SCIP Number

C151e0e4-d5aa-4595-a297-c593b8808426

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Reference contains Substances of Very High Concern above the threshold](#)

Energy efficiency

Optimized Energy Efficiency

Energy efficient product

Product contributes to saved and avoided emissions

Yes

Use Longer

Lifetime extension

Repair

No

Use Again

Repack and remanufacture

Circularity Profile

[End of Life Information](#)

Removable battery

User replaceable

Take-back

Yes

WEEE Label

The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

