

# Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1000VA, Tower, 120V, 8x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD

SMT1000C

Product availability: Non-Stock - Not normally stocked in distribution facility

## Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

## Main

Main Input Voltage	120 V AC 1 phase
Other Input Voltages	110 V 125 V
Input Connection Type	NEMA 5-15P
Efficiency at full load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	120 V AC 1 phase
Other Output Voltages	110 V 125 V
Rated power in W	700 W
rated power in VA	1000 VA
output connection type	8 NEMA 5-15R
Harmonic distortion	Less than 5%
Maximum configurable power in VA	1000 VA
Max Configurable Power (Watts)	700 W
Transfer Time	6ms typical : 10ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	<a href="#">RBC6</a>

## Graphs

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>

## Complementary

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Battery Size</b>	Lead-acid internal included
<b>Control panel</b>	Multi-function LCD status and control console
<b>Free slots</b>	1
<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays
<b>UPS connectivity</b>	Serial port USB port SmartConnect port Available expansion slot
<b>Communication port support</b>	SmartConnect Ethernet port: for cloud monitoring feature availability varies by terms of use
<b>Software package</b>	SmartConnect software for remote power monitoring feature availability varies by terms of use
<b>Surge energy rating</b>	680 J
<b>Filtering</b>	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
<b>Cable length</b>	6 ft (1.8 m)
<b>Number of cables</b>	1
<b>color</b>	Black
<b>Height</b>	8.6 in (219 mm)
<b>Width</b>	6.7 in (171 mm)
<b>Depth</b>	17.3 in (439 mm)
<b>Product Weight</b>	44.3 lb(US) (20.1 kg)
<b>Mounting Location</b>	Front
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Not rack-mountable
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting mode</b>	Tower
<b>Provided equipment</b>	User Manual USB cable
<b>Number of power module</b>	0
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Additional specification</b>	Cloud-enabled monitoring
<b>Redundant</b>	No
<b>Range of Product</b>	Smart-UPS
<b>Product or Component Type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product Certifications</b>	cULus ENERGY STAR V2.0 (USA)
<b>Equipment protection policy</b>	Lifetime : \$150000
<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)

Storage altitude	0...50000 ft (0...15240 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	41 dBA
Online Thermal Dissipation	175 Btu/h
Operating altitude	0...10000 ft

## Batteries & Runtime

Battery Type	Lead-Acid battery
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery Life	3...5 year(s)
Battery Charge Power (Watts)	88 W rated

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	731304322771
Returnability	No
Country of origin	PH

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13.0 in (33 cm)
Package 1 Width	23.2 in (59 cm)
Package 1 Length	13.0 in (33 cm)
Package weight(Lbs)	49.91 lb(US) (22.64 kg)

## Contractual warranty

Warranty (in months)	36 UPS 24 Battery
----------------------	-------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	801 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	614 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	15 kg CO2 eq.
Carbon footprint of the installation phase [A5]	4 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	146 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	22 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	B2b22a56-41f2-497e-9ea6-cf093b3b8bd3
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>



### Energy efficiency

Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	51
Circularity Profile	<a href="#">End of Life Information</a>

Removable battery

User replaceable

Take-back

Yes

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Technical Illustration

Dimensions

---




Offer Marketing Illustration

Product benefits / Features

---

**Extended Runtime**

Support your sensitive electronics with battery power during utility power outages.



Offer Marketing Illustration

Product benefits / Features

---



Offer Marketing Illustration

Product benefits / Features

---

**Premium Power Protection**

Maintain business operations, customer satisfaction, and revenue by mitigating power and voltage disruptions.



1000VA / 900W  
Battery backup



Pure Sine Wave  
Power



99%  
Energy efficiency



Offer Marketing Illustration

Product benefits / Features

---

### Communication Ports and Outlets

Advanced monitoring and management capabilities with numerous outlets to power and protect all your sensitive devices.



Offer Marketing Illustration

Product benefits / Features

---

### SmartConnect Ethernet Port

Out-of-box cloud-based remote power monitoring



Select features may be subject to tier-based licensing. Terms on the Smart-UPS Web Portal.

Offer Marketing Illustration

Product benefits / Features

---

**Peace of mind at home or office with  
PowerChute™ Serial Shutdown Software**

UPS management, graceful shutdown, and  
energy management software for:



Desktops



Servers



Workstations



Image of product / Alternate images

Alternative

---

