

Product data sheet

Specifications



APC Smart-UPS, Line Interactive, 1500VA, Rackmount 2U, 120V, 6x NEMA 5-15R outlets, SmartConnect Port+SmartSlot, AVR, LCD [TAA]

SMT1500RM2UCUS

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V AC 1 phase

Other Input Voltages 110 V
125 V

Input Connection Type NEMA 5-15P

Efficiency at full load 75...154 V adjustable

Input Frequency 50/60 Hz +/- 3 Hz auto-sensing

Output voltage 120 V AC 1 phase

Other Output Voltages 110 V
125 V

Rated power in W 1000 W

rated power in VA 1440 VA

output connection type 6 NEMA 5-15R

Maximum configurable power in VA 1440 VA

Max Configurable Power (Watts) 1000 W

Topology Line Interactive

Waveform Type Sine wave

Output frequency 50/60 Hz +/- 3 Hz sync to mains

Replacement battery [APCRBC159](#)

Graphs

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Complementary

Battery Size Lead-acid internal included

UPS connectivity Serial port
USB port
SmartConnect port
Available expansion slot

Number of rack unit 2U

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

color	Black
Height	3.4 in (86 mm)
Width	17.008 in (432 mm)
Depth	18.8 in (477 mm)
Product Weight	58.4 lb(US) (26.5 kg)
Mounting Mode	Rack-mounted
Mounting mode	Rack-mounted with included kit
Provided equipment	CD with software
Redundant	No
Range of Product	Smart-UPS
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	cULus ENERGY STAR V2.0 (USA) TAA compliance
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

Batteries & Runtime

Battery Type	Lead-Acid battery
Extendable Run Time	0
Battery Charge Power (Watts)	144 W rated

Ordering and shipping details

GTIN	731304424420
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.3 in (23.5 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	23.2 in (59 cm)
Package weight(Lbs)	70.81 lb(US) (32.12 kg)

Compliance

Compliance	TAA Compliant
------------	---------------

Contractual warranty

Warranty (in months)	36
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	2 192 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	684 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	8 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 494 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold



Energy efficiency

Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	58
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

