

# Product data sheet

Specifications




APC Smart-UPS, Line Interactive, 3kVA, Rackmount 2U, 120V, 6 NEMA 5-15R+2 NEMA 5-20R outlets, Network Card, AVR, LCD [TAA]

SMT3000RM2UNCUS



## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	120 V AC 1 phase
Other Input Voltages	110 V
Input Connection Type	NEMA L5-30P
Efficiency at full load	75...154 V adjustable
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	120 V AC 1 phase
Rated power in W	2700 W
rated power in VA	2880 VA
output connection type	6 NEMA 5-15R
Harmonic distortion	Less than 5%
Maximum configurable power in VA	2880 VA
Max Configurable Power (Watts)	2700 W
Transfer Time	4ms typical : 8ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	<a href="#">RBC43</a> 

## Graphs

Run Time	<a href="#">View Runtime Graph</a> 
Efficiency	<a href="#">View Efficiency Graph</a> 

## Complementary

Battery Size	Lead-acid internal included
Control panel	Multi-function LCD status and control console
Free slots	0
Pre-Installed SmartSlot Cards	Network management card 3 with environmental monitoring
Control panel	LED status display with on line : on battery : replace battery and overload indicators

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Alarm</b>	Alarm when on battery : distinctive low battery alarm : configurable delays
<b>UPS connectivity</b>	Serial port USB port Pre-installed network management card 3
<b>Software package</b>	SmartConnect software for remote power monitoring feature availability varies by terms of use
<b>Surge energy rating</b>	459 J
<b>Number of rack unit</b>	2U
<b>Cable length</b>	8 ft (2.4 m)
<b>Number of cables</b>	1
<b>color</b>	Black
<b>Height</b>	3.40 in (86.36 mm) 3.4 in (86 mm)
<b>Width</b>	17.0080 in (432.0032 mm) 17.008 in (432 mm)
<b>Depth</b>	26.9 in (683 mm)
<b>Product Weight</b>	97.62 lb(US) (44.28 kg)
<b>Mounting Location</b>	Front
<b>Mounting preference</b>	No preference
<b>Mounting Mode</b>	Rack-mounted
<b>Two post mountable</b>	0
<b>USB compatible</b>	Yes
<b>Mounting mode</b>	Tower
<b>Provided equipment</b>	CD with software
<b>Number of power module</b>	0
<b>Number of power module filled slots</b>	0
<b>Number of power module free slots</b>	0
<b>Redundant</b>	No
<b>Range of Product</b>	Smart-UPS
<b>Product or Component Type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product Certifications</b>	CSA ENERGY STAR V2.0 (USA) TAA compliance
<b>Equipment protection policy</b>	Lifetime : \$150000
<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Storage altitude</b>	0...50000 ft (0...15240 m)
<b>Relative Humidity</b>	0...95 %
<b>Storage Relative Humidity</b>	0...95 %
<b>Acoustic level</b>	55 dBA
<b>Online Thermal Dissipation</b>	348 Btu/h
<b>Operating altitude</b>	0...10000 ft

## Batteries & Runtime

Battery Type	Lead-Acid battery
Extendable Run Time	0
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery Life	3...5 year(s)
Battery Charge Power (Watts)	188 W rated

## Ordering and shipping details

GTIN	731304740544
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	10.0 in (25.4 cm)
Package 1 Width	38.6 in (98 cm)
Package 1 Length	23.6 in (60 cm)
Package weight(Lbs)	113.93 lb(US) (51.68 kg)

## Compliance

Compliance	TAA Compliant
------------	---------------

## Contractual warranty

Warranty (in months)	36 UPS 24 Battery
----------------------	-------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	2 747 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	791 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	9 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 944 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>



### Energy efficiency

Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	58
Circularity Profile	<a href="#">End of Life Information</a>
Take-back	Yes

Technical Illustration

Dimensions

---



Image of product / Alternate images

Alternative

---

