

# Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 2000VA, Rack/tower convertible 4U, 100V-127V, 6x 5-15R+3x 5-20R+1x L5-20R NEMA, SmartSlot, Extended runtime, Short depth

SMX2000LV

**Product availability: Non-Stock - Not normally stocked in distribution facility**

## Overview


Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 2 Weeks


## Main

Main Input Voltage	120 V AC 1 phase
Other Input Voltages	100 V 110 V 127 V
Input Connection Type	NEMA 5-20P
Efficiency at full load	75...154 V adjustable 70...153 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing
Output voltage	120 V AC 1 phase
Other Output Voltages	100 V 110 V 127 V
Rated power in W	1800 W
rated power in VA	1920 VA
output connection type	6 NEMA 5-15R 3 NEMA 5-20R 1 NEMA L5-20R
Harmonic distortion	Less than 5%
Maximum configurable power in VA	1920 VA
Max Configurable Power (Watts)	1800 W
Transfer Time	2-4 ms 4ms typical : 8ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	<a href="#">APCRBC143</a>

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Graphs

Run Time [View Runtime Graph](#) 

Efficiency [View Efficiency Graph](#) 

## Complementary

Battery Size	Lead-acid internal included
Control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes
Free slots	1
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rating	540 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Number of rack unit	4U
Cable length	8 ft (2.4 m)
Number of cables	1
color	Black
Height	17.008 in (432 mm)
Width	7.008 in (178 mm)
Depth	19.02 in (483 mm)
Product Weight	85.19 lb(US) (38.64 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	1
USB compatible	Yes
Mounting mode	Tower
Provided equipment	CD with software Documentation CD Installation guide Rack mounting hardware Rack Mounting brackets Rack Mounting support rails Removable support feet Smart UPS signalling RS-232 cable USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	Extended run
Redundant	No
Range of Product	Smart-UPS

---

Product or Component Type	Uninterruptible power supply (UPS)
---------------------------	------------------------------------

## Environment

---

Product Certifications	BSMI CSA NOM TÜV VCCI Class A
------------------------	---

---

Equipment protection policy	Lifetime : \$150000
-----------------------------	---------------------

---

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

---

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

---

Storage altitude	0...50000 ft (0...15240 m)
------------------	----------------------------

---

Relative Humidity	0...95 %
-------------------	----------

---

Storage Relative Humidity	0...95 %
---------------------------	----------

---

Acoustic level	55 dBA
----------------	--------

---

Online Thermal Dissipation	203 Btu/h
----------------------------	-----------

---

Operating altitude	0...10000 ft
--------------------	--------------

## Batteries & Runtime

---

Battery Type	Lead-Acid battery
--------------	-------------------

---

Extendable Run Time	1
---------------------	---

---

Included Battery Modules	0
--------------------------	---

---

Battery Slots Empty	0
---------------------	---

---

Typical recharge time	3 h
-----------------------	-----

---

RBC Quantity	1
--------------	---

---

Battery Life	3...5 year(s)
--------------	---------------

---

Battery Charge Power (Watts)	229 W rated
------------------------------	-------------

## Ordering and shipping details

---

GTIN	731304292586
------	--------------

---

Country of origin	PH
-------------------	----

## Packing Units

---

Unit Type of Package 1	PCE
------------------------	-----

---

Nbr. of units in pkg.	1
-----------------------	---

---

Package 1 Height	13.0 in (33 cm)
------------------	-----------------

---

Package 1 Width	24.9 in (63.3 cm)
-----------------	-------------------

---

Package 1 Length	23.07 in (58.6 cm)
------------------	--------------------

---

Package weight(Lbs)	105.23 lb(US) (47.73 kg)
---------------------	--------------------------

---

Pallet unit layers	2
--------------------	---

---

Pallet layers	4
---------------	---

## Contractual warranty

---

Warranty (in months)	36 UPS 24 Battery
----------------------	-------------------



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	2 892 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	1 543 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	18 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 326 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	4 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>



### Energy efficiency

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	58
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	Yes

WEEE Label



The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

---

Image of product / Alternate images

Alternative

---







