

Product data sheet

Specifications



APC Smart-UPS X, Line Interactive, 2000VA, Rack/tower convertible 2U, 100V-127V, 3x 5-15R+3x 5-20R+1x L5-20R NEMA,NMC,Extended runtime,10 Ft input cord

SMX2KR2UNCX145

Overview

Lead time Usually in Stock

Main

Main Input Voltage 120 V AC 1 phase

Input Connection Type NEMA L5-20P

Efficiency at full load 75...154 V adjustable
70...153 V

Input Frequency 50/60 Hz +/- 3 Hz auto-sensing

Output voltage 120 V AC 1 phase

Rated power in W 1800 W

rated power in VA 1920 VA

output connection type 3 NEMA 5-15R
3 NEMA 5-20R
1 NEMA L5-20R

Harmonic distortion Less than 5%

Maximum configurable power in VA 1920 VA

Max Configurable Power (Watts) 1800 W

Transfer Time 4ms typical : 8ms maximum

Topology Line Interactive

Waveform Type Sine wave

Output frequency 50/60 Hz +/- 3 Hz sync to mains

Replacement battery [APCRBC117](#)

Graphs

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Complementary

Battery Size Lead-acid internal included

Control panel Multi-function LCD status and control console

Free slots 0

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Pre-Installed SmartSlot Cards	Network management card 2 with environmental monitoring
Control panel	LED status display with on line : on battery : replace battery and overload indicators
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
UPS connectivity	Serial port USB port Pre-installed network management card 3
Surge energy rating	540 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Number of rack unit	2U
Cable length	10 ft (3.05 m)
Number of cables	1
color	Black
Height	3.3 in (85 mm)
Width	17.008 in (432 mm)
Depth	26.3 in (667 mm)
Product Weight	84.77 lb(US) (38.45 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	No
Mounting mode	Rack-mounted
Provided equipment	CD with software Documentation CD Installation guide Network Management Card Rack mounting hardware Rack Mounting brackets Rack Mounting support rails Smart UPS signalling RS-232 cable USB cable
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	Network card pre-installed
Redundant	No
Range of Product	Smart-UPS
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	BSMI CSA NOM TÜV VCCI Class A
Equipment protection policy	Lifetime : \$150000
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	55 dBA
Online Thermal Dissipation	203 Btu/h
Operating altitude	0...10000 ft

Batteries & Runtime

Battery Type	Lead-Acid battery
Extendable Run Time	1
Included Battery Modules	1
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery Life	3...5 year(s)
Battery Charge Power (Watts)	229 W rated

Ordering and shipping details

GTIN	731304343271
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	9.6 in (24.3 cm)
Package 1 Width	34.2 in (86.9 cm)
Package 1 Length	23.5 in (59.6 cm)
Package weight(Lbs)	100.002 lb(US) (45.36 kg)
Pallet unit layers	2
Pallet layers	4

Contractual warranty

Warranty (in months)	36 UPS 24 Battery
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	3 095 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	966 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	11 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	2 110 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold



Energy efficiency

Optimized Energy Efficiency	Energy efficient product
-----------------------------	--------------------------

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture


Recyclability potential, in %	58
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative



