

Product data sheet

Specifications



APC Smart-UPS SRT 192V 5kVA and 6kVA RM Battery Pack Marine



SRT192RMBPM

Overview

Lead time Usually in Stock

Main

Product or Component Type External battery pack

Number of rack unit 3U

Battery Type Lead-Acid battery

Provided Equipment Installation guide
Warranty card

Range of Product Marine

Replacement battery [APCRBC140](#)

Batteries & Runtime

Device mounting Stand alone battery stack

Included Battery Modules 0

Battery Slots Empty 0

RBC Quantity 2

Battery Voltage 192V

Physical

Color Black

Height 5.1 in (130 mm)

Width 17.008 in (432 mm)

Depth 26.9 in (682.7 mm)

Product Weight 200.6 lb(US) (91 kg)

Mounting Mode Rack-mounted

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Relative Humidity 0...95 % non-condensing

Operating altitude 0...10000 ft

Ambient Air Temperature for Storage 5...113 °F (-15...45 °C)

Storage Relative Humidity 0...95 % non-condensing

Storage altitude 0...50000 ft (0...15240 m)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ordering and shipping details

GTIN 731304324317

Packing Units

| | |
|------------------------|-------------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 16.5 in (42 cm) |
| Package 1 Width | 39.4 in (100 cm) |
| Package 1 Length | 23.6 in (60 cm) |
| Package weight(Lbs) | 232.6 lb(US) (105.5 kg) |

Contractual warranty

Warranty (in months) 24



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|----------------|
| Total lifecycle Carbon footprint | 483 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 390 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 26 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 30 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 37 kg CO2 eq. |

Use Better



Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| SCIP Number | 488c31fb-3af8-42cf-9558-1362d000a07e |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|---------------------|--|
| Circularity Profile | End of Life Information |
| Removable battery | User replaceable |
| Take-back | Yes |
| WEEE Label |  The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

Image of product / Alternate images

Alternative

