

Product data sheet

Specifications



APC Smart-UPS On-Line, 3kVA,
Rackmount 2U, 208V, 2x
L6-20R+1x L6-30R NEMA outlets,
Network Card, Extended runtime,
W/ rail kit [TAA]

SRT3000RMXLT-NCUS

Overview

Lead time Usually in Stock

Main

Main Input Voltage	208 V AC 1 phase
Other Input Voltages	240 V
Input Connection Type	NEMA L6-20P
Efficiency at full load	100...275 V adjustable (half load)
Input Frequency	40 - 70 Hz auto-sensing
Output voltage	208 V AC 1 phase
Other Output Voltages	240 V
Rated power in W	2700 W
rated power in VA	3000 VA
output connection type	2 NEMA L6-20R
Bypass type	Internal Bypass (Automatic and Manual)
Crest factor	3 : 1
Harmonic distortion	Less than 2%
Maximum configurable power in VA	3000 VA
Max Configurable Power (Watts)	2700 W
Topology	On-Line
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains
Replacement battery	APCRBC152

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Additional information	Configurable for 208 or 240 nominal output voltage
Battery Size	Lead-acid internal included
Emergency Power Off (EPO)	Yes

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Free slots	0
Pre-Installed SmartSlot Cards	Network management card 3 with environmental monitoring
Alarm	Audible and visible alarms : prioritized by severity
UPS connectivity	Serial port USB port Available expansion slot Pre-installed network management card 3
Surge energy rating	340 J
Number of rack unit	2U
Cable length	10.007 ft (3.05 m)
Number of cables	1
color	Black
Height	3.3 in (85 mm)
Width	17.008 in (432 mm)
Depth	25 in (635 mm)
Product Weight	69.005 lb(US) (31.3 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	Yes
Mounting position	Horizontal
Mounting mode	Rack-mounted with kit sold separately
Provided equipment	CD with software
Number of power module filled slots	0
Number of power module free slots	0
Additional specification	High density
Redundant	No
Range of Product	Smart-UPS On-Line
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	ENERGY STAR V2.0 (USA) TAA compliance
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)
IP degree of protection	IP20
Relative Humidity	0...95 % non-condensing
Storage Relative Humidity	0...95 % non-condensing
Acoustic level	55 dBA
Online Thermal Dissipation	773 Btu/h

Operating altitude	0...10000 ft
--------------------	--------------

Batteries & Runtime

Battery Type	Lead-Acid battery
--------------	-------------------

Battery Voltage	96V
-----------------	-----

Extendable Run Time	1
---------------------	---

Included Battery Modules	1
--------------------------	---

Typical recharge time	3 h
-----------------------	-----

RBC Quantity	1
--------------	---

Battery Life	3...5 year(s)
--------------	---------------

Battery Charge Power (Watts)	165 W rated
------------------------------	-------------

Ordering and shipping details

GTIN	731304740629
------	--------------

Country of origin	MX
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	9.7 in (24.6 cm)
------------------	------------------

Package 1 Width	34.3 in (87.1 cm)
-----------------	-------------------

Package 1 Length	23.6 in (59.9 cm)
------------------	-------------------

Package weight(Lbs)	88.009 lb(US) (39.92 kg)
---------------------	--------------------------

Compliance

Compliance	TAA Compliant
------------	---------------

Contractual warranty

Warranty (in months)	36 UPS 24 Battery
----------------------	-------------------



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	7 242 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	212 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	7 026 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold



Energy efficiency

Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	58
Circularity Profile	End of Life Information
Take-back	Yes

Image of product / Alternate images

Alternative

