

# Product data sheet

Specifications



## APC Smart-UPS SRT 96V 3kVA RM Battery Pack



SRT96RMBPUS

### Overview

Lead time Usually in Stock

### Main

Product or Component Type	External battery pack
Number of rack unit	2U
Battery Type	Lead-Acid battery
Provided Equipment	Rack Mounting brackets User Manual Warranty card
Range of Product	Smart-UPS Accessories

### Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Stand alone battery stack
Battery Voltage	96V
RBC Quantity	2

### Physical

Color	Black
Height	3.3 in (85 mm)
Width	17.008 in (432 mm)
Depth	23.4 in (594 mm)
Product Weight	89.5 lb(US) (40.6 kg)
Mounting Mode	Rack-mounted

### Output

Battery Capacity 19 Ah

### Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

<b>Storage altitude</b>	0...50000 ft (0...15240 m)
-------------------------	----------------------------

---

<b>Storage Relative Humidity</b>	0...95 % non-condensing
----------------------------------	-------------------------

---

## Ordering and shipping details

---

<b>GTIN</b>	731304380030
-------------	--------------

---

<b>Country of origin</b>	PH
--------------------------	----

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Nbr. of units in pkg.</b>	1
------------------------------	---

---

<b>Package 1 Height</b>	9.4 in (23.9 cm)
-------------------------	------------------

---

<b>Package 1 Width</b>	32.7 in (83.1 cm)
------------------------	-------------------

---

<b>Package 1 Length</b>	23.6 in (59.9 cm)
-------------------------	-------------------

---

<b>Package weight(Lbs)</b>	98.1 lb(US) (44.5 kg)
----------------------------	-----------------------

---

## Contractual warranty

---

<b>Warranty (in months)</b>	24
-----------------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	204 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	165 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	11 kg CO2 eq.
Carbon footprint of the installation phase [A5]	13 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	16 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture


Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---

