

# Product data sheet

Specifications



## APC Smart-UPS Ultra Li-ion 10KVA 208V RM UPS with 2 of 5KVA Step Down Transformer

SRTL10KRM4UT-5KTF2

### Overview

Lead time Usually in Stock

### Main

Main Input Voltage	208 V AC 1 phase 240 V AC 1 phase
Other Input Voltages	208 V
Input Frequency	50/60 Hz
Output voltage	208 V AC 1 phase 240 V AC 1 phase
Other Output Voltages	208 V
Rated power in W	10000 W
rated power in VA	10000 VA
Crest factor	3 : 1
Maximum configurable power in VA	10000 VA
Max Configurable Power (Watts)	10000 W
Topology	On-Line
Waveform Type	Sine wave
Output frequency	50/60 Hz +/- 3 Hz sync to mains

### Complementary

Battery Size	Li-Ion (Lithium Ion) internal included
Control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Yes
Alarm	Audible and visible alarms : prioritized by severity
UPS connectivity	Serial port USB port Available expansion slot Embedded network management card 3
Number of rack unit	4U
Number of cables	1
color	Silver grey
USB compatible	Yes
Mounting mode	Rack/tower convertible with included kit
Provided equipment	RJ45 Cable

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Additional specification</b>	High density
<b>Redundant</b>	No
<b>Range of Product</b>	Smart-UPS Ultra
<b>Product or Component Type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Storage altitude</b>	0...50000 ft (0...15240 m)
<b>IP degree of protection</b>	IP20
<b>Relative Humidity</b>	0...95 % non-condensing
<b>Storage Relative Humidity</b>	0...95 % non-condensing
<b>Acoustic level</b>	55 dB
<b>Operating altitude</b>	0...10000 ft

## Batteries & Runtime

<b>Battery Type</b>	Li-Ion (Lithium Ion)
<b>Battery Voltage</b>	180 V
<b>Extendable Run Time</b>	0
<b>Typical recharge time</b>	1.5 h
<b>Battery Charge Power (Watts)</b>	1200 W rated

## Ordering and shipping details

<b>GTIN</b>	731304735960
<b>Country of origin</b>	PH

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	41.5 in (105.4 cm)
<b>Package 1 Width</b>	25.6 in (65 cm)
<b>Package 1 Length</b>	39.4 in (100 cm)
<b>Package weight(Lbs)</b>	397.9 lb(US) (180.5 kg)

## Contractual warranty

<b>Warranty (in months)</b>	60
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	16 425 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	638 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	13 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	15 762 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	11 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	86
Circularity Profile	<a href="#">End of Life Information</a>
Take-back	Yes

# Product data sheet SRTL10KRM4UT-5KTF2

Image of product / Alternate images

Alternative

---

