

# Product data sheet

Specifications



## APC Smart-UPS Ultra On-Line Lithium-ion XBP 180V 2U Rack/ Tower



SRTL180RM2UBP

### Overview

Lead time Usually in Stock

### Main

Product or Component Type External battery pack

Number of rack unit 2U

Battery Type Li-Ion (Lithium Ion)

Provided Equipment Rack Mounting brackets  
Vertical mounting brackets

Range of Product Smart-UPS Ultra

### Batteries & Runtime

Battery Slots Empty 0

Included Battery Modules 0

Battery Voltage 180 V

RBC Quantity 2

### Physical

Color Silver grey

Height 3.4 in (86 mm)

Width 17.008 in (432 mm)

Depth 28.5 in (724 mm)

Product Weight 71.4 lb(US) (32.4 kg)

Mounting Mode Rack-mounted with kit  
Tower-mounted with kit

### Output

Battery Capacity 8 Ah

### Conformance

Product Certifications UL 1973

### Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Operating altitude 0...10000 ft

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0...15240 m)
Storage Relative Humidity	0...95 % non-condensing

---

## Ordering and shipping details

---

GTIN 731304437024

## Packing Units

---

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	15.4 in (39.2 cm)
Package 1 Width	23.03 in (58.5 cm)
Package 1 Length	38.7 in (98.4 cm)
Package weight(Lbs)	92.6 lb(US) (42 kg)
SCC14	10731304437024

---

## Contractual warranty

---

Warranty (in months) 60



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	310 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	297 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	7 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	6 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	5ee38369-4dfb-4636-ab65-b08aa3242891
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	95
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative

---



