

Product data sheet

Specifications



APC Smart-UPS Ultra Tower Isolation/Step-Down Transformer, 5kVA, 8x 5-20R & 2x L6-20R & 1x L6-30R & 1x L14-30R NEMA outlets

SRTL5KTF

Overview

Lead time Usually in Stock

Main

Main Input Voltage	208 V
Product or Component Type	Transformer
Main Output Voltage	120 V
Other Output Voltage	240 V
rated power in VA	5 kVA
Input Connection Type	NEMA L6-30P
Cable length	3.0 ft (0.9 m)
Number of cables	1
Provided Equipment	User Manual
Range of Product	Smart-UPS Ultra

Physical

Color	Black
Height	17.008 in (432 mm)
Width	5.1 in (130 mm)
Depth	26.0 in (660 mm)
Product Weight	125.002 lb(US) (56.7 kg)
Mounting preference	No preference
Mounting Mode	Rack-mounted with kit

Input

Load Capacity	5000 VA
Input Frequency	50/60 Hz

Output

Maximum Total Current Draw per Phase	5000 A
Number of power socket outlets	12
Number of power socket outlets	8 NEMA 5-20R

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Conformance

Product Certifications	CSA
------------------------	-----

Standards	UL 1778
-----------	---------

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
---------------------------------------	-------------------------

Relative Humidity	0...95 % non-condensing
-------------------	-------------------------

Operating altitude	0...10000 ft
--------------------	--------------

Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
-------------------------------------	--------------------------

Storage Relative Humidity	0...95 % non-condensing
---------------------------	-------------------------

Storage altitude	0...50000 ft (0...15240 m)
------------------	----------------------------

Ordering and shipping details

GTIN	731304437048
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	13.7 in (34.7 cm)
------------------	-------------------

Package 1 Width	38.6 in (98 cm)
-----------------	-----------------

Package 1 Length	23.7 in (60.3 cm)
------------------	-------------------

Package weight(Lbs)	140.0 lb(US) (63.5 kg)
---------------------	------------------------

Contractual warranty

Warranty (in months)	60
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	22 141 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 887 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	21 kg CO2 eq.
Carbon footprint of the installation phase [A5]	28 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	97 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	53
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative

