

Product data sheet

Specifications



APC Smart-UPS SRT 19 inch Rail Kit for Smart-UPS SRT 5/6/8/10kVA

SRTRK2

Overview

Presentation	Accessory solutions to tailor the Smart-UPS to meet your specific needs.
Lead time	Usually in Stock

Main

Product or Component Type	Mounting kit
Provided Equipment	Installation guide Mounting Hardware Rack Mounting brackets
Range of Product	Smart-UPS Accessories

Physical

Color	Gray
Height	1.7 in (44 mm)
Width	20.7 in (527 mm)
Depth	3.5 in (89 mm)
Product Weight	6.02 lb(US) (2.73 kg)
Mounting Mode	Rack-mounted

Environmental

Ambient Air Temperature for Operation	-105...284 °F (-76...140 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 % non-condensing
Ambient Air Temperature for Storage	-105...284 °F (-76...140 °C)
Storage altitude	0...10000 ft (0...3048 m)
Storage Relative Humidity	0...95 % non-condensing

Ordering and shipping details

GTIN	731304313113
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	2.8 in (7.1 cm)
Package 1 Width	5.6 in (14.2 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package 1 Length	27.4 in (69.6 cm)
Package weight(Lbs)	8.025 lb(US) (3.640 kg)
Unit Type of Package 2	P12
Number of Units in Package 2	10
Package 2 Height	19.685 in (50.000 cm)
Package 2 Width	31.496 in (80.000 cm)
Package 2 Length	47.244 in (120.000 cm)
Package 2 Weight	142.529 lb(US) (64.650 kg)

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	719 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	29 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	1 739 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	65
Circularity Profile	End of Life Information
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.