

# Product data sheet

Specifications



APC Smart-UPS Modular Ultra On-Line, 15kW, Lithium-ion, Rackmount 9U, 208/240V, Network Management, Extended runtime, W/rail kit

SRYL15K15RMXLT

## Overview

Lead time Usually in Stock

## Main

Main Input Voltage	208 V AC 1 phase 120 V AC 1 phase 240 V AC 1 phase
Other Input Voltages	240 V
Maximum Input Current per Phase	75 A
Load power factor	0.5 leading to 0.5 lagging
Number of input connectors	1 Hard Wire 4-wire (2PH+N+G)
Input Frequency	40 - 70 Hz
Output voltage	120 V AC 1 phase 208 V AC 1 phase 240 V AC 1 phase
Other Output Voltages	240 V
Rated power in W	15000 W
rated power in VA	15000 VA
Bypass type	Built-in Bypass
Maximum configurable power in VA	15000 VA
Max Configurable Power (Watts)	15000 W
Overload Operation	60 seconds @ 125% and 30 seconds @ 150%
Topology	On-Line
Waveform Type	Sine wave

## Graphs

Run Time	<a href="#">View Runtime Graph</a>
Efficiency	<a href="#">View Efficiency Graph</a>

## Complementary

Battery Size	Li-Ion (Lithium Ion) internal included
Control panel	Touch Screen LCD User Interface
Emergency Power Off (EPO)	Yes
Pre-Installed SmartSlot Cards	Network management card

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>UPS connectivity</b>	Serial port USB port Available expansion slot Embedded network management card 3
<b>Number of rack unit</b>	9U
<b>color</b>	Silver
<b>Height</b>	15.4 in (390 mm)
<b>Width</b>	17.3 in (440 mm)
<b>Depth</b>	27.6 in (700 mm)
<b>Product Weight</b>	243.6 lb(US) (110.5 kg)
<b>Mounting Location</b>	Front Rear Side
<b>Mounting Mode</b>	Rack-mounted
<b>Two post mountable</b>	1
<b>USB compatible</b>	Yes
<b>Mounting position</b>	Horizontal
<b>Mounting mode</b>	Rack-mounted with included kit
<b>Number of power module</b>	3
<b>Number of power module filled slots</b>	3
<b>Number of power module free slots</b>	0
<b>Number preinstalled power module</b>	3
<b>Additional specification</b>	Network management card
<b>Redundant</b>	Yes
<b>Range of Product</b>	Smart-UPS Modular Ultra
<b>Product or Component Type</b>	Uninterruptible power supply (UPS)

## Environment

<b>Product Certifications</b>	ENERGY STAR V2.0 (USA)
<b>Marking</b>	CULus FCC
<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Storage altitude</b>	0...49212.6 ft (0...15000 m)
<b>Storage Relative Humidity</b>	0...95 %
<b>Acoustic level</b>	68 dB
<b>Operating altitude</b>	0...9842.52 ft (0...3000 m)

## Batteries & Runtime

<b>Battery Type</b>	Li-Ion (Lithium Ion)
<b>Extendable Run Time</b>	1
<b>Included Battery Modules</b>	3
<b>Battery Slots Empty</b>	0

---

<b>RBC Quantity</b>	3
---------------------	---

---

<b>Battery design life</b>	8...10 year(s)
----------------------------	----------------

---

## Ordering and shipping details

---

<b>GTIN</b>	731304420132
-------------	--------------

---

## Packing Units

---

<b>Unit Type of Package 1</b>	PCE
-------------------------------	-----

---

<b>Nbr. of units in pkg.</b>	1
------------------------------	---

---

<b>Package 1 Height</b>	38.7 in (98.2 cm)
-------------------------	-------------------

---

<b>Package 1 Width</b>	23.6 in (60 cm)
------------------------	-----------------

---

<b>Package 1 Length</b>	22.8 in (58 cm)
-------------------------	-----------------

---

<b>Package weight(Lbs)</b>	294.3 lb(US) (133.5 kg)
----------------------------	-------------------------

---

## Contractual warranty

---

<b>Warranty (in months)</b>	60
-----------------------------	----

---



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	29 574 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 018 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	39 kg CO2 eq.
Carbon footprint of the installation phase [A5]	28 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	26 332 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	157 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	8c493f2b-82c6-495f-a54a-f7d594e2b537
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>



### Energy efficiency

Optimized Energy Efficiency	Energy efficient product
 ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)
Product contributes to saved and avoided emissions	Yes

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	61
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	Yes



Image of product / Alternate images

Alternative

---



