

Product data sheet

Specifications



APC Smart-UPS Modular Ultra On-Line, 15kW, Lithium-ion, Tower 24U, 208/240V, Network Management Card

SRYL15K15XLT24

Overview

Lead time Usually in Stock

Main

Main Input Voltage 208 V AC 1 phase
120 V AC 1 phase
240 V AC 1 phase

Other Input Voltages 240 V

Maximum Input Current per Phase 75 A

Load power factor 0.5 leading to 0.5 lagging

Number of input connectors 1 Hard Wire 4-wire (2PH+N+G)

Input Frequency 40 - 70 Hz

Output voltage 120 V AC 1 phase
208 V AC 1 phase
240 V AC 1 phase

Other Output Voltages 240 V

Rated power in W 15000 W

rated power in VA 15000 VA

Bypass type Built-in Bypass

Maximum configurable power in VA 15000 VA

Max Configurable Power (Watts) 15000 W

Overload Operation 60 seconds @ 125% and 30 seconds @ 150%

Topology On-Line

Waveform Type Sine wave

Graphs

Run Time [View Runtime Graph](#)

Efficiency [View Efficiency Graph](#)

Complementary

Battery Size Li-Ion (Lithium Ion) internal included

Control panel Touch Screen LCD User Interface

Emergency Power Off (EPO) Yes

Pre-Installed SmartSlot Cards Network management card

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

UPS connectivity	Serial port USB port Available expansion slot Embedded network management card 3
Number of rack unit	24U
color	Black and silver
Height	47.2 in (1198 mm)
Width	23.6 in (600 mm)
Depth	35.4 in (900 mm)
Product Weight	470.5 lb(US) (213.4 kg)
Mounting Location	Front
Mounting mode	Tower
Number of power module	3
Number preinstalled power module	3
Additional specification	Network management card
Range of Product	Smart-UPS Modular Ultra
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	ENERGY STAR V2.0 (USA)
Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...49212.6 ft (0...15000 m)
Storage Relative Humidity	0...95 %
Acoustic level	68 dB
Operating altitude	0...9842.52 ft (0...3000 m)

Batteries & Runtime

Battery Type	Li-Ion (Lithium Ion)
Extendable Run Time	0
Included Battery Modules	3
RBC Quantity	3
Battery design life	8...10 year(s)

Ordering and shipping details

GTIN	731304622123
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	52.05 in (132.2 cm)
Package 1 Width	29.4 in (74.6 cm)
Package 1 Length	39.2 in (99.5 cm)

Package weight(Lbs) 519.76 lb(US) (235.76 kg)

Contractual warranty

Warranty (in months) 60



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	37 516 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	9 505 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	124 kg CO2 eq.
Carbon footprint of the installation phase [A5]	89 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	27 304 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	494 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	31346aed-552c-4a16-81d9-e683a383b6da
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold



Energy efficiency

Optimized Energy Efficiency	Energy efficient product
ENERGY STAR®	ENERGY STAR UPS V2.0 (USA)
Product contributes to saved and avoided emissions	Yes

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	61
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative

