

# Product data sheet

Specifications



## APC Smart-UPS Modular Ultra 15kW Frame, N+1 Redundant, Tower, 18U, 208/120V

SRYLF15T18

### Overview

Lead time Usually in Stock

### Main

|                           |  |
|---------------------------|--|
| Main Input Voltage        | 208 V AC   |
| Product or Component Type | Frame  |
| Main Output Voltage       | 208 V AC   |
| Other Output Voltage      | 240 V  |
| Number of rack unit       | 3U   |
| Cable length              | 1.0 ft (0.3 m)   |
| Battery Type              | Li-Ion (Lithium Ion)                                       |
| Provided equipment        | 10 x 10 wires<br>1 x 1 DIN rail<br>1 x Free trial software |
| Range of Product          | Smart-UPS Modular Ultra                                    |

### General

|                                   |                         |
|-----------------------------------|-------------------------|
| product web sub-family            | Network management card |
| Number of power module free slots | 1                       |

### Physical

|                |                         |
|----------------|-------------------------|
| color          | Black and silver        |
| Height         | 37.09 in (942 mm)       |
| Width          | 23.6 in (600 mm)        |
| Depth          | 35.4 in (900 mm)        |
| Product Weight | 318.1 lb(US) (144.3 kg) |
| Mounting Mode  | Rack-mounted with kit   |

### Ordering and shipping details

|      |              |
|------|--------------|
| GTIN | 731304622314 |
|------|--------------|

### Packing Units

|                        |                  |
|------------------------|------------------|
| Unit Type of Package 1 | PCE              |
| Nbr. of units in pkg.  | 1                |
| Package 1 Height       | 41.7 in (106 cm) |

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

---

|                            |                         |
|----------------------------|-------------------------|
| <b>Package 1 Width</b>     | 29.5 in (75 cm)         |
| <b>Package 1 Length</b>    | 39.2 in (99.5 cm)       |
| <b>Package weight(Lbs)</b> | 307.5 lb(US) (139.5 kg) |

---

## **Contractual warranty**

---

|                             |    |
|-----------------------------|----|
| <b>Warranty (in months)</b> | 60 |
|-----------------------------|----|



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Use Better

#### Materials and Substances

|  |  |
|--|--|
| Packaging made with recycled cardboard | Yes  |
| Packaging without single use plastic   | No   |
| SCIP Number                            | 31346aed-552c-4a16-81d9-e683a383b6da   |
| EU RoHS Directive                      | <a href="#">Compliant By Exemption</a>   |
| REACH Regulation                       | <a href="#">Reference contains Substances of Very High Concern above the threshold</a> |

### Use Longer

#### Lifetime extension

|        |    |
|--------|----|
| Repair | No |
|--------|----|

### Use Again

#### Repack and remanufacture

|                   |                  |
|-------------------|------------------|
| Removable battery | User replaceable |
| Take-back         | Yes              |