

Product data sheet

Specifications



APC Service Bypass Unit for SRYL, 200/208/230/240V, 125A, MBB, Hardwire Input/Output

SRYLSBP20KP

Overview

Lead time Usually in Stock

Main

Product or Component Type Bypass kit
Number of rack unit 4U
Range of Product Smart-UPS Modular Ultra Accessories

Physical

Color Black and silver
Height 6.9 in (175 mm)
Width 17.008 in (432 mm)
Depth 29.7 in (755 mm)
Product Weight 50.7 lb(US) (23 kg)
Mounting Mode Rack-mounted

Input

Max line current 125 A

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)
Operating altitude 0...9842.52 ft (0...3000 m)
Ambient Air Temperature for Storage -22...158 °F (-30...70 °C)
Storage altitude 0...49212.6 ft (0...15000 m)

Ordering and shipping details

GTIN 731304434702

Packing Units

Unit Type of Package 1 PCE
Nbr. of units in pkg. 1
Package 1 Height 11.8 in (30 cm)
Package 1 Width 22.8 in (58 cm)
Package 1 Length 38.2 in (97 cm)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Package weight(Lbs) 71.7 lb(US) (32.5 kg)

Contractual warranty

Warranty (in months) 60



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

Use Better



Materials and Substances

Packaging made with recycled cardboard

Yes

Packaging without single use plastic

No

EU RoHS Directive

[Compliant By Exemption](#)

REACH Regulation

[Free of Substances of Very High Concern above the threshold](#)

Use Longer



Lifetime extension

Repair

No

Use Again



Repack and remanufacture

Take-back

Yes

Image of product / Alternate images

Alternative



