

Product data sheet

Specifications



APC Smart-UPS Hardwire Kit for 2200/3000/5000VA SUA models, 120/208/230V

SUA031

Overview

Presentation	Accessory solutions to tailor the Smart-UPS to meet your specific needs.
Lead time	Usually in Stock

Main

Main Input Voltage	120 V 208 V 230 V
Product or Component Type	Spare part
Main Output Voltage	120 V 208 V 230 V
Provided Equipment	Hardwire panel Installation guide
Range of Product	Smart-UPS Accessories

Physical

Height	5 in (127 mm)
Width	7.008 in (178 mm)
Depth	2.008 in (51 mm)
Product Weight	2.006 lb(US) (0.91 kg)
Mounting Location	Rear
Mounting preference	No preference
Mounting Mode	Not rack-mountable
USB compatible	No

Input

Max line current	30 A
------------------	------

Output

Maximum Total Current Draw per Phase	30 A
--------------------------------------	------

Conformance

Product Certifications	cUL Recognized UL Recognized
------------------------	---------------------------------

Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	731304260226
------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.0 in (12.7 cm)
Package 1 Width	7.008 in (17.8 cm)
Package 1 Length	10.0 in (25.4 cm)
Package weight(Lbs)	2.992 lb(US) (1.357 kg)

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	10 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	10 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	Cd7f4ef4-11c7-46fb-b58a-a57ec8773a93
EU RoHS Directive	Compliant
REACH Regulation	Free of Substances of Very High Concern above the threshold

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
Circularity Profile	End of Life Information
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.