

Product data sheet

Specifications



APC Smart-UPS 5000VA 208V Rackmount/Tower

SUA5000RMT5U

Product availability: Non-Stock - Not normally stocked in distribution facility

Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually Ships within 3 Weeks

Main

Main Input Voltage	208 V AC 1 phase
Input Connection Type	NEMA L6-30P
Efficiency at full load	131...268 V adjustable 141...255 V
Input Frequency	50/60 Hz +/- 5 Hz manual switch
Output voltage	208 V AC 1 phase
Rated power in W	4000 W
rated power in VA	5000 VA
output connection type	2 NEMA L6-20R 2 NEMA L6-30R
Harmonic distortion	Less than 5 % at full load
Maximum configurable power in VA	5000 VA
Max Configurable Power (Watts)	4000 W
Transfer Time	2ms typical : 4ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output frequency	47...53 Hz for 50 Hz nominal sync to mains 57...63 Hz for 60 Hz nominal sync to mains
Replacement battery	RBC55

Graphs

Run Time	View Runtime Graph
Efficiency	View Efficiency Graph

Complementary

Battery Size	Lead-acid internal included
Control panel	LED status display with load and battery bar-graphs and On Line : On Battery : Replace Battery : and Overload Indicators
Emergency Power Off (EPO)	Optional

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Free slots	0
Pre-Installed SmartSlot Cards	Network management card
Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
UPS connectivity	Serial port USB port Available expansion slot
Surge energy rating	480 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m
Number of rack unit	5U
Cable length	8 ft (2.4 m)
Number of cables	1
color	Black
Height	8.7 in (222 mm)
Width	19.02 in (483 mm)
Depth	26.0 in (660 mm)
Product Weight	215.46 lb(US) (97.73 kg)
Mounting Location	Front
Mounting preference	Lower
Mounting Mode	Rack-mounted
Two post mountable	0
USB compatible	No
Mounting mode	Rack-mounted with included kit
Provided equipment	CD with software Rack Mounting support rails Smart UPS signalling RS-232 cable User Manual Web/SNMP Management Card
Number of power module	0
Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Range of Product	Smart-UPS
Product or Component Type	Uninterruptible power supply (UPS)

Environment

Product Certifications	CSA
Equipment protection policy	Lifetime : \$150000
Ambient Air Temperature for Operation	32...113 °F (0...45 °C)
Ambient Air Temperature for Storage	23...131 °F (-5...55 °C)
Storage altitude	0...50000 ft (0...15240 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %
Acoustic level	53 dBA

Online Thermal Dissipation	344 Btu/h
----------------------------	-----------

Operating altitude	0...10000 ft
--------------------	--------------

Batteries & Runtime

Battery Type	Lead-Acid battery
--------------	-------------------

Extendable Run Time	0
---------------------	---

Included Battery Modules	0
--------------------------	---

Battery Slots Empty	0
---------------------	---

Typical recharge time	3 h
-----------------------	-----

RBC Quantity	2
--------------	---

Battery Life	3...5 year(s)
--------------	---------------

Battery Charge Power (Watts)	542 W rated
------------------------------	-------------

Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
----------	-----------------------------

GTIN	731304255338
------	--------------

Returnability	No
---------------	----

Country of origin	PH
-------------------	----

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	25.0 in (63.5 cm)
------------------	-------------------

Package 1 Width	30.0 in (76.2 cm)
-----------------	-------------------

Package 1 Length	24.02 in (61 cm)
------------------	------------------

Package weight(Lbs)	235.50 lb(US) (106.82 kg)
---------------------	---------------------------

Contractual warranty

Warranty (in months)	24
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	9 143 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	3 655 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	43 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	5 434 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	10 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	58
Circularity Profile	End of Life Information
Removable battery	User replaceable
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative



