

# Product data sheet

Specifications



## APC Smart-UPS RT192V RM Battery Pack 2 Rows

SURT192RMXLBP2

### Overview

Lead time Usually in Stock

### Main

Product or Component Type	External battery pack
Number of rack unit	6U
Battery Type	Lead-Acid battery
Provided Equipment	All required connectors Rack Mounting brackets User Manual
Range of Product	Smart-UPS Battery Systems
Replacement battery	<a href="#">APCRBC140</a>

### Batteries & Runtime

Battery Slots Empty	0
Included Battery Modules	0
Device mounting	19 inch Battery tray
Battery Voltage	192V
RBC Quantity	4

### Physical

Color	Black
Height	10.4 in (263 mm)
Width	17.008 in (432 mm)
Depth	29.09 in (739 mm)
Product Weight	400.84 lb(US) (181.82 kg)
Mounting Mode	Rack-mounted

### Output

Battery Capacity	19 Ah
------------------	-------

### Conformance

Standards	OSHPD
-----------	-------

### Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Operating altitude</b>	0...10000 ft
<b>Relative Humidity</b>	0...95 % non-condensing
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Storage altitude</b>	0...50000 ft (0...15240 m)
<b>Storage Relative Humidity</b>	0...95 % non-condensing

## Ordering and shipping details

<b>GTIN</b>	731304255734
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	17.008 in (43.2 cm)
<b>Package 1 Width</b>	24.02 in (61 cm)
<b>Package 1 Length</b>	39.5 in (100.3 cm)
<b>Package weight(Lbs)</b>	486.009 lb(US) (220.45 kg)
<b>Unit Type of Package 2</b>	PAL
<b>Number of Units in Package 2</b>	4
<b>Package 2 Height</b>	39.9 in (101.4 cm)
<b>Package 2 Width</b>	39.4 in (100 cm)
<b>Package 2 Length</b>	47.2 in (120 cm)
<b>Package 2 Weight</b>	1939.999 lb(US) (879.968 kg)

## Contractual warranty

<b>Warranty (in months)</b>	24
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)

### Environmental footprint

Total lifecycle Carbon footprint	1 009 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	816 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	55 kg CO2 eq.
Carbon footprint of the installation phase [A5]	62 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	769 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	77 kg CO2 eq.

### Use Better

#### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	A64c500c-f72a-458b-8faa-8175a94429fe
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

### Use Longer

#### Lifetime extension

Repair	No
--------	----

### Use Again

#### Repack and remanufacture

Recyclability potential, in %	48
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	Yes
WEEE Label	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---



