

# Product data sheet

Specifications



## APC Smart-UPS RT 192V Battery Pack

SURT192XLBP

### Overview

Lead time Usually in Stock

### Main

Product or Component Type	External battery pack
Number of rack unit	3U
Battery Type	Lead-Acid battery
Provided Equipment	Installation guide User Manual
Range of Product	Smart-UPS Battery Systems
Replacement battery	<a href="#">APCRBC140</a>

### Batteries & Runtime

Battery blocks per string	16
Battery Slots Empty	0
Included Battery Modules	4
Device mounting	Stand alone battery stack
Battery Voltage	192V
Additional information	Replace all batteries in operation together (UPS internal and external batteries) all-at-once
RBC Quantity	2

### Physical

Color	Black
Height	5.1 in (130 mm)
Width	17.008 in (432 mm)
Depth	26.0 in (660 mm)
Product Weight	200.42 lb(US) (90.91 kg)
Mounting Mode	Rack-mounted with kit
USB compatible	No

### Output

Battery Capacity 18 Ah

### Environmental

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Ambient Air Temperature for Operation</b>	32...104 °F (0...40 °C)
<b>Operating altitude</b>	0...10000 ft
<b>Relative Humidity</b>	0...95 %
<b>Ambient Air Temperature for Storage</b>	5...113 °F (-15...45 °C)
<b>Storage altitude</b>	0...50000 ft (0...15240 m)
<b>Storage Relative Humidity</b>	0...95 %

## Ordering and shipping details

<b>GTIN</b>	731304205241
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	16.260 in (41.300 cm)
<b>Package 1 Width</b>	23.622 in (60.000 cm)
<b>Package 1 Length</b>	39.370 in (100.000 cm)
<b>Package weight(Lbs)</b>	223.461 lb(US) (101.360 kg)

## Contractual warranty

<b>Warranty (in months)</b>	24
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	464 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	375 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	25 kg CO2 eq.
Carbon footprint of the installation phase [A5]	29 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	35 kg CO2 eq.

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>
California proposition 65	<b>WARNING:</b> This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>

## Use Longer




### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.