

Product data sheet

Specifications



APC Symmetra LX Extended Run Rack-mount w/ 3 SYBT5, 208V

SYARMXR3B3



Overview

Lead time Usually in Stock

Main

Product or Component Type Battery accessory

Number of rack unit 5U

Number of cables 1

Battery Type Lead-Acid battery

Provided Equipment Installation guide
User Manual

Range of Product Symmetra Battery Systems

Batteries & Runtime

Battery Placement Battery Cabinet

Battery Slots Empty 0

Included Battery Modules 0

Battery manufacturer Panasonic

Device mounting Enclosed battery cabinet

RBC Quantity 3

Physical

Color Black

Height 8.5 in (215 mm)

Width 18.6 in (472 mm)

Depth 27.008 in (686 mm)

Product Weight 251.53 lb(US) (114.09 kg)

Mounting Mode Rack-mounted

Conformance

Standards UL 1778

Product Certifications CSA

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

| | |
|--|---------------------------|
| Operating altitude | 0...10000 ft |
| Relative Humidity | 0...95 % |
| Ambient Air Temperature for Storage | 5...113 °F (-15...45 °C) |
| Storage altitude | 0...15000 ft (0...4572 m) |
| Storage Relative Humidity | 0...95 % |

Ordering and shipping details

| | |
|-------------|--------------|
| GTIN | 731304740032 |
|-------------|--------------|

Packing Units

| | |
|-------------------------------|---------------------------|
| Unit Type of Package 1 | PCE |
| Nbr. of units in pkg. | 1 |
| Package 1 Height | 13.5 in (34.3 cm) |
| Package 1 Width | 38.6 in (98 cm) |
| Package 1 Length | 23.6 in (59.9 cm) |
| Package weight(Lbs) | 281.60 lb(US) (127.73 kg) |

Contractual warranty

| | |
|-----------------------------|----|
| Warranty (in months) | 24 |
|-----------------------------|----|



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

| | |
|--|-------------------|
| Total lifecycle Carbon footprint | 23 832 kg CO2 eq. |
| Carbon footprint of the manufacturing phase [A1 to A3] | 1 813 kg CO2 eq. |
| Carbon footprint of the distribution phase [A4] | 17 kg CO2 eq. |
| Carbon footprint of the installation phase [A5] | 17 kg CO2 eq. |
| Carbon footprint of the use phase [B2, B3, B4, B6] | 0 kg CO2 eq. |
| Carbon footprint of the end-of-life phase [C1 to C4] | 46 kg CO2 eq. |

Use Better



Materials and Substances

| | |
|--|--|
| Packaging made with recycled cardboard | Yes |
| Packaging without single use plastic | No |
| EU RoHS Directive | Compliant By Exemption |
| REACH Regulation | Reference contains Substances of Very High Concern above the threshold |

Use Longer



Lifetime extension

| | |
|--------|----|
| Repair | No |
|--------|----|

Use Again



Repack and remanufacture

| | |
|-------------------------------|---|
| Recyclability potential, in % | 66 |
| Circularity Profile | End of Life Information |
| Removable battery | User replaceable |
| Take-back | Yes |

Image of product / Alternate images

Alternative





