

Product data sheet

Specifications



APC SYMMETRA 3 Battery RACKMOUNT XR FRAME (208/120V REGIONS)

SYBFXR3RM

Overview

Lead time Usually in Stock

Main

Product or Component Type Frame

Number of rack unit 5U

Number of cables 1

Battery Type Lead-Acid battery

Provided Equipment Installation guide
User Manual

Range of Product Symmetra Battery Systems

Batteries & Runtime

Battery Placement Battery Cabinet

Battery Slots Empty 3

Included Battery Modules 0

Battery manufacturer Panasonic

Device mounting Enclosed battery cabinet

RBC Quantity 3

Physical

Color Black

Height 8.5 in (215 mm)

Width 18.6 in (472 mm)

Depth 27.008 in (686 mm)

Product Weight 59.13 lb(US) (26.82 kg)

Mounting Mode Rack-mounted

Conformance

Standards UL 1778

Product Certifications CSA

Environmental

Ambient Air Temperature for Operation 32...104 °F (0...40 °C)

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...15000 ft (0...4572 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

GTIN	731304233787
-------------	--------------

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	13.5 in (34.3 cm)
Package 1 Width	38.6 in (98 cm)
Package 1 Length	23.6 in (59.9 cm)
Package weight(Lbs)	68.17 lb(US) (30.92 kg)

Contractual warranty

Warranty (in months)	24
-----------------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	109 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	104 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	2 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
Circularity Profile	No need of specific recycling operations
Removable battery	User replaceable
Take-back	Yes

Image of product / Alternate images

Alternative





