

Product data sheet

Specifications

Battery Module for Symmetra PX, Smart-UPS VT or Galaxy 3500



SYBT4

Product availability: Stock - Normally stocked in distribution facility

Overview

Presentation	Battery module containing 4 battery units. Compatible with Symmetra PX 20/40/80, Smart-UPS VT, and Galaxy 3500 UPSs.
Lead time	Usually in Stock

Main

Battery Type	Lead-Acid battery
--------------	-------------------

Batteries & Runtime

Battery Placement	Internal Battery
Battery blocks per string	4
Device mounting	Enclosed battery cartridge
Battery Voltage	384 V
Battery Volt-Amp-Hour Capacity	2765 VAh

Physical

Color	Black
Height	6.3 in (15.9 cm)
Width	17.008 in (43.2 cm)
Depth	28.0 in (71.1 cm)
Product Weight	200.42 lb(US) (90.91 kg)

Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...3333 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...104 °F (-15...40 °C)
Storage altitude	0...50000 ft (0...15240 m)
Storage Relative Humidity	0...95 %

Ordering and shipping details

Category	80230-IG SEBA TO SEUSA
Discount Schedule	BMS1
GTIN	731304238256

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Returnability	No
Country of origin	PH

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	18.0 in (45.7 cm)
Package 1 Width	24.02 in (61 cm)
Package 1 Length	33.0 in (83.8 cm)
Package weight(Lbs)	224.47 lb(US) (101.82 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	7
Package 2 Height	18.00 in (45.72 cm)
Package 2 Width	39.4 in (100 cm)
Package 2 Length	47.2 in (120 cm)
Package 2 Weight	1571.32 lb(US) (712.74 kg)



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	0 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	0 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	080b8d64-796e-42e7-a17d-31b86e55d143
EU RoHS Directive	Compliant
REACH Regulation	Reference contains Substances of Very High Concern above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Use Longer




Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Take-back	No
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.