

# Product data sheet

Specifications



## APC Symmetra RM 2-6kVA Power Module (2kVA)

SYPM2KU

### Overview

Presentation	High density, double-conversion on-line power protection with scalable runtime.
Lead time	Usually in Stock

### Main

Main Input Voltage	200 V 208 V
Product or Component Type	Power module
Main Output Voltage	200 V 208 V 230 V
Rated power in W	1400 W
rated power in VA	2000 VA
Number of rack unit	0U
Number of cables	1
Provided Equipment	Installation guide
Range of Product	Symmetra Power Module

### Batteries & Runtime

Included Battery Modules	0
Battery Slots Empty	0

### Physical

Height	3.3 in (82.6 mm)
Width	8.5 in (215.9 mm)
Depth	21.5 in (546.1 mm)
Product Weight	17.04 lb(US) (7.73 kg)
Mounting Location	Front
Mounting preference	No preference
Mounting Mode	Not rack-mountable
USB compatible	No

### Input

Input Frequency	50/60 Hz +/- 5 Hz auto-sensing
Efficiency at full load	155...276 V

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

## Output

---

Max Configurable Power (Watts) 1400 W

## Ordering and shipping details

---

GTIN 731304016885

## Packing Units

---

Unit Type of Package 1 PCE

Nbr. of units in pkg. 1

Package 1 Height 9.75 in (24.77 cm)

Package 1 Width 14.00 in (35.56 cm)

Package 1 Length 26.00 in (66.04 cm)

Package weight(Lbs) 19.998 lb(US) (9.071 kg)

## Contractual warranty

---

Warranty (in months) 24



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	17 391 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	97 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0 kg CO2 eq.
Carbon footprint of the installation phase [A5]	7 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	17 319 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	8 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

### Use Better



### Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
SCIP Number	8c493f2b-82c6-495f-a54a-f7d594e2b537
EU RoHS Directive	<a href="#">Compliant By Exemption</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

### Use Longer



### Lifetime extension

Repair	No
--------	----

### Use Again



### Repack and remanufacture


Recyclability potential, in %	27
Circularity Profile	<a href="#">End of Life Information</a>
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

---

