

# Product data sheet

Specifications



## SmartUPS Industrial Battery 50Ah 12VDC Extended Temperature Shelf Mount

XB050XX1XS

### Overview

Lead time Usually in Stock

### Main

Product or Component Type Battery  
Battery Type Gel Cell  
Range of Product Smart-UPS Battery Systems

### Batteries & Runtime

Battery blocks per string 4  
Battery Slots Empty 0  
Included Battery Modules 0  
Device mounting Stand alone battery stack  
Battery Voltage 12 V

### Physical

Height 8.07 in (205 mm)  
Width 5.4 in (138 mm)  
Depth 9.02 in (229 mm)  
Product Weight 36.6 lb(US) (16.6 kg)  
Mounting Mode Not rack-mountable

### Conformance

Product Certifications UL Recognized  
Marking CE Mark

### Environmental

Ambient Air Temperature for Operation -4...131 °F (-20...55 °C)  
Ambient Air Temperature for Storage -4...122 °F (-20...50 °C)

### Ordering and shipping details

GTIN 731304327165

### Packing Units

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

<b>Unit Type of Package 1</b>	PCE
<b>Nbr. of units in pkg.</b>	1
<b>Package 1 Height</b>	11.0 in (27.9 cm)
<b>Package 1 Width</b>	10.0 in (25.4 cm)
<b>Package 1 Length</b>	6.5 in (16.5 cm)
<b>Package weight(Lbs)</b>	38.008 lb(US) (17.24 kg)

## **Contractual warranty**

<b>Warranty (in months)</b>	24
-----------------------------	----



## Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



### Environmental footprint

Total lifecycle Carbon footprint	3 407 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	136 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	2 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	4 531 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	1 kg CO2 eq.
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Use Better



### Materials and Substances

Packaging made with recycled cardboard	No
Packaging without single use plastic	No
EU RoHS Directive	<a href="#">Compliant</a>
REACH Regulation	<a href="#">Reference contains Substances of Very High Concern above the threshold</a>

## Use Longer



### Lifetime extension

Repair	No
--------	----

## Use Again



### Repack and remanufacture

Recyclability potential, in %	65
Circularity Profile	<a href="#">End of Life Information</a>
Removable battery	User replaceable
Take-back	Yes