

Product data sheet

Specifications



APC Smart-UPS Industrial Service Bypass Unit, 30A, 120V, rack mount, 2U, with generator input

XS30ALLXR2G

Overview

Lead time Special Order - Call for Quoted Lead Times

Main

Main Input Voltage	120 V
Product or Component Type	Bypass kit
Main Output Voltage	110 V 120 V
Other Output Voltage	110 V
Output connector type	Hard Wire 3-wire (H N + E) for 1 zone(s)
Number of rack unit	2U
Provided Equipment	Rack Mounting brackets
Range of Product	Smart-UPS Accessories

Physical

Color	Black
Height	3.4 in (87.6 mm)
Width	11.02 in (280 mm)
Depth	2.8 in (72 mm)
Product Weight	2.9 lb(US) (1.3 kg)
Mounting Support	Wall
Mounting preference	No preference
Mounting Mode	Rack-mounted

Input

Input Frequency	50/60 Hz
Number of input connectors	1 Hard Wire 3-wire (1PH+N+G)
Max line current	30 A
Input current limits	30 A
Power factor	0...1

Output

Maximum Total Current Draw per Phase	30 A
Protection Type	Circuit breaker

Price is "List Price" and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Efficiency	99 %
------------	------

Conformance

Product Certifications	CSA GOST VDE
------------------------	--------------------

Environmental

Ambient Air Temperature for Operation	-35...165 °F (-37...74 °C)
---------------------------------------	----------------------------

Relative Humidity	0...95 %
-------------------	----------

Operating altitude	0...15000 ft
--------------------	--------------

Ambient Air Temperature for Storage	-40...185 °F (-40...85 °C)
-------------------------------------	----------------------------

Storage Relative Humidity	0...95 %
---------------------------	----------

Storage altitude	0...50000 ft (0...15240 m)
------------------	----------------------------

Ordering and shipping details

GTIN	731304399353
------	--------------

Packing Units

Unit Type of Package 1	PCE
------------------------	-----

Nbr. of units in pkg.	1
-----------------------	---

Package 1 Height	5.9 in (15 cm)
------------------	----------------

Package 1 Width	11.6 in (29.5 cm)
-----------------	-------------------

Package 1 Length	18.1 in (46 cm)
------------------	-----------------

Package weight(Lbs)	4.50 lb(US) (2.04 kg)
---------------------	-----------------------

Contractual warranty

Warranty (in months)	36
----------------------	----



Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

[Environmental Data explained >](#)

[How we assess product sustainability >](#)



Environmental footprint

Total lifecycle Carbon footprint	15 kg CO2 eq.
Carbon footprint of the manufacturing phase [A1 to A3]	14 kg CO2 eq.
Carbon footprint of the distribution phase [A4]	0.3 kg CO2 eq.
Carbon footprint of the installation phase [A5]	0 kg CO2 eq.
Carbon footprint of the use phase [B2, B3, B4, B6]	0 kg CO2 eq.
Carbon footprint of the end-of-life phase [C1 to C4]	0.3 kg CO2 eq.
Environmental Disclosure	Product Environmental Profile

Use Better



Materials and Substances

Packaging made with recycled cardboard	Yes
Packaging without single use plastic	No
EU RoHS Directive	Compliant By Exemption
REACH Regulation	Reference contains Substances of Very High Concern above the threshold

Use Longer



Lifetime extension

Repair	No
--------	----

Use Again



Repack and remanufacture

Recyclability potential, in %	95
Take-back	Yes
WEEE Label	 The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Image of product / Alternate images

Alternative

