



Quantum Spark 2500 Series for SMBs and Branches

Security Gateways



YOU DESERVE THE BEST SECURITY



Quantum

Network Security

Top Security Effectiveness

Check Point has been ranked #1 for the third consecutive year, achieving a 99.9% malware block rate, 99.7% phishing prevention and 98% high and critical exploit prevention in the

[Miercom Hybrid Mesh Firewall Benchmark 2025](#)

Named a Leader by Top Analyst Firms

[Forrester Wave™ for Enterprise Firewalls 2024](#)

Check Point Recognized as a Leader and Outperformer for Enterprise Firewalls

[GigaOm Radar for Enterprise Firewalls 2025](#)

Supercharge your network security with the Quantum Spark 2500 gateway series of next generation firewalls designed for today's fast-paced SMBs and branches. Experience lightning-fast threat prevention with throughputs up to 3,200 Mbps, and stay connected with the latest Wi-Fi 7, 5G cellular, and 10GbE LAN ports.



Enterprise Grade
Security



Fastest Connectivity
with Wi-Fi 7 and
5G Cellular



Unified Security
Management

Quantum Spark 2500 Performance Highlights

Model	Next Gen Firewall	Threat Prevention
QS 2530	1,200 Mbps	750 Mbps
QS 2550	1,600 Mbps	1,000 Mbps
QS 2560	3,750 Mbps	1,850 Mbps
QS 2570	5,000 Mbps	2,500 Mbps
QS 2580	9,000 Mbps	3,200 Mbps

Advanced security and uncompromising performance, built for SMBs & branches

Check Point Quantum Spark 2500 security gateway family delivers enterprise-grade security for small and medium businesses and enterprise branches in a series of simple and affordable, all-in-one security solutions. Models with the latest Wi-Fi 7 and embedded 5G modem provide fast and resilient connectivity.

Comprehensive and Industry-Leading Security

- Next Generation Firewall
- Site-to-Site and Remote Access VPN
- Application and Web Filtering
- Intrusion Prevention
- Antivirus and Anti-Bot
- Advanced DNS Security
- Sandboxing
- Zero-phishing (no agent required)

Quantum Spark Management

Managed Service Providers use Quantum Spark Management to provision up to thousands of gateways efficiently, reducing operational overhead. Interactive dashboards provide quick identification of security, connectivity and licensing issues across all customers. With proactive management alerts, MSP administrators can be notified of issues over SMS, email, MS Teams and more, enabling faster resolution.

Spark Management is included with the Spark appliance at no extra cost.

The Spark 2500 series can be managed by Spark Management, Web UI, Smart-1Cloud and Management Server.

5G cellular connectivity

Get the latest 5G cellular standard, offering the highest throughputs, which can be used as a primary WAN connection (Fixed Wireless Access) or as a backup link. Supports Dual SIM Single Standby (DSSS) and backward compatibility to 4G/LTE networks.

Latest Wi-Fi 7

The Quantum Spark 2500 series support the latest Wi-Fi 7 standard with up to 30% added throughput over previous Wi-Fi 6 models as well as improved client density and reduced latency.

Highest Performance Threat Prevention

Thanks to R82 security and management technology, with the 2500 Series, you can inspect encrypted traffic and prevent even the most evasive attacks without impacting internal network performance. Achieve 3.2 Gbps of threat prevention throughput and 17.5 Gbps of firewall throughput.

Quantum Spark 2530/2550




1. Power Switch
2. 6x RJ45 1GbE copper LAN ports
3. 1GbE copper/fiber WAN port
4. 1GbE copper/fiber DMZ port
5. USB 3.0 Type-A port
6. USB Type-C console port
7. Power Supply Connector
8. Wi-Fi Antennas (x2) for supported models:
CPAP-SG2530W-SNBT
CPAP-2550W-SNBT
CPAP-2550W5G-SNBT (roadmap)

Quantum Spark 2560/2570



1. Power Switch
2. 8x RJ45 1GbE copper LAN ports
3. 1GbE copper WAN port
4. 1GbE Fiber DMZ port
5. 2x 10GbE fiber LAN/WAN ports
6. USB 3.0 Type-A port
7. USB Type-C console port
8. Power Supply Connector (Dual)
9. Wi-Fi Antennas (x4) for supported models:
CPAP-SG2560W-SNBT
CPAP-2570W-SNBT
CPAP-2570W5G-SNBT

Quantum Spark 2580



1. 2x RJ45 2.5GbE copper LAN ports
2. 8x RJ45 1GbE copper LAN ports
3. 10GbE copper/fiber DMZ ports
4. 10GbE copper/fiber WAN ports
5. USB 3.0 Type-A port
6. RJ45 console port
7. USB Type-C console port
8. Factory Default switch
9. Reset switch
10. Dual power Supply Connector
11. Power Switch

Specifications

Test Conditions	2530	2550	2560	2570	2580
Threat Prevention [Mbps]	750	1,000	1,850	2,500	3,200
Next Generation Firewall [Mbps] ¹	1,200	1,600	3,750	5,000	9,000
IPS Throughput [Mbps]	1,720	2,300	5,170	6,900	11,000
Firewall Throughput [Mbps]	2,250	3,000	6,750	9,000	17,500
RFC 3511, 2544, 2647, 1242 Performance (Lab)					
Firewall 1518 bytes UDP [Mbps]	3,000	4,000	11,600	15,500	20,000
Firewall Latency Avg. (µSec)	90		30		24
VPN AES-GCM 1452B [Mbps]	1,400		4,000		4,500
Connections/Sec	16,000	20,000	53,000	62,000	72,000
Concurrent Connections	1,000,000		2,000,000		
Software					
Security	Firewall, VPN, User Aware, QoS, Application Control, URLF, IPS, Anti-Bot, Antivirus, Anti-Spam, sandboxing				
Unicast, Multicast Routing and Clustering	OSPFv2, BGPv4 and 4++, RIP, PIM (SM, DM, SSM), IGMP, ClusterXL High Availability				
IPv6	local network and internet connections, dual stack tunneling IPv4 over IPv6 networks, prefix delegation				
Remote Access Users	100		200		1,000
SD-WAN	Integrated SD-WAN network optimization and resilience				
VLAN's	Total physical and virtual (VLAN) interfaces per appliance: 1024 (single gateway)				
Link Aggregation	802.3ad passive and active link aggregation				
Layer 2	Layer 2 (transparent) and Layer 3 (routing) mode				
IPv6	NAT66, NAT64, NAT46 / CoreXL, SecureXL, HA with VRRPv3				
Management Options	Web UI, Spark Management application, Smart-1 Cloud & Management Server				

Hardware	2530		2550	2560		2570	2580
WAN Port	1 x 1GbE RJ45/SFP			1 x 1GbE RJ45			1 x 10GbE RJ45/SFP
DMZ Ports	1 x 1GbE RJ45/SFP			1 x 1GbE SFP			1 x 10GbE RJ45/SFP
LAN Ports	6 x 1GbE RJ45			8 x 1GbE RJ45 and 2 x 10GbE SFP+			8 x 1GbE RJ45 2 x 2.5GbE RJ45
Wi-Fi & bands	Wi-Fi 7 2x2 2.4Ghz + 5Ghz			Wi-Fi 7 4X4 2.4Ghz + 5Ghz + 6Ghz			-
5G ² (optional)	No	Yes		No	Yes		No
SD Card Slot	Micro-SD slot						
Dimensions							
Dimensions (W x D x H)	210 x 170 x 42 mm, 8.3 x 6.7 x 1.7 in.			210 x 170 x 42 mm, 8.3 x 6.7 x 1.7 in.			210 x 209x 42 mm, 8.3 x 8.3 x 1.7 in.
Weight	0.87 kg (1.9 lbs.)			0.87 kg (1.9 lbs.)			0.988 kg (2.178lbs.)
Environment							
Operating / Storage	0°C ~ 40°C / -45°C ~ 60°C (5~95%, non-condensing)						
MTBF	Wired / Wi-Fi Models - 126 Years			Wired / Wi-Fi Models - 33 Years			Wired - 57 Years
Power Requirements							
AC Input	100 to 240VAC (47-63Hz)						
Dual Power	No			Available			
Power Supply Rating	12V/3.3A 40W power adapter (non-Wi-Fi)			12V/5A 60W power adapter (all Wi-Fi models)			
Power Consumption (Max)	26.01W (non-Wi-Fi); 31.28W (Wi-Fi); 35.5W (Wi-Fi-5G)						
Certifications							
Safety	CB IEC 62368-1, CE LVD EN62368-1, UL62368-1, ASNZS 62368.1						
Emissions	CE, FCC IC, VCCI, ASNZS ACMA						
Environmental	ROHS, REACH, WEEE, ISO14001						
Regulated Model	T90 (Wired), T90W (Wi-Fi)			T91 (Wired), T91W (Wi-Fi)			T92

¹ Includes Firewall, App Control and IPS with logging enabled

² Roadmap

Security Appliances	SKU
2530 Desktop form factor, 1x1GbE copper/SFP WAN port, 1x1GbE copper/SFP SFP port, 4x1GbE copper LAN ports.	CPAP-SG2530-SNBT
2530W Desktop form factor, 1x1GbE copper/SFP WAN port, 1x1GbE copper/SFP SFP port, 4x1GbE copper LAN ports, 802.11ax 2x2 MIMO Wi-Fi 7.	CPAP-SG2530W-SNBT
2550 Desktop form factor, 1x1GbE copper/SFP WAN port, 1x1GbE copper/SFP SFP port, 4x1GbE copper LAN ports.	CPAP-SG2550-SNBT
2550W Desktop form factor, 1x1GbE copper/SFP WAN port, 1x1GbE copper/SFP SFP port, 4x1GbE copper LAN ports, 802.11ax 2x2 MIMO Wi-Fi 7.	CPAP-SG2550W-SNBT
2550W Desktop form factor, 1x1GbE copper/SFP WAN port, 1x1GbE copper/SFP SFP port, 4x1GbE copper LAN ports, 802.11ax 2x2 MIMO Wi-Fi 7, 5G cellular	CPAP-SG2550-W-5G-SNBT
2560 Desktop form factor, 1x1GbE copper WAN port, 1x1GbE copper/SFP DMZ port, 8x1GbE copper LAN ports, 2x10GbE SFP+ LAN ports.	CPAP-SG2560-SNBT
2560 Desktop form factor, 1x1GbE copper WAN port, 1x1GbE copper/SFP DMZ port, 8x1GbE copper LAN ports, 2x10GbE SFP+ LAN ports, 802.11ax 4x4 MIMO Wi-Fi 7.	CPAP-SG2560W-SNBT
2570 Desktop form factor, 1x1GbE copper WAN port, 1x1GbE copper/SFP DMZ port, 8x1GbE copper LAN ports, 2x10GbE SFP+ LAN ports.	CPAP-SG2570-SNBT
2570 Desktop form factor, 1x1GbE copper WAN port, 1x1GbE copper/SFP DMZ port, 8x1GbE copper LAN ports, 2x10GbE SFP+ LAN ports, 802.11ax 4x4 MIMO Wi-Fi 7.	CPAP-SG2570W-SNBT
2570 Desktop form factor, 1x1GbE copper WAN port, 1x1GbE copper/SFP DMZ port, 8x1GbE copper LAN ports, 2x10GbE SFP+ LAN ports, 802.11ax 4x4 MIMO Wi-Fi 7, 5G cellular.	CPAP-SG2570-W-5G-SNBT
2580 half-sized rack mounted, 1x10GbE copper/SFP WAN port, 1x10GbE copper/SFP DMZ port, 8x1GbE and 2x2.5GbE copper LAN ports and Dual power supply.	CPAP-SG2580-SNBT

ACCESSORIES

Power Supplies	SKU
Replacement Power Supply for 2530, 2550 wired and Wi-Fi models	CPAC-2530/2550-PSU
Replacement Power Supply for 2550W5G, 2560, 2560W, 2570, 2570W, 2580, 3920, & 3950 models	CPAC-2550W5G/2580/3920/3950-PSU
Replacement Power Supply for 2570W5G models	CPAC-2570W5G-PSU

Rack Mounts	SKU
Rack Mount ears for 2530, 2550, 2560, 2570, 2580, 3920, 3950 models	CPAC-2500/3900-RM-EARS
Rack Mount shelf for Single/Dual for 2500/ 3600/ 3800 desktop appliances. The mount does not support Quantum Spark models with Wi-Fi	CPAP-2500/3900-RM-DUAL

Antennas	SKU
Replacement Wi-Fi and 5G antennas for 2530 and 2550 models. Contains four antennas (2+2)	CPAC-2550-ANTENNA
Replacement of 5G antennas for 2570 and 2590 models. Contains four antennas	CPAC-2570-ANTENNA

Transceivers	SKU
1GB Short Range Transceiver	CPAC-TR-1SX-D
1GB Long Range Transceiver	CPAC-TR-1LX-D
10GB Short Range Transceiver	CPAC-TR-10SR-D
10GB Long Range Transceiver	CPAC-TR-10LR-D

SUBSCRIPTION SERVICES

	NGFW	NGTP	SNBT (SandBlast)*
Application Control	✓	✓	✓
IPS	✓	✓	✓
URL Filtering		✓	✓
Anti-Bot		✓	✓
Anti-Virus		✓	✓
Anti-Spam		✓	✓
SandBlast Threat Emulation (sandboxing)			✓
Zero Phishing			✓
IoT Network Protection	IoT for SMB (Web UI and Spark Management) is included IoT for Enterprise (Smart1) requires an additional license		
SD-WAN Network Optimization**	SD-WAN for SMB (Web UI and Spark Management) is included SD-WAN for Enterprise (Smart1) requires an additional license		

*The first-year purchase includes the SNBT package. Security subscription renewals, NGFW, NGTP and SNBT are available for subsequent years.

**SD-WAN for Enterprise is pending availability of Central Management.

Worldwide Headquarters

5 Shlomo Kaplan Street, Tel Aviv 6789159, Israel | Tel: +972-3-753-4599

U.S. Headquarters

100 Oracle Parkway, Suite 800 Redwood City, CA 94065 | Tel: 1-800-429-4391

www.checkpoint.com

© 2025 Check Point Software Technologies Ltd. All rights reserved.