

Cisco 8010 Series Large Density Fixed Routers

Contents

Product overview	3
Key product highlights	3
Key attributes	4
Key software feature support	6
Supported transceiver modules	9
Regulatory standards compliance	9
Ordering information	11
Service and support	13
Warranty information	13
Product sustainability	13
Cisco Capital	13
Document history	14

Powered by the Cisco Silicon One™ A100 ASIC, the Cisco® 8010 Series Large Density Fixed Routers offer Class C timing support and end-to-end encryption, enabling seamless network growth and scalability. Built on the robust Cisco IOS® XR operating system, these routers are designed for use in dense metro access and preaggregation deployments, delivering both Capital Expenditure (CapEx) savings and enhanced operational simplicity.

Product overview

Building on the success of our Cisco 8000 Series Routers, which use the Cisco Silicon One™ ASIC, we are thrilled to introduce the Cisco 8010 Series, powered by the new A100 ASIC. This unified silicon architecture eliminates boundaries across a significant portion of the networking market, providing scalability from web-scale to service provider deployments. The Cisco 8010 Series offers versatile Ethernet interface options, ranging from 1G and 25G to 100G and 400G. These industrial-temperature devices support Class C timing and feature encryption capabilities, including MACsec at line rate on all ports and IPsec for data security.

Powered by the industry-leading, carrier-class version of Cisco IOS XR software, these routers are designed for operational efficiency and service agility. The Cisco 8010 Series uses the new Cisco IOS XR Flexible Consumption Model (FCM) 2.0, which consists of three main components: Hardware, Right to Use (RTU), and System-Level Software Innovation Access (SIA). For more details about FCM 2.0, please refer to the FCM 2.0 data sheet.

In line with our sustainability goals, these devices feature Gold-level efficient power supply units for improved power utilization and use minimal plastic labels and parts, helping to reduce your carbon footprint.

Key product highlights

- 1 Rack-Unit (1RU) fixed form factor
- Versatile Ethernet interface options: 1/10/25/50G and 40/100G/400G
- Low speed Ethernet options: 10/100/1000M
- G.8273.2 Class C Timing compliant
- Modular GNSS with Primary Reference Time Clock Class B (PRTC-B) for better performance
- MACsec and IPsec support for secure data communication¹
- Rich packet Ethernet Operations, Administration, and Management (OAM) capabilities, including Y.1564 SADT
- Power-optimized router with advanced algorithms for reduced Operating Expenses (OpEx)
- Suitable for indoor or outdoor cabinets: Sealed IP65/IP66 cabinet with heat exchanger conforming to GR487 specs with sufficient cooling
- Based on Cisco IOS XR [Flexible Consumption Model \(FCM\) 2.0](#)

¹ Feature available post FCS.




Figure 1.
Cisco 8011-4G24Y4H-I




Figure 2.
Cisco 8011-32Y8L2H2FH

Key attributes

Table 1. Key attributes of the 8011-4G24Y4H-I model

Chassis product ID	8011-4G24Y4H-I	8011-32Y8L2H2FH
CPU	4 cores 2.2GHz	4 cores 2.2GHz
Memory	16GB DRAM	16GB DRAM
Storage	38GB eMMC	38GB eMMC
Interfaces	4 ports 40/100G QSFP28 24 ports 1/10/25G SFP28 4 ports 10/100/1000M RJ-45	2 ports 400G QSFP56-DD 2 ports 100G QSFP28 8 ports 10/25/50G SFP56 32 ports 1/10/25G SFP28
Performance	Up to 500 Mpps	Up to 500 Mpps
Power supplies	Modular redundant (AC/DC)	Modular redundant (AC/DC)
Fans	Fixed fans with redundancy	Modular fans with redundancy
Airflow	Front to back	Front to back
Operating temperature range	I-Temp -40° to +65° C (-40° to +149° F)	C-Temp -5° to +55° C (+32° to +140° F)

Chassis product ID	8011-4G24Y4H-I	8011-32Y8L2H2FH
Non-operating (storage) temperature	-40° to +70° C (-40° to +158° F)	-40° to +70° C (-40° to +158° F)
Operating humidity range	5% to 95% RH, noncondensing	5% to 85% RH, noncondensing
Storage (relative) humidity	5% to 95% at 40° C (104° F) per NEBS GR-63-Core	5% to 95% at 40° C (104° F) for 96 hours as per NEBS GR-63-Core
Altitude	Up to 3960 meters (13,000 feet)	Up to 3960 meters (13,000 feet)
Power	Worldwide ranging AC (90 to 264V; 50 to 60 Hz) Worldwide ranging DC (-40.8V to -72V)	Worldwide ranging AC (90 to 264V; 50 to 60 Hz) Worldwide ranging DC (-40.8V to -72V)
Surge rating*	DC: 2kV CM, 1kV DM AC: 2kV CM, 2kV DM	DC: 2kV CM, 1kV DM AC: 4kV CM, 2kV DM
Timing ports	Time of Day (ToD) and Building Integrated Timing Supply (BITS) 8000-TIC: 1 PPS, 10 MHz 8000-TIC-GNSS (internal GNSS PRTC-B module): 1 PPS, 10 MHz, ANT	Time of Day (ToD) and Building Integrated Timing Supply (BITS) 8000-TIC: 1 PPS, 10 MHz 8000-TIC-GNSS (internal GNSS PRTC-B module): 1 PPS, 10 MHz, ANT
Physical specifications	Height: 43.6 mm (1.72 in.) Width: 439.4 mm (17.3 in.) Depth: 260 mm (10.24 in.) Weight: 4.5 kg (no PSU); 5.7 kg (with 2 PSUs)	Height: 43.6 mm (1.72 in.) Width: 439.4 mm (17.3 in.) Depth: 437 mm (17.2 in.) Weight: 6.7 kg (no PSU); 8.8 kg (with 2 PSUs)
Mounting options	19 in., 23 in., ETSI	19 in., 23 in., ETSI
Management interfaces	USB console port USB memory port RS-232 console port 10/100/1000M RJ-45 Ethernet out-of-band management port	USB console port USB memory port RS-232 console port 10/100/1000M RJ-45 Ethernet out-of-band management port

* Requires external surge protection devices for installations where higher surge levels are expected. Failure to do so might lead to permanent damage.

Key software feature support

Table 2. Key software feature support

Specification	Description
Layer 3	<ul style="list-style-type: none"> IPv4 and IPv6 unicast routing Virtual Routing and Forwarding (VRF) Open Shortest Path First (OSPF) v2, v3 Intermediate System to Intermediate System (IS-IS) for IPv4 and IPv6 Equal-Cost Multipath (ECMP) Virtual Router Redundancy Protocol (VRRP) Hot Standby Router Protocol (HSRP) Generic Routing Encapsulation (GRE) Policy-Based Routing (PBR) ACL-based Forwarding (ABF) L3 Virtual Private Network (L3VPN)
Layer 2	<ul style="list-style-type: none"> Ethernet Flow Point (EFP) Bridge Domains Virtual Private Wire Service (VPWS) Virtual Private LAN Service (VPLS) Ethernet VPN (EVPN) Ethernet VPN Virtual Private Wire Service (EVPN-VPWS)
Integrated Routing and Bridging (IRB)	<ul style="list-style-type: none"> Bridge Virtual Interfaces (BVI) Ethernet VPN IRB (EVPN-IRB)
MPLS	<ul style="list-style-type: none"> Multiprotocol Label Switching (MPLS) Label Distribution Protocol (LDP) MPLS Traffic Engineering (MPLS-TE) with RSVP-TE
Segment Routing (SR)	<ul style="list-style-type: none"> Segment Routing with MPLS data plane (SR-MPLS) Segment Routing with IPv6 data plane (SRv6) Segment Routing Traffic Engineering (SR-TE) Segment Routing Path Computation Element (SR-PCE) Topology-Independent Loop-Free Alternate (TI-LFA) Segment Routing On-Demand Next-Hop (SR-ODN) Segment Routing Performance Management (SR-PM) Segment Routing v6 Performance Management (SRv6-PM) Segment Routing Data Plane Monitoring (SR-DPM) Tree-SID Integrated Performance Monitoring (IPM)

Specification	Description
Multicast	IPv4 and IPv6 multicast routing Protocol Independent Multicast - Sparse Mode (PIM-SM) PIM - Source Specific Multicast (PIM-SSM) Internet Group Management Protocol (IGMP) v3 Multicast Listener Discovery (MLD) v2 Multicast Label Distribution Protocol (mLDP) MPLS Point-to-Multipoint Traffic Engineering (MPLS P2MP-TE) Next Generation multicast VPN (NG mVPN)
Quality of Service (QoS)	Virtual Output Queueing (VOQ) with deep packet buffering Class-based 3-level hierarchical QoS Policing, shaping, remarking Multilevel priority queuing Random Early Detection (RED), Weighted RED (WRED) Dual Queue Limit (DQL)
Timing	Enhanced Synchronous Ethernet (eSyncE) Enhanced Ethernet Synchronization Message Channel (eESMC) Internal PRTC-B GNSS receiver (optional HW module) External GNSS receiver IEEE 1588-2008 Precision Time Protocol (PTP): T-GM, T-BC, Virtual Port, A-PTS G.8275.1, G.8275.2, G.8265.1, G.8273.2 Class C Network Time Protocol (NTP)
Security	MACsec and IPsec Control Plane Protection (CoPP) Management Plane Protection (MPP) Local Packet Transport Services (LPTS) Authentication, Authorization, and Accounting (AAA) Access Control Lists (ACL) for IPv4, IPv6, and L2 BGP FlowSpec Unicast Reverse Path Forwarding (uRPF) 802.1X

Specification	Description
OAM	<p>Link Layer Discovery Protocol (LLDP)</p> <p>Cisco Discovery Protocol (CDP)</p> <p>Internet Control Message Protocol (ICMP)</p> <p>Dynamic Host Configuration Protocol (DHCP), DHCP Relay</p> <p>Bidirectional Forwarding Detection (BFD) v4, v6</p> <p>MPLS OAM</p> <p>Connectivity Fault Management (CFM)</p> <p>Y.1731 Delay Measurement (DM)</p> <p>Y.1731 Synthetic Loss Measurement (SLM)</p> <p>Two-Way Active Measurement Protocol (TWAMP, TWAMP Lite)</p> <p>IP SLA (Service-Level Agreement)</p> <p>NetFlow, sFlow, IPFIX 315</p> <p>Switch Port Analyzer (SPAN, ERSPAN, SPAN to file)</p> <p>Dying Gasp</p>
Manageability	<p>Command-Line Interface (CLI)</p> <p>SSH, Telnet, SCP, FTP, TFTP</p> <p>Simple Network Management Protocol (SNMP)</p> <p>Network Configuration Protocol (NETCONF)</p> <p>gRPC (Remote Procedure Calls)</p> <p>YANG models (OpenConfig, IETF)</p> <p>Model/event-Driven Telemetry (MDT)</p> <p>RPM-based software infrastructure</p> <p>Embedded Event Manager (EEM)</p> <p>Zero-Touch Provisioning (ZTP)</p> <p>Secure Zero-Touch Provisioning (sZTP)</p>

Note: Some features are not supported at FCS.

Supported transceiver modules

Please refer to the [Transceiver Module Group \(TMG\) Compatibility Matrix](#) for the transceivers supported by the 8010 Series.

Regulatory standards compliance

Table 3. Regulatory standards compliance

Specification	8010 Series Large Density Routers
Regulatory compliance	Products comply with CE Markings according to directives 2014/30/EU and 2014/35/EU
Network Equipment Building Standards (NEBS)	GR-63-CORE GR-1089-CORE 8011-32Y8L2H2FH: GR-3108 Class-1 8011-4G24Y4H-I: GR-3108 Class-2
ATIS TEER certification	ATIS-0600015.03.2009
Safety	ANSI / UL 60950-1 CAN/CSA C22.2 No. 60950-1 ANSI / UL 62368-1 CAN/CSA C22.2 No. 62368-1 EN / IEC 62368-1
EMC standards (Emissions)	47 CFR Part 15:2016 CISPR32:2012:Ed:1 CISPR32:2015:Ed:2 CNS 15936:2016 EN 55032:2012 EN 55032:2015 EN 61000-3-3:2013+A1:2019 EN IEC 61000-3-2:2019+A1:2020 EN300 386:2012:V1.6.1 EN300 386:2021:V2.1.23 ICES-003:2020:Iss:7 KS C 9610-3-2:2020 KS C 9610-3-3:2020 KS C 9832:2019 VCCI-CISPR 32:2016 1TR9:2016 EN50121-4:2016 EN50121-4:2016:A1:2019 IEC62236-4:2018:Ed:3.0

Specification	8010 Series Large Density Routers
	TEC 11016:2016_TEC/SD/DD/EMC-221/05/OCT16 EN 301 489-1:2019:V2.2.3 EN 301 489-19:2022:V:2.2.1
EMC standards (Immunity)	CISPR24:2010+A1:2015 CISPR35:2016:Ed:1 EN 55035:2017 EN IEC61000-6-1:2019 EN300 386:2012:V1.6.1 EN300 386:2021:V2.1.23 EN61000-6-1:2007 EN61000-6-2:2005 EN61000-6-2:2019 IEC61000-6-1:2016:Ed:3 IEC61000-6-2:2016:Ed:3 KS C 9835:2019 1TR9:2005 1TR9:2016 EN50121-4:2016 EN50121-4:2016:A1:2019 IEC62236-4:2018:Ed:3.0 TEC 11016:2016_TEC/SD/DD/EMC-221/05/OCT16 EN 301 489-1:2019:V2.2.3 EN 301 489-19:2022:V:2.2.1
ETSI	ETS/EN 300 119 Part 4 ETS/EN 300 019 - Storage: Class 1.2, Transportation: Class 2.3, In-Use/Operational: Class 3.2 ETS/EN 300 753
RoHS	The product is RoHS-6 compliant with exceptions for leaded-Ball Grid-Array (BGA) balls and lead press-fit connectors.

Ordering information

Table 4. Ordering information

Router product ID	8011-4G24Y4H-I	8011-32Y8L2H2FH
Description	Cisco 8010 4x1G Cu, 24x25G, 4x100G QSFP28	Cisco 8010 32x25G, 8x50G, 2x100G QSFP28, 2x400G QDD
Power supply for AC variant	PWR-400-AC	PWR-650-AC-R
Power supply for DC variant	PWR-400-DC	PWR-930-DC-R
Fans	Not Applicable	FAN-1RU-PI-V3
Timing card	8000-TIC 8000-TIC-GNSS (optional)	8000-TIC 8000-TIC-GNSS (optional)
FCS software	Cisco IOS XR 25.1.1	Cisco IOS XR 25.4.1

Table 5. Accessory kit for 8011-4G24Y4H-I

Accessories	Description
CBL-BRKT-V1	Cable Management Bracket for 8010 Series
RCKMT-19-V1	19-inch Rack Mounting Kit for 8010 Series
RCKMT-ETSI-V1	21-inch (ETSI) Rack Mounting Kit for 8010 Series
RCKMT-23-V1	23-inch Rack Mounting Kit for 8010 Series

Table 6. Accessory kit for 8011-32Y8L2H2FH

Product ID	Description
CBL-BRKT-V2	Cable Management Bracket for 8010 Series Router
RCKMT-19-KIT1	2 Post 19-inch Rack Mounting Kit for 8010 Series
RCKMT-19-KIT2	4 Post 19-inch Rack Mounting Kit for 8010 Series
RCKMT-ETSI-KIT1	2 Post 21-inch (ETSI) Rack Mounting Kit for 8010 Series
RCKMT-ETSI-KIT2	4 Post 21-inch (ETSI) Rack Mounting Kit for 8010 Series
RCKMT-23-KIT1	2 Post 23-inch Rack Mounting Kit for 8010 Series
RCKMT-23-KIT2	4 Post 23-inch Rack Mounting Kit for 8010 Series
CAB-48DC-40A-8AWG	C-Series -48VDC PSU Power Cord, 3.5M, 3 Wire, 8AWG, 40A

Table 7. Ordering information for software licenses available on Cisco 8010 Series

Product ID	Description
ESS-NGA-10G-RTU	Access Network SW&Autom Ess 1.0 Perp RTU (per 10G)
ADN-NGA-10G-RTU	Access Network SW&Autom Adn 1.0 Perp RTU (per 10G)
PRM-NGA-10G-RTU	Access Network SW&Autom Prm 1.0 Perp RTU (per 10G)
NGA-L-SIA-3	SIA per system for 3 years - Large
NGA-L-SIA-5	SIA per system for 5 years - Large

Table 8. Ordering information for power cables supported

Part number	Description
CAB-AC-SA	Power Cord - South Africa, 16/10A, 250V, 1830mm, -40C to +85C
CAB-AC-ARG	Power Cord - Argentina, 10A, 250V, 2500mm, -40C to +85C
CAB-AC-ISR	Power Cord - Israel, 16/10A, 250V, 2500mm, -40C to +85C
CAB-AC-TAI	Power Cord - Taiwan, 15/10A, 125V, 2500mm, -40C to +85C
CAB-AC-CHI	Power Cord - China, 10A, 250V, 2500mm, -40C to +85C
CAB-AC-KOR	Power Cord - Korea, 16/10A, 125V, 2500mm, -40C to +85C
CAB-AC-EUR	Power Cord - Europe, 16/10A, 250V, 2500mm, -40C to +85C
CAB-AC-ITL	Power Cord - Italy, 10A, 250V, 2500mm, -40C to +85C
CAB-AC-UK	Power Cord - UK, 13/10A, 250V, 2500mm, -40C to +85C
CAB-AC-AUS	Power Cord - Australia, 10A, 250V, 2500mm, -40C to +85C
CAB-AC-US	Power Cord - US, 15A, 125V, 2500mm, -40C to +85C
CAB-AC-BRA	Power Cord - Brazil, 10A, 250V, 2500mm, -40C to +85C
CAB-AC-IND	Power Cord - India, 16/10A, 250V, 2500mm, -40C to +85C
CAB-AC-SUI	Power Cord - Swiss, 10A, 250V, 2500mm, -40C to +85C

Service and support

Cisco offers a wide range of services to help accelerate your success in deploying and optimizing the Cisco 8010 Series. These innovative [Cisco Customer Experience \(CX\)](#) offerings are delivered through a unique combination of people, processes, tools, and partners, and they are focused on helping you increase operating efficiency and improve your network operation. Cisco CX helps you resolve mission-critical problems with direct access at any time to Cisco network experts and award-winning resources. Spanning the entire network lifecycle, Cisco CX offerings help increase investment protection, optimize network operations, support migration operations, and strengthen your IT expertise.

Warranty information

The Cisco 8010 Series Large Density Fixed Routers has a 1-year limited hardware warranty. The warranty includes hardware replacement with a 10-day turnaround from receipt of a Return Materials Authorization (RMA).

Product sustainability

Information about Cisco's Environmental, Social, and Governance (ESG) initiatives and performance is provided in Cisco's CSR and sustainability [reporting](#).

Table 9. Cisco environmental sustainability information

Sustainability Topic		Reference
General	Information on product-material-content laws and regulations	Materials
	Information on electronic waste laws and regulations, including our products, batteries, and packaging	WEEE Compliance
	Information on product takeback and reuse program	Cisco Takeback and Reuse Program
	Sustainability inquiries	Contact: csr_inquiries@cisco.com
Material	Product packaging weight and materials	Contact: environment@cisco.com

Cisco Capital

Flexible payment solutions to help you achieve your objectives

Cisco Capital® makes it easier to get the right technology to achieve your objectives, enable business transformation and help you stay competitive. We can help you reduce the total cost of ownership, conserve capital, and accelerate growth. In more than 100 countries, our flexible payment solutions can help you acquire hardware, software, services and complementary third-party equipment in easy, predictable payments. [Learn more](#).

Document history

New or revised topic	Described In	Date
Updated key attributes	Table 1. Key attributes of the 8011-4G24Y4H-I mode	October 10, 2025

Americas Headquarters
Cisco Systems, Inc.
San Jose, CA

Asia Pacific Headquarters
Cisco Systems (USA) Pte. Ltd.
Singapore

Europe Headquarters
Cisco Systems International BV Amsterdam,
The Netherlands

Cisco has more than 200 offices worldwide. Addresses, phone numbers, and fax numbers are listed on the Cisco Website at <https://www.cisco.com/go/offices>.

Cisco and the Cisco logo are trademarks or registered trademarks of Cisco and/or its affiliates in the U.S. and other countries. To view a list of Cisco trademarks, go to this URL: <https://www.cisco.com/go/trademarks>. Third-party trademarks mentioned are the property of their respective owners. The use of the word partner does not imply a partnership relationship between Cisco and any other company. (1110R)