

Meraki Go Security Gateway

GX20

<p>Performance</p> <hr/> <ul style="list-style-type: none">• Firewall Throughput - 250 Mbps• Recommended for 50 clients or fewer	<p>Interfaces</p> <hr/> <ul style="list-style-type: none">• WAN Interface: 1x 10/100/1000 BASE-T Ethernet (RJ45)• LAN interfaces: 4x 10/100/1000 BASE-T Ethernet (RJ45)• PoE: 1x 802.3af enabled port (15.5W)
<p>Network and Security Services</p> <hr/> <ul style="list-style-type: none">• Stateful firewall• Port Forwarding	<p>Environment</p> <hr/> <ul style="list-style-type: none">• Operating temperature: 32 °F to 104 °F (0 °C to 40 °C)

<ul style="list-style-type: none"> • DHCP services • DNS based security powered by Cisco Umbrella (additional subscription required) 	<ul style="list-style-type: none"> • Humidity: 5 to 95% non-condensing • Kensington lock hard point
<p>Power</p> <hr/> <ul style="list-style-type: none"> • 50W (54V / 0.92 A) Power Supply Included 	<p>LED Indicators</p> <hr/> <ul style="list-style-type: none"> • 2 Ethernet status • 1 power/booting/firmware upgrade status
<p>Physical Dimensions</p> <hr/> <ul style="list-style-type: none"> • 6.83" x 4.41" x 1.0.4" (173.4mm x 112mm x 26.3mm), not including deskmount feet or mount plate 	<p>Warranty</p> <hr/> <ul style="list-style-type: none"> • 1 year hardware warranty
<p>In the Box</p> <hr/> <ul style="list-style-type: none"> • GX20-HW: Meraki Go Security Gateway • Wall mount and screw kit • Quick start guide • PSU and ethernet cable 	<p>Model List / Accessories</p> <hr/> <p>GX20-HW-XX Security Gateway - Desktop</p> <p>GA-PWR-50WAC 50W Replacement Laptop Style Adapter for GX20</p> <p>XX = US/UK/EU</p>

Cisco Systems, Inc. | 500 Terry A. Francois Blvd, San Francisco, CA 94158 | (415) 432-1000 | help@meraki-go.com