

# MR66

Dual-Radio Outdoor  
802.11n Access Point



## High performance, ruggedized, outdoor cloud-managed wireless LAN

The Meraki MR66 is an enterprise class, dual-concurrent 802.11n cloud managed access point designed for high-density deployments in harsh outdoor locations and industrial indoor environments. The MR66 features dual-concurrent, dual-band operation and advanced 802.11n technologies such as MIMO and beamforming, delivering the high capacity, throughput and reliable coverage required by the most demanding business applications, even in harsh environments.

### MR66 and Meraki Cloud Management: A Powerful Combination

The MR66 is managed via the Meraki cloud, with an intuitive browser-based interface that lets you get up and running quickly without training or certifications. Since the MR66 is self-configuring and managed over the web, it can even be deployed at a remote location without on-site IT staff.

The MR66 is monitored 24x7 via the cloud, which delivers real-time alerts if your network encounters problems. Remote diagnostics tools also enable real-time troubleshooting over the web.

The MR66's firmware is always kept up to date from the cloud. New features, bug fixes, and enhancements are delivered seamlessly over the web, so you never have to manually download software updates or worry about missing security patches.

### Product Highlights

- Ideal for outdoor and industrial indoor environments
- Dual-concurrent 802.11n radios with up to 600 Mbps throughput
- Point-to-point links with optional panel antennas
- High performance multi-radio mesh routing
- Layer 7 application fingerprinting and QoS
- Built-in enterprise security, guest access, and NAC
- Self-configuring, plug-and-play deployment
- Automatic cloud-based RF optimization with spectrum analysis
- Real-time WIPS with Air Marshal

# Recommended Use Cases

## Outdoor coverage for high client density corporate campuses, educational institutions, and parks

- Provide high-speed access to a large number of clients
- Point-to-multi-point mesh

## Indoor coverage for industrial areas (e.g., warehouses, manufacturing facilities)

- Reliable coverage for scanner guns, security cameras, and POS devices
- High speed-access for iPads, tablets and laptops

## Long distance point-to-point

- Build a long-distance bridge between two networks
- Two MR66s can establish up to a 20 km link using high-gain antennas

# Features

## Dual enterprise class 802.11n radios, up to 600 Mbps

The MR66 features two powerful radios and advanced RF design for enhanced receive sensitivity. Combined with 802.11n technologies including MIMO and beamforming, the MR66 delivers up to 600 Mbps throughput and up to 50% increased capacity compared to typical rugged enterprise-class 802.11g access points, meaning fewer access points are required for a given deployment. In addition, dual-concurrent 802.11n radios and band steering technology allow the MR66 to automatically serve legacy 802.11b/g clients using the 2.4 GHz radio and newer 802.11n clients using the 5 GHz radio, thus providing maximum speed to all clients.

## Rugged industrial design

The MR66 is designed and tested for salt spray, vibration, extreme thermal conditions, shock and dust and is IP67-rated, making it ideal for extreme environments. Despite its rugged design, MR66 has a low profile and is easy to deploy.

## Application-aware traffic shaping

The MR66 includes an integrated layer 7 packet inspection, classification, and control engine, enabling you to set QoS policies based on traffic type. Prioritize your mission critical applications, while setting limits on recreational traffic, e.g. peer-to-peer and video streaming.

## Automatic cloud-based RF optimization with spectrum analysis

The MR66's sophisticated, automated RF optimization means that there is no need for the dedicated hardware or RF expertise typically required to tune a wireless network. An integrated spectrum analyzer monitors the airspace for neighboring WiFi devices as well as non-802.11 interference – microwave ovens, Bluetooth headsets, etc. The Meraki cloud then automatically optimizes the MR66's channel selection, transmit power, and client connection settings, providing optimal performance even under challenging RF conditions.

## Integrated enterprise security and guest access

The MR66 features integrated, easy-to-configure security technologies to provide secure connectivity for employees and guests alike. Advanced security features such as AES hardware-

based encryption and WPA2-Enterprise authentication with 802.1X and Active Directory integration provide wire-like security with the convenience of wireless mobility. One-click guest isolation provides secure, Internet-only access for visitors. Our policy firewall (Identity Policy Manager) enables group or device-based, granular access policy control. PCI compliance reports check network settings against PCI requirements to simplify secure retail deployments.

## Secure wireless environments using Air Marshal

Meraki wireless comes equipped with Air Marshal, a built-in wireless intrusion prevention system (WIPS) for threat detection and attack remediation. APs will scan their environment opportunistically or in real-time based on intuitive user-defined preferences. Alarms and auto-containment of malicious rogue APs are configured via flexible remediation policies, ensuring optimal security and performance in even the most challenging wireless environments.

## High performance mesh

The MR66's advanced mesh technologies like multi-channel routing protocols and multiple gateway support enable scalable, high throughput coverage of hard-to-wire areas with zero configuration. Mesh also improves network reliability - in the event of a switch or cable failure, the MR66 will automatically revert to mesh mode, providing continued gateway connectivity to clients.

## Self-configuring, self-optimizing, self-healing

When plugged in, the MR66 automatically connects to the Meraki cloud, downloads its configuration, and joins your network. It self optimizes, determining the ideal channel, transmit power, and client connection parameters. It also self heals, responding automatically to switch failures and other errors.

## Low profile, environmentally friendly design

In addition to eliminating excess packaging and documentation, 90% of the access point materials are recyclable. A maximum power draw of only 10.5 watts and a cloud-managed architecture mean that pollution, material utilization and your electric bill are kept to a minimum.

# Specifications

## Radio

One 802.11b/g/n and one 802.11a/n radio

Dual concurrent operation in 2.4 and 5 GHz bands

Max throughput rate 600 Mbit/s

2.4 GHz 26 dBm peak transmission power

5 GHz 24 dBm peak transmission power

Max transmission power is decreased for certain geographies to comply with local regulatory requirements

Operating bands:

### FCC (US)

2.412-2.484 GHz

5.150-5.250 GHz (UNII-1)

5.725 -5.825 GHz (UNII-3)

### EU (Europe)

2.412-2.484 GHz

5.470-5.600, 5.660-5.725 GHz (UNII-2)

## 802.11n Capabilities

2 x 2 multiple input, multiple output (MIMO) with two spatial streams

Maximal ratio combining (MRC)

Beamforming

Packet aggregation

Cyclic shift diversity (CSD) support

## Power

Power over Ethernet: 24 - 57 V (802.3af compatible)

Power consumption: 10.5 W max

Power over Ethernet injector sold separately

## Mounting

Mounts to walls and horizontal and vertical poles

Mounting hardware included

## Physical Security

Security screw included

## Environment

Operating temperature: -4°F to 122°F (-20°C to 50°C)

IP67 environmental rating

## Physical Dimensions

10.5" x 7.6" x 2.2" (267mm x 192mm x 57mm)

Weight: 1.9 lb (862g)

## Interfaces

1x 100/1000 Base-T Ethernet (RJ45) with 48V DC 802.3af PoE

Four external N-type antenna connectors

## Security

Integrated policy firewall (Identity Policy Manager)

Mobile device policies

Air Marshal: Real-time WIPS (wireless intrusion prevention system) with alarms

Rogue AP containment

Guest isolation

Teleworker VPN with IPsec

PCI compliance reporting

WEP, WPA, WPA2-PSK, WPA2-Enterprise with 802.1X

TKIP and AES encryption

VLAN tagging (802.1q)

## Quality of Service

Wireless Quality of Service (WMM/802.11e)

DSCP (802.1p)

Layer 7 application traffic shaping and firewall

## Mobility

PMK and OKC credential support for fast Layer 2 roaming

L3 roaming

## LED Indicators

4 signal strength

1 Ethernet connectivity

1 power/booting/firmware upgrade status

## Regulatory

FCC (US), IC (Canada), CE (Europe), C-Tick (Australia/New Zealand)

Anatel (Brazil), Cofetel (Mexico), TK (Turkey)

RoHS

## Mean Time Between Failure (MTBF)

450,000 hours

## Warranty

1 year hardware warranty with advanced replacement included

## Ordering Information

MR66-HW: Meraki MR66 Cloud-Managed Dual-Radio 802.11n Ruggedized Access Point

POE-INJ-3-XX: Meraki 802.3af Power over Ethernet Injector (XX = US, EU, UK or AU)

ANT-10: Meraki 5/7 dBi Omni Antenna, Dual-band, N-type, Set of 2

ANT-11: Meraki 14 dBi Sector Antenna, 5 GHz MIMO, N-type

ANT-13: Meraki 11 dBi Sector Antenna, 2.4 GHz MIMO, N-type

Note: Meraki Enterprise license required.

### RF Performance Table

Maximum hardware capability shown. Transmit power is configurable in increments of 1 dB and is automatically limited by the Meraki cloud to comply with local regulatory settings.

Operating Band	Operating Mode	Data Rate	TX Power (dBm)	RX Sensitivity
2.4 GHz	802.11b	1 Mb/s	23	-96
		2 Mb/s	23	-94
		5.5 Mb/s	22	-95
		11 Mb/s	21	-92
2.4 GHz	802.11g	6 Mb/s	20	-95
		9 Mb/s	26	-94
		12 Mb/s	25	-93
		18 Mb/s	25	-93
		24 Mb/s	24	-90
		36 Mb/s	24	-87
		48 Mb/s	23	-83
54 Mb/s	21	-81		
2.4 GHz	802.11n (HT20)	MCS0/8 HT20	22	-96
		MCS1/9 HT20	22	-94
		MCS2/10 HT20	21	-92
		MCS3/11 HT20	21	-89
		MCS4/12 HT20	21	-85
		MCS5/13 HT20	21	-82
		MCS6/14 HT20	20	-81
		MCS7/15 HT20	19	-79
2.4 GHz	802.11n (HT40)	MCS0/8 HT40	21	-93
		MCS1/9 HT40	21	-91
		MCS2/10 HT40	21	-89
		MCS3/11 HT40	21	-86
		MCS4/12 HT40	21	-82
		MCS5/13 HT40	21	-79
		MCS6/14 HT40	19	-78
MCS7/15 HT40	18	-77		
5 GHz	802.11a	6 Mb/s	24	-97
		9 Mb/s	24	-96
		12 Mb/s	23	-94
		18 Mb/s	23	-92
		24 Mb/s	22	-90
		36 Mb/s	21	-87
		48 Mb/s	20	-85
54 Mb/s	20	-83		
5 GHz	802.11n (HT20)	MCS0/8 HT20	23	-98
		MCS1/9 HT20	23	-96
		MCS2/10 HT20	22	-93
		MCS3/11 HT20	21	-90
		MCS4/12 HT20	21	-84
		MCS5/13 HT20	20	-82
		MCS6/14 HT20	19	-80
MCS7/15 HT20	15	-79		
5 GHz	802.11n (HT40)	MCS0/8 HT40	23	-94
		MCS1/9 HT40	22	-93
		MCS2/10 HT40	21	-91
		MCS3/11 HT40	20	-88
		MCS4/12 HT40	19	-85
		MCS5/13 HT40	18	-81
		MCS6/14 HT40	18	-78
MCS7/15 HT40	14	-76		