

HP 6600 Router Series



Key features

- High-performance WAN routing
- Multicore distributed or centralized processing
- Comprehensive routing, switching, and security
- Embedded hardware encryption
- Robust high availability and resiliency

Product overview

The HP 6600 Router Series is a family of high-performance WAN routers that is ideal for campus and data center WAN edge and aggregation deployments.

These routers are built with a multicore architecture offering distributed or centralized processing to help balance performance and cost. The 6600 Router Series delivers robust routing, security, full Layer 2 switching, and modular high-density WAN and LAN interface options, all integrated in a single high-performance routing platform.

In addition, the HP 6600 Router Series features robust carrier-class reliability capabilities to help reduce disruption from network or system failures.

Features and benefits

Quality of Service (QoS)

- Traffic policing
 - supports Committed Access Rate (CAR) and line rate
- Congestion management
 - supports FIFO, PQ, CQ, WFQ, CBQ, and RTPQ

- Other QoS technologies

support traffic shaping, FR QoS, MPLS QoS, and MP QoS/LFI

- Congestion avoidance

weighted random early detection (WRED)/random early detection (RED)

Management

- Management interface control

provides management access through modem port and terminal interface, as well as in-band and out-of-band Ethernet ports

- Management security

includes multiple administration levels, with password protection and restricted access to critical configuration commands; access control lists (ACLs) provide telnet and SNMP access; local and remote syslog capability allows logging of all access

- SNMP v1, v2, and v3

provides complete support of SNMP, as well as full support of industry-standard MIBs and private MIB extensions

- Industry-standard CLI with a hierarchical structure

reduces training needs and increases productivity in multivendor installations

- Remote monitoring (RMON)

uses standard SNMP to monitor essential network functions; supports events, alarm, history, and statistics group plus a private alarm extension group

- Debug and sampler utility

supports ping and traceroute for both IPv4 and IPv6

- Network Quality Analyzer (NQA)

analyzes network performance and service quality by sending test packets, and provides network performance and service quality parameters such as jitter, TCP, or FTP connection delays and file transfer rates; allows a network manager to determine overall network performance and to diagnose and locate network congestion points or failures

- Network Time Protocol (NTP)

synchronizes timekeeping among distributed time servers and clients; keeps timekeeping consistent among all clock-dependent devices within the network so that the devices can provide diverse applications based on the consistent time

- Information center

provides a central repository for system and network information; aggregates all logs, traps, and debugging information generated by the system and maintains them in order of severity; outputs the network information to multiple channels based on user-defined rules

- FTP and TFTP support

File Transfer Protocol allows bidirectional transfers over a TCP/IP network and is used for configuration updates; Trivial FTP is a simpler method using User Datagram Protocol (UDP)

- Loopback

supports internal loopback testing for maintenance purposes and high availability; loopback detection protects the system from incorrect cabling or network configurations and can be enabled on a port or VLAN

- Internet Group Management Protocol (IGMP)

is used by IP hosts to establish and maintain multicast groups; supports v1, v2, and v3; utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks

Connectivity

- High port density

provides up to 16 interface module slots, and high-density Ethernet interface cards; a single card can provide up to 48 GbE interfaces, which enables the routers to fully satisfy the demands of high-density Ethernet (MSTP) link distribution
- Multiple WAN interfaces

support Fast Ethernet/Gigabit Ethernet/10GbE ports, OC3~OC48 POS/CPOS, and ATM ports
- Flexible port selection

provides a combination of fiber and copper interface modules, 100/1000BASE-X auto speed selection, and 10/100/1000BASE-T auto speed detection plus auto duplex and MDI/MDI-X; speed is adaptable between 155 M POS and 622 M POS

Performance

- Industry-leading performance

provides up to 252 Mpps forwarding performance
- Flexible chassis selection

consists of 4 models: 16 HIM-slot chassis, 8 HIM-slot chassis, 4 HIM-slot chassis, and 2 HIM-slot chassis
- Scalable system design

backplane is designed for smooth bandwidth upgrade

Resiliency and high availability

- Separate data and control planes

provide greater flexibility and enable continual services
- Hitless software upgrades

allow patches to be installed without restarting the device, increasing network uptime and simplifying maintenance
- Redundant design of main processing unit and power supply

increases the overall system availability
- Virtual Router Redundancy Protocol (VRRP)

enables fast convergence of routes and packet forwarding when links fail, ensuring high network availability
- IP Fast Reroute Framework (FRR)

nodes are configured with backup ports and routes; local implementation requires no cooperation of adjacent devices, simplifying the deployment; solves the traditional convergence faults in IP forwarding; provides restoration within 50 ms, with the restoration time independent of the number of routes and fast link switchovers without route convergence
- Graceful restart

features are fully supported, including graceful restart for OSPF, IS-IS, Border Gateway Protocol (BGP), LDP, and RSVP; network remains stable during the active-standby switchover; after the switchover, the device quickly learns the network routes by communicating with adjacent routers; forwarding remains uninterrupted during the switchover to realize nonstop forwarding (NSF)
- Hot-swappable modules

facilitates the replacement of hardware interface modules without impacting the traffic flow through the system

Layer 3 services

- Address Resolution Protocol (ARP)

determines the MAC address of another IP host in the same subnet; supports static ARPs; gratuitous ARP allows detection of duplicate IP addresses; proxy ARP allows normal ARP operation between subnets or when subnets are separated by a Layer 2 network

- User Datagram Protocol (UDP) helper
 - redirects UDP broadcasts to specific IP subnets to prevent server spoofing
- Dynamic Host Configuration Protocol (DHCP)
 - simplifies the management of large IP networks and supports client and server; DHCP Relay enables DHCP operation across subnets
- Domain Name System (DNS)
 - provides a distributed database that translates domain names and IP addresses, which simplifies network design; supports client and server

Layer 3 routing

- Static IPv4 routing
 - provides simple manually configured IPv4 routing
- Routing Information Protocol (RIP)
 - uses a distance vector algorithm with UDP packets for route determination; supports RIPv1 and RIPv2 routing; includes loop protection
- Open shortest path first (OSPF)
 - delivers faster convergence; uses this link-state routing Interior Gateway Protocol (IGP), which supports ECMP, NSSA, and MD5 authentication for increased security and graceful restart for faster failure recovery
- Intermediate system to intermediate system (IS-IS)
 - uses a path vector Interior Gateway Protocol (IGP), which is defined by the ISO organization for IS-IS routing and extended by IETF RFC 1195 to operate in both TCP/IP and the OSI reference model (Integrated IS-IS)
- Static IPv6 routing
 - provides simple manually configured IPv6 routing
- Dual IP stack
 - maintains separate stacks for IPv4 and IPv6 to ease the transition from an IPv4-only network to an IPv6-only network design
- Routing Information Protocol next generation (RIPng)
 - extends RIPv2 to support IPv6 addressing
- OSPFv3
 - provides OSPF support for IPv6
- BGP+
 - extends BGP-4 to support Multiprotocol BGP (MBGP), including support for IPv6 addressing
- IS-IS for IPv6
 - extends IS-IS to support IPv6 addressing
- IPv6 tunneling
 - allows IPv6 packets to traverse IPv4-only networks by encapsulating the IPv6 packet into a standard IPv4 packet; supports manually configured, 6to4, and Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) tunnels; is an important element for the transition from IPv4 to IPv6
- Multiprotocol Label Switching (MPLS)
 - uses BGP to advertise routes across Label Switched Paths (LSPs), but uses simple labels to forward packets from any Layer 2 or Layer 3 protocol, which reduces complexity and increases performance; supports graceful restart for reduced failure impact; supports LSP tunneling and multilevel stacks
- Multiprotocol Label Switching (MPLS) Layer 3 VPN
 - allows Layer 3 VPNs across a provider network; uses MP-BGP to establish private routes for increased security; supports RFC 2547bis multiple autonomous system VPNs for added flexibility

- Multiprotocol Label Switching (MPLS) Layer 2 VPN

establishes simple Layer 2 point-to-point VPNs across a provider network using only MPLS Label Distribution Protocol (LDP); requires no routing and therefore decreases complexity, increases performance, and allows VPNs of non-routable protocols; uses no routing information for increased security; supports Circuit Cross Connect (CCC), Static Virtual Circuits (SVCs), Martini draft, and Kompella-draft technologies

- Policy routing

allows custom filters for increased performance and security; supports ACLs, IP prefix, AS paths, community lists, and aggregate policies

- Multicast VPN

supports Multicast Domain (MD) multicast VPN, which can be distributed on separate service cards, providing high performance and flexible configuration

- Border Gateway Protocol 4

Exterior Gateway Protocol (EGP) with path vector protocol uses TCP for enhanced reliability for the route discovery process, reduces bandwidth consumption by advertising only incremental updates, and supports extensive policies to increase flexibility and scale to large networks

- OSPFv3 MCE

Multi-VPN-Instance CE (MCE) binds different VPNs to different interfaces on one single CE; the OSPFv3 MCE feature creates and maintains separate OSPFv3 routing tables for each IPv6 VPN to isolate VPN services in the device

Security

- Access control list

supports powerful ACLs for both IPv4 and IPv6; ACLs are used for filtering traffic to prevent illegal users from accessing the network or for controlling network traffic flow; rules can either deny or permit traffic to be forwarded; rules can be based on a Layer 2 header or a Layer 3 protocol header; rules can also be set to operate on specific dates or times

- Remote Authentication Dial-In User Service (RADIUS)

eases switch security access administration by using a password authentication server

- Terminal Access Controller Access-Control System (TACACS+) delivers an authentication tool using TCP with encryption of the full authentication request, providing additional security

- Network address translation (NAT)

supports repeated multiplexing of a port and automatic 5-tuple collision detection, enabling NAPT to support unlimited connections; supports blacklist in NAT/NAPT/internal server, a limit on the number of connections, session log, and multi-instance

- Secure shell (SSHv2)

uses external servers to securely log in to a remote device; with authentication and encryption, it protects against IP spoofing and plain-text password interception; increases the security of Secure FTP (SFTP) transfers

- Unicast Reverse Path Forwarding (URPF)

allows normal packets to be forwarded correctly, but discards the attaching packet due to lack of reverse path route or incorrect inbound interface; prevents source spoofing and distributed attacks; supports distributed URPF

- Dynamic Virtual Private Network (DVPN)

collects, maintains, and distributes dynamic public addresses through the VPN Address Management (VAM) protocol, making VPN establishment available between enterprise branches that use dynamic addresses to access the public network; compared to traditional VPN technologies, DVPN technology is more flexible and has richer features, such as NAT traversal of DVPN packets, AAA identity authentication, IPSec protection of data packets, and multiple VPN domains

Multicast support

- Internet Group Management Protocol (IGMP)
is used by IP hosts to establish and maintain multicast groups; supports v1, v2, and v3; utilizes Any-Source Multicast (ASM) or Source-Specific Multicast (SSM) to manage IPv4 multicast networks
- Protocol Independent Multicast (PIM)
is used for IPv4 and IPv6 multicast applications; supports PIM Dense Mode (PIM-DM), Sparse Mode (PIM-SM), and Source-Specific Mode (PIM-SSM)
- Multicast Source Discovery Protocol (MSDP)
is used for interdomain multicast applications, allowing multiple PIM-SM domains to interoperate
- Multicast Border Gateway Protocol (MBGP)
allows multicast traffic to be forwarded across BGP networks separately from unicast traffic

Integration

- Embedded VPN firewall
provides enhanced stateful packet inspection and filtering; provides advanced VPN services with 3DES and AES encryption at high performance and low latency
- Open Application Architecture (OOA)
provides both software and hardware platforms based on open standards so that third-party applications can be integrated seamlessly into routers

Additional information

- Green initiative support
provides support for RoHS and WEEE regulations

Product architecture

- Multicore CPU
delivers multi-threaded processing, with eight cores and 32 hardware threads
- Distributed processing
the main processing engine and service engine have separate hardware for high performance and parallel processing; the main processing engine is used for route calculation and system management, while the service engine is used for service processing
- Separate FIP card and interface card
interface cards are separated from the FIP card to support flexible service configurations

Warranty and support

- 1-year Warranty 2.0
advance hardware replacement with 10-calendar-day delivery (available in most countries)
- Electronic and telephone support (for Warranty 2.0)
limited electronic and 24x7 telephone support is available from HP for the entire warranty period; to reach our support centers, refer to hp.com/networking/contact-support; for details on the duration of support provided with your product purchase, refer to hp.com/networking/warrantysummary
- Software releases
to find software for your product, refer to hp.com/networking/support; for details on the software releases available with your product purchase, refer to hp.com/networking/warrantysummary

HP 6600 Router Series

Specifications



	HP 6602 Router (JC176A)	HP 6604 Router Chassis (JC178B)
I/O ports and slots	2 HIM slots	4 HIM slots or 2 SAP slots, or a combination
Additional ports and slots		2 MPU (for management modules) slots
Physical characteristics		
Weight	17.40(w) x 18.11(d) x 1.73(h) in (44.2 x 46 x 4.4 cm) (1U height)	17.17(w) x 18.9(d) x 8.66(h) in (43.61 x 48.01 x 22 cm) (5U height)
Full configuration weight	16.53 lb (7.5 kg)	83.77 lb (38 kg) 83.77 lb (38 kg)
Memory and processor	Multi-core MIPS @ 1000 MHz, 2 GB DDR2 SDRAM, 4 GB DDR2 SDRAM, 256 MB flash, 1 GB flash; packet buffer size: 128 MB DDR2 SDRAM	
Mounting and enclosure	EIA-standard 19-inch rack	EIA-standard 19-inch rack
Performance		
Throughput	up to 4.5 million pps	up to 36 million pps
Routing table size	1000000 entries (IPv4), 300000 entries (IPv6)	2000000 entries (IPv4), 500000 entries (IPv6)
Forwarding table size	1000000 entries (IPv4), 100000 entries (IPv6)	1000000 entries (IPv4), 300000 entries (IPv6)
Backplane bandwidth	48 Gb/s	100 Gb/s
Environment		
Operating temperature	32°F to 113°F (0°C to 45°C)	32°F to 113°F (0°C to 45°C)
Operating relative humidity	10% to 95%, noncondensing	10% to 95%, noncondensing
Nonoperating/Storage temperature	14°F to 131°F (-10°C to 55°C)	14°F to 131°F (-10°C to 55°C)
Nonoperating/Storage relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing
Electrical characteristics		
Frequency	50/60 +/- 2 Hz	50/60 +/- 2 Hz
Maximum heat dissipation	410 BTU/hr (432.55 kJ/hr)	1126 BTU/hr (1187.93 kJ/hr)
AC voltage	100 - 240 VAC	100 - 240 VAC
Maximum power rating	150 W	650 W
Reliability		
MTBF (years)	26.24	31.19
MTTR (hours)	1	1

	HP 6602 Router (JC176A)	HP 6604 Router Chassis (JC178B)
Safety	<p>CSA 22.2 No. 60950; cUL (CSA 22.2 No. 60950); CSA 22.2 No. 60950 3rd edition; CSA 22.2 No. 950; CSA 950; cUL (CSA 950); EN 60950/IEC 60950; UL 1950 3rd edition; UL 1950; UL 60950; UL 60950-1; CAN/CSA 22.2 No. 60950; CAN/CSA 22.2 No. 60950-1; EN 60825; AS/NZS 60950; KN 60950; GOST R MEK60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; EN 609500 Safety Information Technology Equipment; UL 60950; CSA 22.2 No. 60950/cUL; IEC 60950; IEC 60950-1; EN 60950; EN 60950-1; IEC 60825; CSA 22.2 No. 950-95; IEC 60950-1:2001 (with CB Report); CAN/CSA-C22.2 No. 60950-1-03; CAN/CSA-C22.2 No. 60950-1; CSA 60950-1; CSA C22.2 60950-1; EU RoHS Compliant; EN 60950-1/A1; CSA 22.2 60950-1; EN 60950: 2000, ZB and ZC Deviations; IEC 60950: 1999, Corr Feb 2000, all national deviations; As/NZS 60950:2000, Australia; UL 60950-1:2003; UL 60950-1:2001; CSA 22.2 60950-1:2003; IEC 60950-1:2001; EN 60950-1:2001; CSA 22.2-60950; AS/NZS 60950: 2000 Australia, Russian GOST Safety Approval; CSA 22.2 No. 950 3rd Edition 1995; UL 60950 3rd Edition; CAN/CSA 22.2 No. 60950-00/UL 60950 3rd Edition, Safety Information for Technology Equipment; EN 60950/IEC 60950 3rd Edition; UL 60950 Standard for the Safety of Information Technology Equipment; EN 60825: Safety of Laser Products</p>	<p>CSA 22.2 No. 60950; cUL (CSA 22.2 No. 60950); CSA 22.2 No. 60950 3rd edition; CSA 22.2 No. 950; CSA 950; cUL (CSA 950); EN 60950/IEC 60950; UL 1950 3rd edition; UL 1950; UL 60950; UL 60950-1; CAN/CSA 22.2 No. 60950; CAN/CSA 22.2 No. 60950-1; EN 60825; AS/NZS 60950; KN 60950; GOST R MEK60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; EN 609500 Safety Information Technology Equipment; UL 60950; CSA 22.2 No. 60950/cUL; IEC 60950; IEC 60950-1; EN 60950; EN 60950-1; IEC 60825; CSA 22.2 No. 950-95; IEC 60950-1:2001 (with CB Report); CAN/CSA-C22.2 No. 60950-1-03; CAN/CSA-C22.2 No. 60950-1; CSA 60950-1; CSA C22.2 60950-1; EU RoHS Compliant; EN 60950-1/A1; CSA 22.2 60950-1; EN 60950: 2000, ZB and ZC Deviations; IEC 60950: 1999, Corr Feb 2000, all national deviations; As/NZS 60950:2000, Australia; UL 60950-1:2003; UL 60950-1:2001; CSA 22.2 60950-1:2003; IEC 60950-1:2001; EN 60950-1:2001; CSA 22.2-60950; AS/NZS 60950: 2000 Australia, Russian GOST Safety Approval; CSA 22.2 No. 950 3rd Edition 1995; UL 60950 3rd Edition; CAN/CSA 22.2 No. 60950-00/UL 60950 3rd Edition, Safety Information for Technology Equipment; EN 60950/IEC 60950 3rd Edition; UL 60950 Standard for the Safety of Information Technology Equipment; EN 60825: Safety of Laser Products</p>
Emissions	<p>FCC part 15 Class A; FCC Rules Part 15, Subpart B Class A; EN 55022/CISPR-22 Class A; VCCI Class A; EN 55022/CISPR 22 Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; CISPR 22/A2; IEC/EN 61000-3-2; IEC/EN 61000-3-3; EN 55024/A1; IEC 61000:4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11; BSMI CNS 13438; EMC Directive 89/336/EEC; ICES-003 Class A; ANSI C63.4 2003; CISPR 24; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; Korean EMI Class A; CNS 13438 Class A; EN 55024:1998; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11</p>	<p>FCC part 15 Class A; FCC Rules Part 15, Subpart B Class A; EN 55022/CISPR-22 Class A; VCCI Class A; EN 55022/CISPR 22 Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; CISPR 22/A2; IEC/EN 61000-3-2; IEC/EN 61000-3-3; EN 55024/A1; IEC 61000:4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11; BSMI CNS 13438; EMC Directive 89/336/EEC; ICES-003 Class A; ANSI C63.4 2003; CISPR 24; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; Korean EMI Class A; CNS 13438 Class A; EN 55024:1998; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11</p>
Management	<p>IMC—Intelligent Management Center; command-line interface; limited command-line interface; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); out-of-band management; SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB</p>	<p>IMC—Intelligent Management Center; command-line interface; limited command-line interface; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); out-of-band management; SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB</p>
Notes	<p>Routers that will be shipped to Russia will support only low-level encryption (56 bit) security features by default.</p>	<p>The chassis supports a maximum of four HIM or two SAP slots, or a combination thereof; it supports two HIM or one SAP slot with the redundant JC566A. The forwarding table size shown is with the use of JC566A. JC165A delivers forwarding of 500,000 IPv4 and 100,000 IPv6 addresses.</p>

	HP 6602 Router (JC176A)	HP 6604 Router Chassis (JC178B)
Services	<p>3-year, parts only, global next-day advance exchange (HP826E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (HP830E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (HP817E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (HP820E)</p> <p>3-year, 24x7 SW phone support, software updates (HP823E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR524E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware (HR525E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR526E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (HP831E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (HP818E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HP821E)</p> <p>4-year, 24x7 SW phone support, software updates (HP824E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (HP832E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (HP819E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (HP822E)</p> <p>5-year, 24x7 SW phone support, software updates (HP825E)</p> <p>3-year 6 hr Call-to-Repair Onsite (HP827E)</p> <p>4-year 6 hr Call-to-Repair Onsite (HP828E)</p> <p>5-year 6 hr Call-to-Repair Onsite (HP829E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR528E)</p> <p>1-year, 24x7 software phone support, software updates (HR527E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, parts only, global next-day advance exchange (UW054E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW062E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UV930E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (HR530E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV943E)</p> <p>3-year, 24x7 SW phone support, software updates (UV955E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR529E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR531E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW063E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UV931E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV944E)</p> <p>4-year, 24x7 SW phone support, software updates (UV956E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW064E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UV932E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV945E)</p> <p>5-year, 24x7 SW phone support, software updates (UV957E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW055E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW056E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW057E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR533E)</p> <p>1-year, 24x7 software phone support, software updates (HR532E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

HP 6600 Router Series

Specifications (continued)



	HP 6608 Router Chassis (JC177B)	HP 6616 Router Chassis (JC496A)
I/O ports and slots	8 HIM slots or 4 SAP slots , or a combination	16 HIM slots or 8 SAP slots , or a combination
Additional ports and slots	2 MPU (for management modules) slots	2 MPU (for management modules) slots
Physical characteristics		
Weight	17.17(w) x 18.74(d) x 12.13(h) in (43.61 x 47.6 x 30.81 cm) (7U height) 110.23 lb (50 kg) 110.23 lb (50 kg)	17.17(w) x 18.74(d) x 34.88(h) in (43.61 x 47.6 x 88.6 cm) (20U height) 220.46 lb (100 kg)
Mounting and enclosure	EIA-standard 19-inch rack	EIA-standard 19-inch rack
Performance		
Throughput	up to 108 mpps	up to 252 mpps
Routing table size	2000000 entries (IPv4), 500000 entries (IPv6)	2000000 entries (IPv4), 500000 entries (IPv6)
Forwarding table size	1000000 entries (IPv4), 300000 entries (IPv6)	1000000 entries (IPv4), 300000 entries (IPv6)
Backplane bandwidth	300 Gb/s	700 Gb/s
Environment		
Operating temperature	32°F to 113°F (0°C to 45°C)	32°F to 113°F (0°C to 45°C)
Operating relative humidity	10% to 95%, noncondensing	10% to 95%, noncondensing
Nonoperating/Storage temperature	14°F to 131°F (-10°C to 55°C)	14°F to 131°F (-10°C to 55°C)
Nonoperating/Storage relative humidity	5% to 95%, noncondensing	5% to 95%, noncondensing
Electrical characteristics		
Frequency	50/60 +/- 2 Hz	50/60 +/- 2 Hz
Maximum heat dissipation	1910 BTU/hr (2015.05 kJ/hr)	4265 BTU/hr (4499.58 kJ/hr)
AC voltage	100 - 240 VAC	100 - 240 VAC
Maximum power rating	650 W	1950 W
Reliability		
MTBF (years)	26.8	24.5
MTTR (hours)	1	1

	HP 6608 Router Chassis (JC177B)	HP 6616 Router Chassis (JC496A)
Safety	<p>CSA 22.2 No. 60950; cUL (CSA 22.2 No. 60950); CSA 22.2 No. 60950 3rd edition; CSA 22.2 No. 950; CSA 950; cUL (CSA 950); EN 60950/IEC 60950; UL 1950 3rd edition; UL 1950; UL 60950; UL 60950-1; CAN/CSA 22.2 No. 60950; CAN/CSA 22.2 No. 60950-1; EN 60825; AS/NZS 60950; KN 60950; GOST R MEK60950; EN 60825-2 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; EN 609500 Safety Information Technology Equipment; UL 60950; CSA 22.2 No. 60950/cUL; IEC 60950; IEC 60950-1; EN 60950; EN 60950-1; IEC 60825; CSA 22.2 No. 950-95; IEC 60950-1:2001 (with CB Report); CAN/CSA-C22.2 No. 60950-1-03; CAN/CSA-C22.2 No. 60950-1; CSA 60950-1; CSA C22.2 60950-1; EU RoHS Compliant; EN 60950-1/A1; CSA 22.2 60950-1; EN 60950: 2000, ZB and ZC Deviations; IEC 60950: 1999, Corr Feb 2000, all national deviations; As/NZS 60950:2000, Australia; UL 60950-1:2003; UL 60950-1:2001; CSA 22.2 60950-1:2003; IEC 60950-1:2001; EN 60950-1:2001; CSA 22.2-60950; AS/NZS 60950: 2000 Australia, Russian GOST Safety Approval; CSA 22.2 No. 950 3rd Edition 1995; UL 60950 3rd Edition; CAN/CSA 22.2 No. 60950-00/UL 60950 3rd Edition, Safety Information for Technology Equipment; EN 60950/IEC 60950 3rd Edition; UL 60950 Standard for the Safety of Information Technology Equipment; EN 60825: Safety of Laser Products</p>	<p>CSA 22.2 No. 60950; cUL (CSA 22.2 No. 60950); CSA 22.2 No. 60950 3rd edition; CSA 22.2 No. 950; CSA 950; cUL (CSA 950); EN 60950/IEC 60950; UL 1950 3rd edition; UL 1950; UL 60950; UL 60950-1; CAN/CSA 22.2 No. 60950; CAN/CSA 22.2 No. 60950-1; EN 60825; AS/NZS 60950; KN 60950; GOST R MEK60950; EN 60825-1 Safety of Laser Products-Part 1; EN 60825-2 Safety of Laser Products-Part 2; EN 609500 Safety Information Technology Equipment; UL 60950; CSA 22.2 No. 60950/cUL; IEC 60950; IEC 60950-1; EN 60950; EN 60950-1; IEC 60825; CSA 22.2 No. 950-95; IEC 60950-1:2001 (with CB Report); CAN/CSA-C22.2 No. 60950-1-03; CAN/CSA-C22.2 No. 60950-1; CSA 60950-1; CSA C22.2 60950-1; EU RoHS Compliant; EN 60950-1/A1; CSA 22.2 60950-1; EN 60950: 2000, ZB and ZC Deviations; IEC 60950: 1999, Corr Feb 2000, all national deviations; As/NZS 60950:2000, Australia; UL 60950-1:2003; UL 60950-1:2001; CSA 22.2 60950-1:2003; IEC 60950-1:2001; EN 60950-1:2001; CSA 22.2-60950; AS/NZS 60950: 2000 Australia, Russian GOST Safety Approval; CSA 22.2 No. 950 3rd Edition 1995; UL 60950 3rd Edition; CAN/CSA 22.2 No. 60950-00/UL 60950 3rd Edition, Safety Information for Technology Equipment; EN 60950/IEC 60950 3rd Edition; UL 60950 Standard for the Safety of Information Technology Equipment; EN 60825: Safety of Laser Products</p>
Emissions	<p>FCC part 15 Class A; FCC Rules Part 15, Subpart B Class A; EN 55022/CISPR-22 Class A; VCCI Class A; EN 55022/CISPR 22 Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; CISPR 22/A2; IEC/EN 61000-3-2; IEC/EN 61000-3-3; EN 55024/A1; IEC 61000:4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11; BSMI CNS 13438; EMC Directive 89/336/EEC; ICES-003 Class A; ANSI C63.4 2003; CISPR 24; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; Korean EMI Class A; CNS 13438 Class A; EN 55024:1998; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11</p>	<p>FCC part 15 Class A; FCC Rules Part 15, Subpart B Class A; EN 55022/CISPR-22 Class A; VCCI Class A; EN 55022/CISPR 22 Class A; EN 55022 Class A; CISPR 22 Class A; EN 55024; CISPR 22/A2; IEC/EN 61000-3-2; IEC/EN 61000-3-3; EN 55024/A1; IEC 61000:4-2, 4-3, 4-4, 4-5, 4-6, 4-8, 4-11; BSMI CNS 13438; EMC Directive 89/336/EEC; ICES-003 Class A; ANSI C63.4 2003; CISPR 24; ETSI EN 300 386 V1.3.3; AS/NZS CISPR 22 Class A; EN 61000-3-2; EN 61000-3-3; Korean EMI Class A; CNS 13438 Class A; EN 55024:1998; EN 61000-4-2; EN 61000-4-3; EN 61000-4-4; EN 61000-4-5; EN 61000-4-6; EN 61000-4-11</p>
Management	<p>IMC—Intelligent Management Center; command-line interface; limited command-line interface; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); out-of-band management; SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB</p>	<p>IMC—Intelligent Management Center; command-line interface; limited command-line interface; out-of-band management (serial RS-232C); out-of-band management (DB-9 serial port console); out-of-band management; SNMP Manager; Telnet; RMON1; FTP; in-line and out-of-band; terminal interface (serial RS-232C); modem interface; IEEE 802.3 Ethernet MIB; Ethernet Interface MIB</p>
Notes	<p>The chassis supports a maximum of eight HIM or four SAP slots, or a combination thereof; it supports six HIM or three SAP slots, or a combination thereof, with the redundant JC566A. The forwarding table size shown is with the use of JC566A. JC165A delivers forwarding of 500,000 IPv4 and 100,000 IPv6 addresses.</p>	<p>The chassis supports a maximum of 16 HIM or 8 SAP slots, or a combination thereof; it supports 14 HIM or 7 SAP slots, or a combination thereof, with the redundant JC566A. The forwarding table size shown is with the use of JC566A. JC165A delivers forwarding of 500,000 IPv4 and 100,000 IPv6 addresses.</p>

	HP 6608 Router Chassis (JC177B)	HP 6616 Router Chassis (JC496A)
Services	<p>3-year, parts only, global next-day advance exchange (UW054E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW062E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UV930E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (HR530E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV943E)</p> <p>3-year, 24x7 SW phone support, software updates (UV955E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR529E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR531E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW063E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UV931E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV944E)</p> <p>4-year, 24x7 SW phone support, software updates (UV956E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW064E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UV932E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV945E)</p> <p>5-year, 24x7 SW phone support, software updates (UV957E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW055E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW056E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW057E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR533E)</p> <p>1-year, 24x7 software phone support, software updates (HR532E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>	<p>3-year, parts only, global next-day advance exchange (UW054E)</p> <p>3-year, 4-hour onsite, 13x5 coverage for hardware (UW062E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (UV930E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware (HR530E)</p> <p>3-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 SW phone support and SW updates (UV943E)</p> <p>3-year, 24x7 SW phone support, software updates (UV955E)</p> <p>1-year, post-warranty, 4-hour onsite, 13x5 coverage for hardware (HR529E)</p> <p>1-year, post-warranty, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone support (HR531E)</p> <p>4-year, 4-hour onsite, 13x5 coverage for hardware (UW063E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware (UV931E)</p> <p>4-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV944E)</p> <p>4-year, 24x7 SW phone support, software updates (UV956E)</p> <p>5-year, 4-hour onsite, 13x5 coverage for hardware (UW064E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware (UV932E)</p> <p>5-year, 4-hour onsite, 24x7 coverage for hardware, 24x7 software phone (UV945E)</p> <p>5-year, 24x7 SW phone support, software updates (UV957E)</p> <p>3-year 6 hr Call-to-Repair Onsite (UW055E)</p> <p>4-year 6 hr Call-to-Repair Onsite (UW056E)</p> <p>5-year 6 hr Call-to-Repair Onsite (UW057E)</p> <p>1-year, 6 hour Call-To-Repair Onsite for hardware (HR533E)</p> <p>1-year, 24x7 software phone support, software updates (HR532E)</p> <p>Refer to the HP website at hp.com/networking/services for details on the service-level descriptions and product numbers. For details about services and response times in your area, please contact your local HP sales office.</p>

Standards and Protocols

(applies to all products in series)

BGP	<p>RFC 1267 Border Gateway Protocol 3 (BGP-3)</p> <p>RFC 1657 Definitions of Managed Objects for BGPv4</p> <p>RFC 1771 BGPv4</p> <p>RFC 1772 Application of the BGP</p> <p>RFC 1773 Experience with the BGP-4 Protocol</p> <p>RFC 1774 BGP-4 Protocol Analysis</p> <p>RFC 1997 BGP Communities Attribute</p> <p>RFC 1998 PPP Gandalf FZA Compression Protocol</p> <p>RFC 2385 BGP Session Protection via TCP MD5</p> <p>RFC 2439 BGP Route Flap Damping</p> <p>RFC 2796 BGP Route Reflection</p> <p>RFC 2842 Capability Advertisement with BGP-4</p>	<p>RFC 2858 BGP-4 Multi-Protocol Extensions</p> <p>RFC 2918 Route Refresh Capability</p> <p>RFC 4271 A Border Gateway Protocol 4 (BGP-4)</p> <p>RFC 4272 BGP Security Vulnerabilities Analysis</p> <p>RFC 4274 BGP-4 Protocol Analysis</p> <p>RFC 4275 BGP-4 MIB Implementation Survey</p> <p>RFC 4276 BGP-4 Implementation Report</p> <p>RFC 4277 Experience with the BGP-4 Protocol</p> <p>RFC 4360 BGP Extended Communities Attribute</p> <p>RFC 4451 BGP MULTI_EXIT_DISC (MED) Considerations</p> <p>RFC 4456 BGP Route Reflection: An Alternative to Full Mesh Internal BGP (IBGP)</p>	<p>RFC 4486 Subcodes for BGP Cease Notification Message</p> <p>RFC 4724 Graceful Restart Mechanism for BGP</p> <p>RFC 4760 Multiprotocol Extensions for BGP-4</p> <p>RFC 4893 BGP Support for Four-octet AS Number Space</p> <p>RFC 5065 Autonomous System Confederations for BGP</p> <p>RFC 5291 Outbound Route Filtering Capability for BGP-4</p> <p>RFC 5292 Address-Prefix-Based Outbound Route Filter for BGP-4</p> <p>RFC 5398 Autonomous System (AS) Number Reservation for Documentation Use</p> <p>RFC 5883 BFD for Multihop Paths</p>
------------	--	---	---

Standards and Protocols

(applies to all products in series)

Denial of service protection	CPU DoS Protection	Rate Limiting by ACLs	
Device management	RFC 1155 Structure and Mgmt Information (SMIV1) RFC 1157 SNMPv1/v2c RFC 1305 NTPv3 RFC 1901 (Community based SNMPv2) RFC 1901-1907 SNMPv2c, SMIV2 and Revised MIB-II RFC 1902 (SNMPv2) RFC 1908 (SNMP v1/2 Coexistence) RFC 1945 Hypertext Transfer Protocol —HTTP/1.0	RFC 2068 Hypertext Transfer Protocol —HTTP/1.1 RFC 2452 MIB for TCP6 RFC 2454 MIB for UDP6 RFC 2573 (SNMPv3 Applications) RFC 2576 (Coexistence between SNMP V1, V2, V3) RFC 2578-2580 SMIV2 RFC 2579 (SMIV2 Text Conventions) RFC 2580 (SMIV2 Conformance)	RFC 2819 (RMON groups Alarm, Event, History and Statistics only) RFC 2819 RMON RFC 3410 (Management Framework) RFC 3416 (SNMP Protocol Operations v2) RFC 3417 (SNMP Transport Mappings) Multiple Configuration Files Multiple Software Images SNMP v3 and RMON RFC support SSHv1/SShv2 Secure Shell TACACS/TACACS+
General protocols	IEEE 802.1ad Q-in-Q IEEE 802.1ad Q-in-Q IEEE 802.1ag Service Layer OAM IEEE 802.1ah Provider Backbone Bridges IEEE 802.1AX-2008 Link Aggregation IEEE 802.1D MAC Bridges IEEE 802.1p Priority IEEE 802.1Q (GVRP) IEEE 802.1Q VLANs IEEE 802.1s (MSTP) IEEE 802.1s Multiple Spanning Trees IEEE 802.1v VLAN classification by Protocol and Port IEEE 802.1w Rapid Reconfiguration of Spanning Tree IEEE 802.1X PAE IEEE 802.3 Type 10BASE-T IEEE 802.3ab 1000BASE-T IEEE 802.3ac (VLAN Tagging Extension) IEEE 802.3ad Link Aggregation (LAG) IEEE 802.3ad Link Aggregation Control Protocol (LACP) IEEE 802.3ae 10-Gigabit Ethernet IEEE 802.3ag Ethernet OAM IEEE 802.3ah Ethernet in First Mile over Point to Point Fiber - EFMF IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-X IEEE 802.3x Flow Control IEEE 802.3z 1000BASE-X RFC 768 UDP RFC 783 TFTP Protocol (revision 2) RFC 791 IP RFC 792 ICMP RFC 793 TCP RFC 826 ARP RFC 854 TELNET RFC 855 Telnet Option Specification RFC 856 TELNET RFC 857 Telnet Echo Option RFC 858 Telnet Suppress Go Ahead Option RFC 894 IP over Ethernet RFC 896 Congestion Control in IP/TCP Internetworks RFC 906 TFTP Bootstrap RFC 925 Multi-LAN Address Resolution	RFC 1213 Management Information Base for Network Management of TCP/IP-based internets RFC 1661 The Point-to-Point Protocol (PPP) RFC 1662 PPP in HDLC-like Framing RFC 1695 Definitions of Managed Objects for ATM Management Version 8.0 using SMIV2 RFC 1700 Assigned Numbers RFC 1701 Generic Routing Encapsulation RFC 1702 Generic Routing Encapsulation over IPv4 networks RFC 1721 RIP-2 Analysis RFC 1722 RIP-2 Applicability RFC 1723 RIP v2 RFC 1812 IPv4 Routing RFC 1829 The ESP DES-CBC Transform RFC 1853 IP in IP Tunneling RFC 1877 PPP Internet Protocol Control Protocol Extensions for Name Server Addresses RFC 1944 Benchmarking Methodology for Network Interconnect Devices RFC 1945 Hypertext Transfer Protocol —HTTP/1.0 RFC 1973 PPP in Frame Relay RFC 1974 PPP Stac LZS Compression Protocol RFC 1981 Path MTU Discovery for IP version 6 RFC 1990 The PPP Multilink Protocol (MP) RFC 1994 PPP Challenge Handshake Authentication Protocol (CHAP) RFC 2003 IP Encapsulation within IP RFC 2082 RIP-2 MD5 Authentication RFC 2091 Trigger RIP RFC 2104 HMAC: Keyed-Hashing for Message Authentication RFC 2131 DHCP RFC 2132 DHCP Options and BOOTP Vendor Extensions RFC 2138 Remote Authentication Dial In User Service (RADIUS) RFC 2205 Resource ReSerVation Protocol (RSVP) - Version 1 Functional Specification	RFC 2833 RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals RFC 2856 Textual Conventions for Additional High Capacity Data Types RFC 2865 Remote Authentication Dial In User Service (RADIUS) RFC 2866 RADIUS Accounting RFC 2868 RADIUS Attributes for Tunnel Protocol Support RFC 2869 RADIUS Extensions RFC 2915 The Naming Authority Pointer (NAPTR) DNS Resource Record RFC 2916 E.164 number and DNS P. Faltstrom RFC 2961 RSVP Refresh Overhead Reduction Extensions RFC 2966 Domain-wide Prefix Distribution with Two-Level IS-IS RFC 2973 IS-IS Mesh Groups RFC 2993 Architectural Implications of NAT RFC 3022 Traditional IP Network Address Translator (Traditional NAT) RFC 3027 Protocol Complications with the IP Network Address Translator RFC 3031 Multiprotocol Label Switching Architecture RFC 3032 MPLS Label Stack Encoding RFC 3036 LDP Specification RFC 3046 DHCP Relay Agent Information Option RFC 3063 MPLS Loop Prevention Mechanism RFC 3065 Support AS confederation RFC 3137 OSPF Stub Router Advertisement RFC 3209 RSVP-TE Extensions to RSVP for LSP Tunnels RFC 3210 Applicability Statement for Extensions to RSVP for LSP-Tunnels RFC 3212 Constraint-Based LSP setup using LDP (CR-LDP) RFC 3214 LSP Modification Using CR-LDP RFC 3215 LDP State Machine RFC 3246 Expedited Forwarding PHB RFC 3268 Advanced Encryption Standard (AES) Ciphersuites for Transport Layer Security (TLS)

Standards and Protocols

(applies to all products in series)

RFC 950 Internet Standard Subnetting Procedure	RFC 2209 Resource ReSerVation Protocol (RSVP)—Version 1 Message Processing Rules	RFC 3272 Overview and Principles of Internet Traffic Engineering
RFC 951 BOOTP	RFC 2225 Classical IP and ARP over ATM	RFC 3277 IS-IS Transient Blackhole Avoidance
RFC 959 File Transfer Protocol (FTP)	RFC 2236 IGMP Snooping	RFC 3279 Algorithms and Identifiers for the Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1006 ISO transport services on top of the TCP: Version 3	RFC 2246 The TLS Protocol Version 1.0	RFC 3280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile
RFC 1027 Proxy ARP	RFC 2251 Lightweight Directory Access Protocol (v3)	RFC 3359 Reserved Type, Length and Value (TLV) Codepoints in Intermediate System to Intermediate System
RFC 1034 Domain Concepts and Facilities	RFC 2252 Lightweight Directory Access Protocol (v3): Attribute Syntax Definitions	RFC 3392 Support BGP capabilities advertisement
RFC 1035 Domain Implementation and Specification	RFC 2280 Routing Policy Specification Language (RPSL)	RFC 3410 Applicability Statements for SNMP
RFC 1042 IP Datagrams	RFC 2283 MBGP	RFC 3416 Protocol Operations for SNMP
RFC 1058 RIPv1	RFC 2284 EAP over LAN	RFC 3417 Transport Mappings for the Simple Network Management Protocol (SNMP)
RFC 1071 Computing the Internet Checksum	RFC 2338 VRRP	RFC 3442 The Classless Static Route Option for Dynamic Host Configuration Protocol (DHCP) version 4
RFC 1091 Telnet Terminal-Type Option	RFC 2338 VRRP (Premium Edge License)	RFC 3479 Fault Tolerance for the Label Distribution Protocol (LDP)
RFC 1093 NSFNET routing architecture	RFC 2364 PPP Over AAL5	RFC 3487 Graceful Restart Mechanism for LDP
RFC 1122 Host Requirements	RFC 2374 An Aggregatable Global Unicast Address Format	RFC 3509 OSPF ABR Behavior
RFC 1141 Incremental updating of the Internet checksum	RFC 2390 Inverse Address Resolution Protocol	RFC 3526 More Modular Exponential (MODP) Diffie-Hellman groups for Internet Key Exchange (IKE)
RFC 1142 OSI IS-IS Intra-domain Routing Protocol	RFC 2427 Multiprotocol Interconnect over Frame Relay	RFC 3562 Key Management Considerations for the TCP MD5 Signature Option
RFC 1144 Compressing TCP/IP headers for low-speed serial links	RFC 2451 The ESP CBC-Mode Cipher Algorithms	RFC 3564 Requirements for Support of Differentiated Services-aware MPLS Traffic Engineering
RFC 1171 Point-to-Point Protocol for the transmission of multi-protocol datagrams over Point-to-Point links	RFC 2453 RIPv2	RFC 3567 Intermediate System to Intermediate System (IS-IS) Cryptographic Authentication
RFC 1191 Path MTU discovery	RFC 2510 Internet X.509 Public Key Infrastructure Certificate Management Protocols	RFC 3590 Source Address Selection for the Multicast Listener Discovery (MLD) Protocol
RFC 1195 OSI ISIS for IP and Dual Environments	RFC 2511 Internet X.509 Certificate Request Message Format	RFC 3602 The AES-CBC Cipher Algorithm and Its Use with IPsec
RFC 1253 (OSPF v2)	RFC 2514 Definitions of Textual Conventions and OBJECT-IDENTITIES for ATM Management	RFC 3619 Ethernet Automatic Protection Switching (EAPS)
RFC 1256 ICMP Router Discovery Protocol (IRDP)	RFC 2515 Definitions of Managed Objects for ATM Management	RFC 3623 Graceful OSPF Restart
RFC 1293 Inverse Address Resolution Protocol	RFC 2516 A Method for Transmitting PPP Over Ethernet (PPPoE)	RFC 3704 Unicast Reverse Path Forwarding (URPF)
RFC 1305 NTPv3	RFC 2519 A Framework for Inter-Domain Route Aggregation	RFC 3706 A Traffic-Based Method of Detecting Dead Internet Key Exchange (IKE) Peers
RFC 1315 Management Information Base for Frame Relay DTEs	RFC 2529 Transmission of IPv6 over IPv4 Domains without Explicit Tunnels	RFC 3768 VRRP
RFC 1321 The MD5 Message-Digest Algorithm	RFC 2544 Benchmarking Methodology for Network Interconnect Devices	RFC 3768 VRRP
RFC 1332 The PPP Internet Protocol Control Protocol (IPCP)	RFC 2581 TCP Congestion Control	RFC 3768 VRRP (Premium Edge License)
RFC 1333 PPP Link Quality Monitoring	RFC 2615 PPP over SONET/SDH (Synchronous Optical Network/Synchronous Digital Hierarchy)	RFC 3784 ISIS TE support
RFC 1334 PPP Authentication Protocols (PAP)	RFC 2591 HTTP Compatibility v1.1	RFC 3786 Extending the Number of IS-IS LSP Fragments Beyond the 256 Limit
RFC 1334 PPP Authentication Protocols (PAP)	RFC 2617 HTTP Authentication: Basic and Digest Access Authentication	RFC 3811 Definitions of Textual Conventions (TCs) for Multiprotocol Label Switching (MPLS) Management
RFC 1349 Type of Service	RFC 2622 Routing Policy Specification Language (RPSL)	RFC 3812 Multiprotocol Label Switching (MPLS) Traffic Engineering (TE) Management Information Base (MIB)
RFC 1350 TFTP Protocol (revision 2)	RFC 2644 Directed Broadcast Control	RFC 3847 Restart signaling for IS-IS
RFC 1377 The PPP OSI Network Layer Control Protocol (OSINLCP)	RFC 2661 L2TP	
RFC 1381 SNMP MIB Extension for X.25 LAPB	RFC 2663 NAT Terminology and Considerations	
RFC 1389 RIPv2 MIB Extension	RFC 2684 Multiprotocol Encapsulation over ATM Adaptation Layer 5	
RFC 1471 The Definitions of Managed Objects for the Link Control Protocol of the Point-to-Point Protocol	RFC 2694 DNS extensions to Network Address Translators (DNS_ALG)	
RFC 1472 The Definitions of Managed Objects for the Security Protocols of the Point-to-Point Protocol	RFC 2702 Requirements for Traffic Engineering Over MPLS	
RFC 1473 The Definitions of Managed Objects for the IP Network Control Protocol of the Point-to-Point Protocol	RFC 2716 PPP EAP TLS Authentication Protocol	
RFC 1490 Multiprotocol Interconnect over Frame Relay		

Standards and Protocols

(applies to all products in series)

IP multicast	RFC 1112 IGMP RFC 2236 IGMPv2 RFC 2283 Multiprotocol Extensions for BGP-4 RFC 2362 PIM Sparse Mode RFC 2362 PIM Sparse Mode RFC 2362 PIM Sparse Mode (Premium Edge License) RFC 2365 Administratively Scoped IP Multicast RFC 2934 Protocol Independent Multicast MIB for IPv4 RFC 3376 IGMPv3 RFC 3376 IGMPv3 (host joins only) RFC 3446 Anycast Rendezvous Point (RP) mechanism using Protocol Independent Multicast (PIM) and Multicast Source Discovery Protocol (MSDP)	RFC 2747 RSVP Cryptographic Authentication RFC 2763 Dynamic Name-to-System ID mapping support RFC 2765 Stateless IP/ICMP Translation Algorithm (SIIT) RFC 2766 Network Address Translation - Protocol Translation (NAT-PT) RFC 2767 Dual Stacks IPv4 & IPv6 RFC 2782 A DNS RR (DNS Resource Record) for specifying the location of services (DNS SRV) Domain Name System Server RFC 2784 Generic Routing Encapsulation (GRE) RFC 2787 Definitions of Managed Objects for VRRP RFC 2965 HTTP State Management Mechanism	RFC 3879 Deprecating Site Local Addresses RFC 3906 Calculating Interior Gateway Protocol (IGP) Routes Over Traffic Engineering Tunnels RFC 3917 Requirements for IP Flow Information Export (IPFIX) RFC 3954 Cisco Systems NetFlow Services Export Version 9 RFC 4213 Basic IPv6 Transition Mechanisms RFC 4884 Extended ICMP to Support Multi-Part Messages RFC 5082 The Generalized TTL Security Mechanism (GTSM) RFC 5286 Basic Specification for IP Fast Reroute: Loop-Free Alternates RFC 5880 Bidirectional Forwarding Detection RFC 5882 Generic Application of BFD IP Ping
IPv6	RFC 1350 TFTP RFC 1881 IPv6 Address Allocation Management RFC 1886 DNS Extension for IPv6 RFC 1887 IPv6 Unicast Address Allocation Architecture RFC 1981 IPv6 Path MTU Discovery RFC 2080 RIPng for IPv6 RFC 2292 Advanced Sockets API for IPv6 RFC 2373 IPv6 Addressing Architecture RFC 2375 IPv6 Multicast Address Assignments RFC 2460 IPv6 Specification RFC 2461 IPv6 Neighbor Discovery	RFC 2925 Definitions of Managed Objects for Remote Ping, Traceroute, and Lookup Operations (Ping only) RFC 2925 Remote Operations MIB (Ping only) RFC 3056 Connection of IPv6 Domains via IPv4 Clouds RFC 3162 RADIUS and IPv6 RFC 3306 Unicast-Prefix-based IPv6 Multicast Addresses RFC 3307 IPv6 Multicast Address Allocation RFC 3315 DHCPv6 (client and relay) RFC 3315 DHCPv6 (client only)	RFC 3956 Embedding the Rendezvous Point (RP) Address in an IPv6 Multicast Address RFC 4001 Textual Conventions for Internet Network Addresses RFC 4007 IPv6 Scoped Address Architecture RFC 4022 MIB for TCP RFC 4113 MIB for UDP RFC 4251 SSHv6 Architecture RFC 4252 SSHv6 Authentication RFC 4252 SSHv6 Transport Layer RFC 4253 SSHv6 Transport Layer RFC 4254 SSHv6 Connection RFC 4291 IP Version 6 Addressing Architecture

Standards and Protocols

(applies to all products in series)

IPv6 (Continued)

RFC 2462 IPv6 Stateless Address Auto-configuration	RFC 3363 DNS support	RFC 4293 MIB for IP
RFC 2463 ICMPv6	RFC 3484 Default Address Selection for IPv6	RFC 4419 Key Exchange for SSH
RFC 2464 Transmission of IPv6 over Ethernet Networks	RFC 3493 Basic Socket Interface Extensions for IPv6	RFC 4443 ICMPv6
RFC 2472 IP Version 6 over PPP	RFC 3513 IPv6 Addressing Architecture	RFC 4541 IGMP & MLD Snooping Switch
RFC 2473 Generic Packet Tunneling in IPv6	RFC 3542 Advanced Sockets API for IPv6	RFC 4552 Authentication/Confidentiality for OSPFv3
RFC 2475 IPv6 DiffServ Architecture	RFC 3587 IPv6 Global Unicast Address Format	RFC 4798 Connecting IPv6 Islands over IPv4 MPLS Using IPv6 Provider Edge Routers (6PE)
RFC 2529 Transmission of IPv6 Packets over IPv4	RFC 3596 DNS Extension for IPv6	RFC 4861 IPv6 Neighbor Discovery
RFC 2545 Use of MP-BGP-4 for IPv6	RFC 3646 DNS Configuration options for Dynamic Host Configuration Protocol for IPv6	RFC 4862 IPv6 Stateless Address Auto-configuration
RFC 2553 Basic Socket Interface Extensions for IPv6	RFC 3736 Stateless Dynamic Host Configuration Protocol (DHCP) Service for IPv6	RFC 4940 IANA Considerations for OSPF
RFC 2710 Multicast Listener Discovery (MLD) for IPv6	RFC 3810 MLDDv2 (host joins only)	RFC 5072 IP Version 6 over PPP
RFC 2711 IPv6 Router Alert Option	RFC 3810 MLDDv2 for IPv6	RFC 5095 Deprecation of Type 0 Routing Headers in IPv6
RFC 2740 OSPFv3 for IPv6	RFC 3810 Multicast Listener Discovery Version 2 (MLDDv2) for IPv6	RFC 5340 OSPF for IPv6
RFC 2893 Transition Mechanisms for IPv6 Hosts and Routers		RFC 5340 OSPFv3 for IPv6
RFC 2894 Router Renumbering for IPv6		RFC 5722 Handling of Overlapping IPv6 Fragments
		RFC 5881 BFD for IPv4 and IPv6 (Single Hop)

MIBs

IEEE 8021-PAE-MIB	RFC 2096 IP Forwarding Table MIB	RFC 2787 VRRP MIB
IEEE 8023-LAG-MIB	RFC 2233 Interface MIB	RFC 2819 RMON MIB
RFC 1156 (TCP/IP MIB)	RFC 2233 Interfaces MIB	RFC 2863 The Interfaces Group MIB
RFC 1212 Concise MIB Definitions	RFC 2452 IPv6-TCP-MIB	RFC 2932IP (Multicast Routing MIB)
RFC 1213 MIB II	RFC 2454 IPv6-UDP-MIB	RFC 2933 IGMP MIB
RFC 1229 Interface MIB Extensions	RFC 2465 IPv6 MIB	RFC 3273 HC-RMON MIB
RFC 1286 Bridge MIB	RFC 2466 ICMPv6 MIB	RFC 3414 SNMP-User based-SM MIB
RFC 1493 Bridge MIB	RFC 2571 SNMP Framework MIB	RFC 3415 SNMP-View based-ACM MIB
RFC 1573 SNMP MIB II	RFC 2572 SNMP-MPD MIB	RFC 3418 MIB for SNMPv3
RFC 1643 Ethernet MIB	RFC 2573 SNMP-Notification MIB	RFC 3621 Power Ethernet MIB
RFC 1650 Ethernet-Like MIB	RFC 2573 SNMP-Target MIB	RFC 3813 MPLS LSR MIB
RFC 1657 BGP-4 MIB	RFC 2574 SNMP USM MIB	RFC 3814 MPLS FTN MIB
RFC 1724 RIPV2 MIB	RFC 2618 RADIUS Client MIB	RFC 3815 MPLS LDP MIB
RFC 1757 Remote Network Monitoring MIB	RFC 2620 RADIUS Accounting MIB	RFC 3826 AES for SNMP's USM MIB
RFC 1850 OSPFv2 MIB	RFC 2665 Ethernet-Like-MIB	RFC 4113 UDP MIB
RFC 1907 SNMPv2 MIB	RFC 2668 802.3 MAU MIB	RFC 4133 Entity MIB (Version 3)
RFC 2011 SNMPv2 MIB for IP	RFC 2674 802.1p and IEEE 802.1Q Bridge MIB	RFC 4221 MPLS FTN MIB
RFC 2012 SNMPv2 MIB for TCP	RFC 2688 MAU-MIB	LLDP-EXT-DOT1-MIB
RFC 2013 SNMPv2 MIB for UDP		LLDP-EXT-DOT3-MIB
RFC 2021 RMONv2 MIB	RFC 2737 Entity MIB (Version 2)	LLDP-MIB

MPLS

RFC 3037 LDP (Label Distribution Protocol) Applicability	RFC 4182 Removing a Restriction on the use of MPLS Explicit NULL	RFC 4664 Framework for Layer 2 Virtual Private Networks
RFC 3270 Multi-Protocol Label Switching (MPLS) Support of Differentiated Services	RFC 4216 MPLS Inter-Autonomous System (AS) Traffic Engineering (TE) Requirements	RFC 4665 Service Requirements for Layer 2 Provider Provisioned Virtual Private Networks
RFC 3429 Assignment of the 'OAM Alert Label' for Multiprotocol Label Switching	RFC 4364 BGP/MPLS IP Virtual Private Networks (VPNs)	RFC 4717 Encapsulation Methods for Transport of Asynchronous Transfer Mode (ATM) over MPLS
RFC 3443 Time To Live (TTL) Processing in Multi-Protocol Label Switching (MPLS) Networks	RFC 4365 Applicability Statement for BGP/MPLS IP Virtual Private Networks (VPNs)	RFC 4761 Virtual Private LAN Service (VPLS) Using BGP for Auto-Discovery and Signaling
RFC 3478 Graceful Restart Mechanism for Label Distribution Protocol	RFC 4381 Analyses of the Security of BGP/MPLS IP VPNs	RFC 4762 Virtual Private LAN Service (VPLS) Using Label Distribution Protocol (LDP) Signaling
RFC 3612 Applicability Statement for Restart Mechanisms for the Label Distribution	RFC 4385 Pseudowire Emulation Edge-to-Edge (PWE3) Control Word for Use over an MPLS PSN	RFC 4764 Framework for Layer 2 Virtual Private Networks (L2VPNs)
RFC 3916 Requirements for Pseudo-Wire Emulation Edge-to-Edge (PWE3)	RFC 4446 IANA Allocations for Pseudowire Edge to Edge Emulation (PWE3)	RFC 4765 Service Requirements for Layer 2 Provider Provisioned Virtual Private Networks
RFC 3985 Pseudo Wire Emulation Edge-to-Edge (PWE3) Architecture	RFC 4448 Encapsulation Methods for Transport of Ethernet over MPLS Networks	RFC 4816 Pseudowire Emulation Edge-to-Edge (PWE3) Asynchronous Transfer Mode (ATM)
RFC 4023 Encapsulating MPLS in IP or Generic Routing Encapsulation (GRE)		
RFC 4090 Fast Reroute Extensions to RSVP-TE for LSP Tunnels		

Standards and Protocols

(applies to all products in series)

MPLS (Continued)

RFC 4105 Requirements for Inter-Area MPLS Traffic Engineering	RFC 4576 Using a Link State Advertisement (LSA) Options Bit to Prevent Looping in BGP/MPLS	RFC 4941 Privacy Extensions for Stateless Address Autoconfiguration in IPv6
RFC 4124 Protocol Extensions for Support of DiffServ-aware MPLS Traffic Engineering	RFC 4618 Encapsulation Methods for Transport of PPP/High-Level Data Link Control (HDLC) over MPLS Networks	RFC 5085 Pseudowire Virtual Circuit Connectivity Verification (VCCV): A Control Channel
RFC 4125 Maximum Allocation Bandwidth Constraints Model for DiffServ-aware MPLS Traffic	RFC 4619 Encapsulation Methods for Transport of Frame Relay over Multiprotocol Label	RFC 5443 LDP IGP Synchronization
RFC 4127 Russian Dolls Bandwidth Constraints Model for DiffServ-aware MPLS Traffic	RFC 4659 BGP-MPLS IP Virtual Private Network (VPN) Extension for IPv6 VPN	RFC 5601 Pseudowire (PW) Management Information Base (MIB)
		RFC 5602 Pseudowire (PW) over MPLS PSN Management Information Base (MIB)

Network management

IEEE 802.1AB Link Layer Discovery Protocol (LLDP)	RFC 2275 VACM for SNMPv3	RFC 3414 SNMPv3 User-based Security Model (USM)
IEEE 802.1D (STP)	RFC 2570 SNMPv3 Overview	RFC 3415 SNMPv3 View-based Access Control Model (VACM)
RFC 1098 A Simple Network Management Protocol (SNMP)	RFC 2571 SNMP Management Frameworks	RFC 3584 Coexistence between Version 1 and Version 2 of the Internet-standard Network
RFC 1155 Structure of Management Information	RFC 2572 SNMPv3 Message Processing	RFC 3593 Textual Conventions for MIB Modules Using Performance History Based on 15 Minute
RFC 1157 SNMPv1	RFC 2573 SNMPv3 Applications	RFC 3636 Definitions of Managed Objects for IEEE 802.3 Medium Attachment Units (MAUs)
RFC 1215 SNMP Generic traps	RFC 2574 SNMPv3 User-based Security Model (USM)	RFC 4292 IP Forwarding Table MIB
RFC 1382 SNMP MIB Extension for the X.25 Packet Layer	RFC 2575 SNMPv3 View-based Access Control Model (VACM)	RFC 4502 Remote Network Monitoring Management Information Base Version 2
RFC 1757 RMON 4 groups: Stats, History, Alarms and Events	RFC 2576 VACM for SNMP	RFC 4878 Definitions and Managed Objects for Operations, Administration, and Maintenance (OAM) Functions on ANSI/TIA-1057 LLDP Media Endpoint Discovery (LLDP-MED)
RFC 1901 SNMPv2 Introduction	RFC 2576 Coexistence between SNMP versions	SNMPv1/v2
RFC 1902 SNMPv2 Structure	RFC 2578 SMIv2	SNMPv1/v2c
RFC 1903 SNMPv2 Textual Conventions	RFC 2581 TCP6	SNMPv1/v2c (read only)
RFC 1904 SNMPv2 Conformance	RFC 2819 Four groups of RMON: 1 (statistics), 2 (history), 3 (alarm) and 9 (events)	SNMPv1/v2c/v3
RFC 1905 SNMPv2 Protocol Operations	RFC 3164 BSD syslog Protocol	
RFC 1906 SNMPv2 Transport Mappings	RFC 3176 sFlow	
RFC 1918 Private Internet Address Allocation	RFC 3411 SNMP Management Frameworks	
RFC 2272 SNMPv3 Management Protocol	RFC 3412 SNMPv3 Message Processing	
RFC 2273 SNMPv3 Applications	RFC 3413 Simple Network Management Protocol (SNMP) Applications	
RFC 2274 USM for SNMPv3		

OSPF

RFC 1245 OSPF protocol analysis	RFC 2370 OSPF Opaque LSA Option	RFC 4222 Prioritized Treatment of Specific OSPF Version 2 Packets and Congestion Avoidance
RFC 1246 Experience with OSPF	RFC 3101 OSPF NSSA	RFC 4577 OSPF as the Provider/Customer Edge Protocol for BGP/MPLS IP Virtual Private Networks (VPNs)
RFC 1253 OSPFv2 MIB	RFC 3623 Graceful OSPF Restart	RFC 4811 OSPF Out-of-Band LSDB Resynchronization
RFC 1583 OSPFv2	RFC 3630 Traffic Engineering Extensions to OSPF Version 2	RFC 4812 OSPF Restart Signaling
RFC 1587 OSPF NSSA	RFC 4061 Benchmarking Basic OSPF Single Router Control Plane Convergence	RFC 4813 OSPF Link-Local Signaling
RFC 1745 OSPF Interactions	RFC 4062 OSPF Benchmarking Terminology and Concepts	RFC 5187 OSPFv3 Graceful Restart
RFC 1765 OSPF Database Overflow	RFC 4063 Considerations When Using Basic OSPF Convergence Benchmarks	RFC 5340 OSPF for IPv6
RFC 1850 OSPFv2 Management Information Base (MIB), traps		RFC 5340 OSPFv3 for IPv6
RFC 2178 OSPFv2		RFC 5613 OSPF Link-Local Signaling
RFC 2328 OSPFv2		
RFC 2328 OSPFv2 (Premium Edge License)		

QoS/CoS

IEEE 802.1P (CoS)	RFC 2474, with 4 queues per port	RFC 3247 Supplemental Information for the New Definition of the EF PHB (Expedited Forwarding Per-Hop Behavior)
RFC 2309 Recommendations on queue management and congestion avoidance in the Internet	RFC 2475 DiffServ Architecture	RFC 3260 New Terminology and Clarifications for DiffServ
RFC 2474 DiffServ Precedence, including 8 queues/port	RFC 2597 DiffServ Assured Forwarding (AF)	RFC 3662 A Lower Effort Per-Domain Behavior (PDB) for Differentiated Services
RFC 2474 DiffServ precedence, with 4 queues per port	RFC 2597 DiffServ Assured Forwarding (AF) - partial support	RFC 4594 Configuration Guidelines for DiffServ Service Classes
RFC 2474 DS Field in the IPv4 and IPv6 Headers	RFC 2598 DiffServ Expedited Forwarding (EF)	Ingress Rate Limiting
RFC 2474 DSCP DiffServ	RFC 2697 A Single Rate Three Color Marker	
	RFC 2698 A Two Rate Three Color Marker	
	RFC 2751 Signaled Preemption Priority Policy Element	

Standards and Protocols

(applies to all products in series)

Security	IEEE 802.1X Port Based Network Access Control RFC 1321 The MD5 Message-Digest Algorithm RFC 1492 TACACS+ RFC 2082 RIP-2 MD5 Authentication RFC 2104 Keyed-Hashing for Message Authentication RFC 2138 RADIUS Authentication RFC 2139 RADIUS Accounting RFC 2209 RSVP-Message Processing RFC 2246 Transport Layer Security (TLS) RFC 2459 Internet X.509 Public Key Infrastructure Certificate and CRL Profile RFC 2548 Microsoft Vendor-specific RADIUS Attributes	RFC 2716 PPP EAP TLS Authentication Protocol RFC 2818 HTTP Over TLS RFC 2865 RADIUS (client only) RFC 2865 RADIUS Authentication RFC 2866 RADIUS Accounting RFC 2867 RADIUS Accounting Modifications for Tunnel Protocol Support RFC 2868 RADIUS Attributes for Tunnel Protocol Support RFC 2869 RADIUS Extensions RFC 3567 Intermediate System (IS) to IS Cryptographic Authentication RFC 3576 Dynamic Authorization Extensions to RADIUS	RFC 3579 RADIUS Support For Extensible Authentication Protocol (EAP) RFC 3580 IEEE 802.1X RADIUS RFC 4250 The Secure Shell (SSH) Protocol Assigned Numbers RFC 5214 Intra-Site Automatic Tunnel Addressing Protocol (ISATAP) Access Control Lists (ACLs) Guest VLAN for 802.1x MAC Authentication Port Security Secure Sockets Layer (SSL) SSHv1 Secure Shell SSHv1.5 Secure Shell SSHv1/SSHv2 Secure Shell SSHv2 Secure Shell
VPN	RFC 2403—HMAC-MD5-96 RFC 2404—HMAC-SHA1-96 RFC 2405—DES-CBC Cipher algorithm RFC 2407—Domain of interpretation RFC 2547 BGP/MPLS VPNs RFC 2764 A Framework for IP Based Virtual Private Networks RFC 2796 BGP Route Reflection - An Alternative to Full Mesh IBGP	RFC 2842 Capabilities Advertisement with BGP-4 RFC 2858 Multiprotocol Extensions for BGP-4 RFC 2917 A Core MPLS IP VPN Architecture RFC 2918 Route Refresh Capability for BGP-4	RFC 3107 Carrying Label Information in BGP-4 RFC 4301—Security Architecture for the Internet Protocol RFC 4302—IP Authentication Header (AH) RFC 4303—IP Encapsulating Security Payload (ESP) RFC 4305—Cryptographic Algorithm Implementation Requirements for ESP and AH
IPSec	RFC 1828 IP Authentication using Keyed MD5 RFC 2401 IP Security Architecture RFC 2402 IP Authentication Header RFC 2406 IP Encapsulating Security Payload RFC 2407—Domain of interpretation	RFC 2408—Internet Security Association and Key Management Protocol (ISAKMP) RFC 2409—The Internet Key Exchange RFC 2410—The NULL Encryption Algorithm and its use with IPSec RFC 2411 IP Security Document Roadmap	RFC 2412 – OAKLEY RFC 2865—Remote Authentication Dial In User Service (RADIUS) RFC 4835 Cryptographic Algorithm Implementation Requirements for Encapsulating Security
IKEv1	RFC 2865—Remote Authentication Dial In User Service (RADIUS)	RFC 3748—Extensible Authentication Protocol (EAP)	RFC 4109 Algorithms for Internet Key Exchange version 1 (IKEv1)
PKI		RFC 5280 Internet X.509 Public Key Infrastructure Certificate and Certificate Revocation List (CRL) Profile	

HP 6600 Router Series accessories

Transceivers

HP X110 100M SFP LC LH40 Transceiver (JD090A)
 HP X110 100M SFP LC LH80 Transceiver (JD091A)
 HP X110 100M SFP LC FX Transceiver (JD102B)
 HP X110 100M SFP LC LX Transceiver (JD120B)
 HP X120 622M SFP LC LX 15km Transceiver (JF829A)
 HP X120 622M SFP LC LH 40km 1310 Transceiver (JF830A)
 HP X120 622M SFP LC LH 80km 1550 Transceiver (JF831A)
 HP X125 1G SFP LC LH40 1310nm Transceiver (JD061A)
 HP X120 1G SFP LC LH40 1550nm Transceiver (JD062A)
 HP X120 1G SFP LC BX 10-U Transceiver (JD098B)
 HP X120 1G SFP LC BX 10-D Transceiver (JD099B)
 HP X120 1G SFP LC LH100 Transceiver (JD103A)
 HP X120 1G SFP LC SX Transceiver (JD118B)
 HP X120 1G SFP LC LX Transceiver (JD119B)
 HP X125 1G SFP LC LH70 Transceiver (JD063B)
 HP X120 1G SFP RJ45 T Transceiver (JD089B)
 HP X160 2.5G SFP LC 2km Transceiver (JD084A)
 HP X160 2.5G SFP LC 15km Transceiver (JD085A)
 HP X160 2.5G SFP LC 40km Transceiver (JD086A)

Transceivers (Continued)

HP X160 2.5G SFP LC 80km Transceiver (JD087A)
 HP X135 10G XFP LC ER Transceiver (JD121A)
 HP X130 10G XFP LC LR Transceiver (JD108B)
 HP X130 10G XFP LC SR Transceiver (JD117B)

Cables

HP X200 V.24 DTE 3m Serial Port Cable (JD519A)
 HP X200 V.24 DCE 3m Serial Port Cable (JD521A)
 HP X200 V.35 DTE 3m Serial Port Cable (JD523A)
 HP X200 V.35 DCE 3m Serial Port Cable (JD525A)
 HP X200 X.21 DTE 3m Serial Port Cable (JD527A)
 HP X200 X.21 DCE 3m Serial Port Cable (JD529A)
 HP X260 RS449 3m DTE Serial Port Cable (JF825A)
 HP X260 RS449 3m DCE Serial Port Cable (JF826A)
 HP X260 RSS30 3m DTE Serial Port Cable (JF827A)
 HP X260 RSS30 3m DCE Serial Port Cable (JF828A)
 HP X260 8E1 BNC 75 ohm 3m Router Cable (JD512A)
 HP X260 E1 RJ45 BNC 75-120 ohm Conversion Router Cable (JD511A)

Router Modules

HP 6600 RSE-X1 Main Processing Unit (JC566A)
 HP 6600 RPE-X1 Main Processing Unit (JC165A)
 HP 6600 MCP-X1 Router Main Processing Unit (JG355A)
 HP 6600 MCP-X2 Router Main Processing Unit (JG356A)
 HP 6600 FIP-10 Flexible Interface Platform Router Module (JG357A)
 HP 6600 FIP-20 Flexible Interface Platform Router Module (JG358A)
 HP 6600 FIP-110 Flexible Interface Platform Module (JC166B)
 HP 6600 FIP-210 Flexible Interface Platform Module (JC167B)
 HP 6600 8-port OC-3c/OC-12c POS / GbE SFP HIM Module (JG673A)
 HP 6600 1-port OC-3/STM-1 (E1/T1) CPOS SFP HIM Module (JC161A)
 HP 6600 2-port OC-3/STM-1 (E1/T1) CPOS SFP HIM Module (JC162A)
 HP 6600 2-port OC-3/STM-1 (E3/T3) CPOS SFP HIM Module (JC169A)
 HP 6600 1-port OC-3/STM-1 (E3/T3) CPOS SFP HIM Module (JC170A)
 HP 6600 4-port OC-3c/STM-1c or 2-port OC-12c/STM-4c POS SFP HIM Module (JC172A)
 HP 6600 2-port OC-3c/STM-1c or 1-port OC-12c/STM-4c POS SFP HIM Module (JC173A)
 HP 6600 1-port OC-48c/STM-16c POS/CPOS SFP HIM Module (JC494A)
 HP 6600 1-port OC-3c/STM-1c ATM SFP HIM Module (JC175A)
 HP 6600 2-port OC-3c/STM-1c ATM SFP HIM Module (JC495A)
 HP 6600 4-port GbE SFP HIM Module (JC171A)
 HP 6600 8-port GbE SFP HIM Module (JC174A)
 HP 6600 4-port Gig-T HIM Module (JC163A)
 HP 6600 8-port Gig-T HIM Module (JC164A)
 HP 6600 1-port 10-GbE XFP HIM Module (JC168A)
 HP MSR 2-port Enhanced Sync/Async Serial MIM Module (JD540A)
 HP MSR 4-port Enhanced Sync/Async Serial MIM Module (JD541A)
 HP MSR 8-port Enhanced Sync/Async Serial MIM Module (JD552A)
 HP MSR 2-port Gig-T MIM Module (JD548A)
 HP MSR 8-port E1/CE1/PRI (75ohm) MIM Module (JD563A)
 HP MSR 8-port E1/Fractional E1 (75ohm) MIM Module (JF255A)
 HP MSR 8-port T1/CT1/PRI MIM Module (JC160A)
 HP MSR 1-port FE3/CE3 MIM Module (JD630A)
 HP MSR 8-port T1/Fractional T1 MIM Module (JC159A)
 HP MSR 1-port T3/CT3/FT3 MIM Module (JD628A)
 HP 6600 8-port 10/100Base-T HIM Module (JC575A)
 HP 6600 2-port OC-48c/STM-16c RPR SFP HIM Module (JC576A)
 HP 6600 48-port GbE SFP Service Aggregation Platform Module (JG556A)
 HP 6600 48-port Gig-T Service Aggregation Platform Module (JG567A)
 HP 6600 24-port GbE SFP Service Aggregation Platform Module (JC568A)
 HP MSR 8-port E1/CE1/PRI (75ohm) HMIM Module (JG452A)
 HP MSR 4-port E1/CE1/PRI HMIM Module (JG451A)
 HP MSR 2-port E1/CE1/PRI HMIM Module (JG450A)
 HP MSR 1-port T3/CT3/FT3 HMIM Module (JG435A)
 HP MSR 1-port E3/CE3/FE3 HMIM Module (JG436A)

Memory

HP 6600 1GB SDRAM (JC179A)

HP 6602 Router (JC176A)

HP RPS 800 Redundant Power Supply (JD183A)
 HP X290 MSR30 1m RPS Cable (JD637A)

HP 6604 Router Chassis (JC178B)

HP X130 10G SFP+ LC SR Transceiver (JD092B)
 HP X130 10G SFP+ LC LR Transceiver (JD094B)
 HP X130 10G SFP+ LC ER 40km Transceiver (JG234A)
 HP 7500 650W DC Power Supply (JD209A)

HP 6604 Router Chassis (JC178B) (Continued)

HP 7500 650W AC Power Supply (JD217A)
HP 6604 Dustproof Frame (JC572A)
HP 6604 Spare Fan Assembly (JC569A)
HP 6600 Router Software License (JC180A)
HP 6600 MCP-X1 Router Main Processing Unit (JG355A)
HP 6600 MCP-X2 Router Main Processing Unit (JG356A)
HP 6600 RPE-X1 Main Processing Unit (JC165A)
HP 6600 RSE-X1 Main Processing Unit (JC566A)
HP 6600 24-port GbE SFP Service Aggregation Platform Module (JC568A)
HP 6600 48-port Gig-T Service Aggregation Platform Module (JC567A)
HP 6600 FIP-10 Flexible Interface Platform Router Module (JG357A)
HP 6600 FIP-110 Flexible Interface Platform Module (JC166B)
HP 6600 FIP-20 Flexible Interface Platform Router Module (JG358A)
HP 6600 FIP-210 Flexible Interface Platform Module (JC167B)

HP 6608 Router Chassis (JC177B)

HP X130 10G SFP+ LC SR Transceiver (JD092B)
HP X130 10G SFP+ LC LR Transceiver (JD094B)
HP X130 10G SFP+ LC ER 40km Transceiver (JG234A)
HP 7500 650W DC Power Supply (JD209A)
HP 7500 650W AC Power Supply (JD217A)
HP 6608 Spare Fan Assembly (JC570A)
HP 6608 Dustproof Frame (JC573A)
HP 6600 Router Software License (JC180A)
HP 6600 MCP-X1 Router Main Processing Unit (JG355A)
HP 6600 MCP-X2 Router Main Processing Unit (JG356A)
HP 6600 RPE-X1 Main Processing Unit (JC165A)
HP 6600 RSE-X1 Main Processing Unit (JC566A)
HP 6600 24-port GbE SFP Service Aggregation Platform Module (JC568A)
HP 6600 48-port Gig-T Service Aggregation Platform Module (JC567A)
HP 6600 FIP-10 Flexible Interface Platform Router Module (JG357A)
HP 6600 FIP-110 Flexible Interface Platform Module (JC166B)
HP 6600 FIP-20 Flexible Interface Platform Router Module (JG358A)
HP 6600 FIP-210 Flexible Interface Platform Module (JC167B)

HP 6616 Router Chassis (JC496A)

HP X130 10G SFP+ LC SR Transceiver (JD092B)
HP X130 10G SFP+ LC LR Transceiver (JD094B)
HP X130 10G SFP+ LC ER 40km Transceiver (JG234A)
HP 6600 650W AC Power Supply (JC492A)
HP 6600 650W DC Power Supply (JC493A)
HP 6616 Spare Fan Assembly (JC571A)
HP 6616 Dustproof Frame (JC574A)
HP 6600 RPE-X1 Carrier Card (JC497A)
HP 6600 Router Software License (JC180A)
HP 6600 MCP-X1 Router Main Processing Unit (JG355A)
HP 6600 MCP-X2 Router Main Processing Unit (JG356A)
HP 6600 RPE-X1 Main Processing Unit (JC165A)
HP 6600 RSE-X1 Main Processing Unit (JC566A)
HP 6600 24-port GbE SFP Service Aggregation Platform Module (JC568A)
HP 6600 48-port Gig-T Service Aggregation Platform Module (JC567A)
HP 6600 FIP-10 Flexible Interface Platform Router Module (JG357A)
HP 6600 FIP-110 Flexible Interface Platform Module (JC166B)
HP 6600 FIP-20 Flexible Interface Platform Router Module (JG358A)
HP 6600 FIP-210 Flexible Interface Platform Module (JC167B)

**Learn more at
hp.com/networking**

**Sign up for updates
hp.com/go/getupdated**



Share with colleagues



Rate this document

