

Product Highlights

Power over Ethernet plus 10G

710XP-12TH-2S

- 8x 10M-1GbE RJ45 @ 30W
- 4x 10M-1GbE RJ45 @ 60W
- 2 x 1/10G SFP+ Uplinks
- Fanless for silent operation
- Integrated single power supply
- Small form factor for constrained spaces

710XP-28TNH-2S

- 24x 10M-1GbE RJ45 @ 30W
- 4x 100M-5GbE RJ45 @ 90W
- 2 x 1/10G SFP+ Uplinks
- Integrated single power supply, fans

Hardware

- Built in single power supply
- Mode button for user reset
- Secureboot system with Hardware Root of Trust

Operational Simplicity

- Zero Touch Provisioning
- On-Prem or Cloud Managed

Traffic and Flow Monitoring

- sFlow
- IPFIX

Segmentation and Overlay

- 802.1Q VLANs
- IPv4/v6 VRFs
- VXLAN networks*
- EVPN L2 (type 2)*

Cognitive Campus Resilience *

- Active/Active MLAG aggregation
- Dynamic uplink load balancing
- SSU for software upgrades and hitless patching

Arista Extensible Operating System (EOS®)

- Fine-grained truly modular network OS
- Stateful Fault Containment (SFC)
- Stateful Fault Repair (SFR)
- Full access to Linux shell and tools
- Extensible platform - bash, python, C++ , GO

Overview

The Arista CCS-710XP power efficient campus edge switches include a fanless model and also models with fans. The fanless compact power over ethernet switch was designed to extend the Cognitive Campus network into space-constrained and quiet environments such as conference rooms, retail showrooms, broadcast control rooms and small enclosures like ATMs. With multiple mounting options, the CCS-710 series switches are well suited for any deployment where sound and space are as important as reliable network operations.



Arista 710XP-12TH Series PoE Switch



Arista 710XP-28TNH Series PoE Switch

Arista EOS

The Arista CCS-710XP series runs the same Arista EOS software as all Arista routing and switching products, simplifying network administration and software life cycle management.

Arista EOS is a modular operating system with an architecture that separates state from protocol processing and application logic. Built on top of a hardened Linux kernel, all EOS processes run in protected memory spaces and exchange state through an in-memory database. This multi-process state sharing architecture provides the foundation for smart system updates and self-healing resiliency. With Arista EOS, Linux based tools for monitoring and automation can be run natively on the switch.

*Not currently supported in EOS

CloudVision

CloudVision is Arista's management plane solution for simplifying network operations. Built on a modern state-streaming architecture, CloudVision is a multi-function software platform that enables a suite of capabilities for automated provisioning, change control, continuous compliance, real-time telemetry, predictive analytics and 3rd party management plane orchestration. As a multi-domain solution, CloudVision is a single management platform across data center, campus, WiFi, multi-cloud, and routing interconnect use-cases. CloudVision is offered as an on-premise appliance (virtual or physical) as well as a SaaS solution, CloudVision-as-a-Service.

CloudVision Cognitive Unified Edge

The Arista CCS-710XP also supports CloudVision CUE, a SaaS-based management platform delivering a simplified CloudVision experience focused on the network edge to the commercial market space. This 'Edge as-a-Service' approach provides streamlined dashboards to manage both wired and wireless connectivity, with plug and play Zero Touch Provisioning and AI-powered insights to simplify the network edge with a turnkey solution.

Cognitive Campus

Arista's family of switching and WiFi platforms are managed through a single Cognitive Management Plane in CloudVision. Real time telemetry, time series database for after the fact troubleshooting with sub second granularity, and AI/ML powered analytics to monitor the infrastructure, users and applications on the Network. Rich change control used to simplify and automate the deployment and maintenance of campus infrastructure.

Cognitive Segmentation

The CCS-710XP compact series supports industry standard 802.1X and RADIUS authentication and interoperates with leading authentication solutions. Authorized users and devices can be placed into policy assigned 802.1Q or EVPN VXLAN segments in the network, automating the network layer of zero trust architecture.

Cognitive Continuous PoE

Continuous PoE enables powering downstream devices even when the system is rebooted on a per port basis. Providing uninterrupted power to a devices and eliminates the need for a backup power source.

POE for Workspaces

The CCS-710XP delivers PoE networking in a compact, light weight and fanless form factor. Fans are used for the higher port count models. The fanless model supports new scenarios for deploying powered ethernet outside the wiring closet and into conference rooms, retail environments, remote or temporary workspaces, or sensitive locations such as classrooms and broadcast control booths where traditional fan cooled systems are too noisy or ambient cooling is preferred to forced air.

Power supply

The CCS-710XP-12TH has one 180W fixed internal AC power supply. The CCS-710XP-28TNH has one 460W internal AC power supply.

Arista Optics and Cables

The Arista 710XP series supports a wide range of 1G and 10G pluggable optics and cables. For details about the different optical modules and the minimum EOS Software release required for each of the supported optical modules, visit <https://www.arista.com/en/products/transceivers-cables>

Mounting Options

The CCS-710XP's modern aesthetics work in office desktop use cases. The optional magnetic mount allows the compact switch to be mounted to metal fixtures, in either vertical or under-counter applications. The optional "L" bracket kit, allows fixing to bottom/top flat surfaces. The optional 19" rack mount kit allows the switch and its external power supply to be installed in common IDF or datacenter racks. The DIN rail mount option allows the switch to be deployed in manufacturing or warehousing environments.

Operating Environment

The CCS-710XP's operating temperature is up to 40C/104F in the upright applications. In vertical, under counter or enclosed applications they support operation in ambient temperatures up to 35C/95F.

Layer 2 Features

- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree Protocol
- Rapid Per VLAN Spanning Tree (RPVST+)
- 4096 VLAN IDs, 256 active VLANs
- Q-in-Q
- 802.3ad Link Aggregation/LACP
 - MLAG (Multi-Chassis Link Aggregation)*
 - Uses IEEE 802.3ad LACP
- 802.1Q VLANs/Trunking
- 802.1AB Link Layer Discovery Protocol
- 802.3x Flow Control On Uplinks*
- Jumbo Frames (9216 Bytes)
- IGMP v1/v2/v3 snooping
- Storm Control

Layer 3 Features

- Routing Protocols: OSPF, OSPFv3, BGP, MP-BGP, IS-IS, and RIPv2
- 64-way Equal Cost Multi-path Routing (ECMP)
- Bi-Directional Forwarding Detection (BFD)
- VRF
- Route Maps
- IGMP v2/v3
- PIM-SM* / PIM-SSM* / PIM-BIDIR*
- Anycast RP (RFC 4610)*
- VRRP
- Virtual ARP (VARP)*
- Policy Based Routing (PBR)*
- Selective Route Download

Advanced Monitoring and Provisioning

- Latency Analyzer and Microburst Detection (LANZ)*
- Zero Touch Provisioning (ZTP)
- Integrated packet capture/analysis with TCPDump
- Advanced Mirroring - Port Mirroring (4 sessions)
 - Enhanced Remote Port Mirroring
 - L2/3/4 Filtering on Mirror Sessions
- Advanced Event Management suite (AEM)
 - CLI Scheduler
 - Event Manager
 - Event Monitor
- Linux tools
- Sampled FlowTracking
- RFC 3176 sFlow
- IPFIX support
- Restore & configure from USB
- eAPI
- IEEE 1588 PTP (Transparent Clock and Boundary Clock)*

Virtualization Support

- VXLAN Tunnel Virtual Port Termination*
- VXLAN Bridging*
 - EVPN type 2*

Security Features

- Service ACLs
- Control Plane Protection (CPP)
- Ingress / Egress ACLs using L2, L3, L4 fields
- Ingress / Egress ACL Logging and Counters
- MAC ACLs
- 802.1X Enhancements
 - Multi-Host 802.1X AUTH
 - MAC-Based AUTH (MAB)
 - Dynamic VLAN assignment
 - Named VLAN support
- ACL Deny Logging
- ACL Counters
- Atomic ACL Hitless restart*
- DHCP Relay
- MAC access list security
- TACACS+
- RADIUS
- RadSec*
- ARP trapping and rate limiting

Quality of Service (QoS) Features

- Up to 8 queues per port
- 802.1p based classification
- DSCP based classification and remarking
- Explicit Congestion Notification (ECN)*
- QoS interface trust (COS / DSCP)
- Strict priority queueing
- Weighted Round Robin (WRR) Scheduling
- Per-Priority Flow Control (PFC)*
- ACL based DSCP Marking
- ACL based Policing
- Policing/Shaping
- Rate limiting

PoE Capabilities

- LLDP enhancements for PoE including Media Endpoint Discovery (MED) attributes reporting
- PoE Controls
- VLAN for VoIP, QoS
- Cognitive PoE

Network Management

- Dedicated Management plane Ethernet port
- CloudVision
- Configuration session commit and rollback
- RS-232 Serial Console Port
- USB Port
- SNMP v1, v2, v3
- Management over IPv6
- Telnet and SSHv2
- Syslog
- AAA
- Industry Standard CLI

* Not currently supported in EOS

For detailed EOS feature support visit <https://www.arista.com/en/support/product-documentation/supported-features>

- Beacon LED for system identification
- System Logging
- Environment monitoring
- MLAG ISSU*
- Maintenance mode

Extensibility

- Linux Tools
 - Bash shell access and scripting
 - RPM support
 - Custom kernel modules
- Programmatic access to system state
 - Python
 - C++

Standard Compliance

- 802.1D Bridging and Spanning Tree
- 802.1p QoS/COS
- 802.1Q VLAN Tagging
- 802.1w Rapid Spanning Tree
- 802.1s Multiple Spanning Tree Protocol
- 802.1AB Link Layer Discovery Protocol
- 802.3ad Link Aggregation with LACP
- 802.3az Energy Efficient Ethernet (EEE)*
- 802.3x Flow Control
- 802.3u 100BASE-TX
- 802.3ab 1000BASE-T
- 802.3z Gigabit Ethernet
- 802.3ae 10 Gigabit Ethernet
- 802.3af/at 15W/30W Power over Ethernet (PoE)
- 802.3bt 60W Power over Ethernet (PoE)
- RFC 2460 Internet Protocol, Version 6 (IPv6) Specification
- RFC 2461 Neighbor Discovery for IP Version 6 (IPv6)
- RFC 2462 IPv6 Stateless Address Auto-configuration
- RFC 2463 Internet Control Message Protocol (ICMPv6) for the Internet Protocol Version 6 (IPv6) Specification
- IEEE 1588-2008 Precision Time Protocol*

SNMP

- RFC 3635 EtherLike-MIB
- RFC 3418 SNMPv2-MIB
- RFC 2863 IF-MIB
- RFC 2864 IF-INVERTED-STACK-MIB
- RFC 2096 IP-FORWARD-MIB
- RFC 4363 Q-BRIDGE-MIB
- RFC 4188 BRIDGE-MIB
- RFC 2013 UDP-MIB
- RFC 2012 TCP-MIB
- RFC 2011 IP-MIB
- RFC 2790 HOST-RESOURCES-MIB
- RFC 3636 MAU-MIB
- RMON-MIB
- RMON2-MIB
- HC-RMON-MIB

- LLDP-MIB
- LLDP-EXT-DOT1-MIB
- LLDP-EXT-DOT3-MIB
- ENTITY-MIB
- ENTITY-SENSOR-MIB
- ENTITY-STATE-MIB
- ARISTA-ACL-MIB
- ARISTA-QUEUE-MIB
- RFC 4273 BGP4-MIB
- RFC 4750 OSPF-MIB
- ARISTA-CONFIG-MAN-MIB
- ARISTA-REDUNDANCY-MIB
- RFC 2787 VRRPv2MIB
- MSDP-MIB
- PIM-MIB
- IGMP-MIB
- IPMROUTE-STD-MIB
- SNMP Authentication Failure trap
- ENTITY-SENSOR-MIB support for DOM (Digital Optical Monitoring)
- User configurable custom OIDs

Table Sizes

Ingress / Egress ACLs	1K / 512
MAC addresses	16K
IPv4/v6 Hosts	8K / 4K
IPv4/v6 Routes	2K / 512
ECMP	64-way
IGMP Groups	1024

See EOS release notes for Supported MIBs

*Not currently supported in EOS

Specifications

Feature/Model	710XP-12TH-2S	710XP-28TNH-2S
Ports	12 RJ45 2 10G SFP	24x1G, 4x5 mG RJ45 2 10G SFP
10M-1G UTP (30W) ¹	8	24
10M-1G UTP (60W) ²	4	
100M-5G UTP (90W) ²		4
10G	2	2
Switching ASIC capacity	208 Gbps (ingress + egress)	
Switch throughput (ingress + egress)	64 Gbps	128 Gbps
Packets/Second	95 Mpps	
Latency (RJ-45)	1.8 microseconds	
CPU	Quad Core ARM	
System Memory	8 GB	
System Flash	20 GB	
Packet Buffer	1.5 MB	
USB Ports	1	
Console Ports	1	
Power (Max, excluding PoE)	30W	100W
Power Input	180W fixed internal	460W fixed internal
Fans	None	2+1 (with redundancy)
Size (WxHxD)	10.6" x 1.75" x 10" (26.9 x 4.4 x 25.4 cm)	17.3" x 1.75" x 11" (44 x 4.35 x 27.9 cm)
Weight	6.17 lbs (2.8 kg)	TBD
EOS License Group (LIC-FIX)	G0	
CloudVision License Group	G0	
Minimum EOS	4.35.0	TBD

1: 802.3af/at

2: 802.3bt

Arista Optics and Cables

The Arista CCS-710XP Series supports a wide range of 1G and 10G pluggable optics and cables in the SFP ports. For details about the different optical modules and the minimum EOS Software release required for each of the supported optical modules, visit <https://www.arista.com/en/products/transceivers-cables>

Supported Optics and Cables

Interface Type	10G
10GBASE-CR	SFP+ to SFP+: 0.5m-5m
10GBASE-AOC	SFP+ to SFP+: 3m-30m
10GBASE-SRL	100m
10GBASE-SR	300m
10GBASE-LRL	1km
10GBASE-LR	10km
10GBASE-ER	40km
100Mb TX,1GbE SX/LX/TX	Yes

Power Supply Specifications

Supply	180W fixed internal PSU	460W fixed internal PSU
PoE Power available	150W	360W
Input Voltage	100-240VAC	100-240VAC
Input Current	2.78-5.18A	2.78-5.18A (?)
Input Frequency	50-60Hz	50-60Hz
Input Connector	IEC 320-C13	IEC 320-C13 (?)
Efficiency (Typical)	88%	88%

Environmental Characteristics

Operating Temperature ¹	0 to 40°C (32 to 104°F)
Storage Temperature	-40 to 70°C (-40 to 158°F)
Relative Humidity	5 to 90%
Operating Altitude	0 to 10,000 ft, (0-3,000m)

1. Certain airflow configurations or the use of higher power or reduced temperature range optics may reduce maximum operating temperature.

Emissions and Safety Compliance

EMC	<p>47 CFR FCC 15B Class A ICES-003 Issue 7 EN 55032:2015 EN IEC 61000-3-2:2019 EN 61000-3-3 KS C 9832 VCCI-CISPR 32:2016 AS/NZS CISPR 32:2015 +A1 2020 EN 300 386 TEC/SD/DD/EMC-221 CNS 15936 BS EN 55032:2015+A11:2020 BS EN IEC 61000-3-2 BS EN 61000-3-3</p>
Immunity	<p>EN 55035:2017+A11:2020 EN 300 386 KS C9835 BS EN 55035:2017+A11:2020</p>
Safety	<p>EN 62368-1:2020 + A11:2020 EN 62368-1:2014 + A11:2017 IEC-62368-1:2018 Korea KC Safety KC 62368-1 (2021-08) CSA/UL 62368-1:2019 NOM 019-SCFI-1998 CNS 15598-1 AS/NZS 62368.1:2022</p>
Certifications	<p>BSMI (Taiwan) FCC SDoC Class A (United States) ICES-003 (Canada) CE (European Union) KCC (South Korea) NRTL (North America) RCM (Australia/New Zealand) UKCA (United Kingdom) VCCI (Japan) TEC (India) ANATEL (Brazil) ICASA (South Africa) NOM Equivalency (Mexico)</p>
European Union Directives	<p>2014/35/EU Low Voltage Directive 2014/30/EU EMC Directive 2012/19/EU WEEE Directive 2011/65/EU RoHS Directive 2015/863/EU Commission Delegated Directive</p>
Further Information	<p>Product Certification Portal</p>

Product Number	Product Description
CCS-710XP-12TH-2S	Arista 710XP, 8x1G 30W, 4x1G 60W, 2x10G SFP+ compact switch, 1 x 180W AC PSU, no power cord
CCS-710XP-28TNH-2S-F	Arista 710XP, 24x1G 30W PoE, 4x5 mGig 90W PoE, 2x10G SFP+ front to rear air, 1 x 460W AC PSU, no power cord
KIT-CCS-710	Spare accessory kit for Arista 710P Series switches. (Power cords available separately)
KIT-CCS-710-DIN	Spare DIN-Rail Mount Kit for Arista 710P Series switches
KIT-CCS-710XP-12-RM	Spare Rack Mount Kit for Arista 710XP-12 Series switches
KIT-CCS-710XP-MGN	Spare Magnet Mount Kit for Arista 710XP-12 Series switches
LIC-FIX-G0-FLX-L	FLX-Lite License for Arista Fixed 1G/mG Group 0 Ethernet Switches - Full Routing upto 8K routes (includes E Features)
SS-CV-G0-SWITCH-1M	CloudVision Subscription Lic for 1-Month for 1 Switch. Arista Fixed 1G/mG Group 0 Platforms. Delivered via download only. Includes E, FLX-L.
SS-CV-LT-G0-SWITCH-1M	CloudVision Lite Subscription Lic for 1-Month for 1 Switch. Arista Fixed 1G/mG Group 0 Platforms. Delivered via download only.
SS-CVS-G0-SWITCH-1M	CloudVision as-a-Service Subscription Lic for 1-Month for 1 Switch. Arista Fixed 1G/mG Group 0 Platforms. Includes E, FLX-L.
SS-CVS-LT-G0-SWITCH-1M	CloudVision Lite as-a-Service Subscription Lic for 1-Month for 1 Switch. Arista Fixed 1G/mG Group 0 Platforms.
SS-CVSC-G1-SWITCH-1M	CloudVision CUE as-a-Service Subscription Lic for 1-Month for 1 Switch. Arista Fixed 1G/mG Group 1 Platforms.

Product Number	Product Description
CAB-C13-US	Power Cord, North America, C13 to NEMA 5-15P, 8 Feet (2.5m)
CAB-C13-C14-INTL	Power Cord C13 to C14 (2m)
CAB-C13-EU	Power Cord, Europe, C13 to CEE 7/7, 8 Feet (2.5m)
CAB-C13-UK	Power Cord, United Kingdom, C13 to BS 1363/A, 8 Feet (2.5m)
CAB-C13-JP	Power Cord, Japan, C13-JIS8303, 15A/125V, 2.5m
CAB-C13-AUS	Power Cord, Australia, C13 to AS/NZS 3112, 8 Feet (2.5m)
CAB-C13-IT	Power Cord, Italy, C13 to CEI 23-16, 8 Feet (2.5m)
CAB-C13-AR	Power Cord, Argentina, C13 to IRAM 2073, 8 Feet (2.5m)
CAB-C13-IN	Power Cord C13 to India (10A) 2m
CAB-C13-ISR	Power Cord, Israel, C13-SI32, 10A/250V, 2.5m
CAB-C13-CHN	Power Cord, China, C13-GB2099, 10A/250V, 2.5m
CAB-C13-BR	Power Cord, Brazil, C13-NBR14136, 10A/250V, 2.5m
CAB-C13-SWZ	Power Cord, Switzerland, C13-SN441011, 10A/250V, 2.5m
CAB-C13-TW	Power Cord, Taiwan BSMI, C13-CNS15767/690, 2.5m

Warranty

The Arista CCS-710XP switches come with a one-year limited hardware warranty, which covers parts, repair, or replacement with a 10 business day turnaround after the unit is received.

Service and Support

Support services including next business day and 4-hour advance hardware replacement are available. For service depot locations, please see: <http://www.arista.com/en/service>

Headquarters

5453 Great America Parkway
Santa Clara, California 95054
408-547-5500

Support

support@arista.com
408-547-5502
866-476-0000

Sales

sales@arista.com
408-547-5501
866-497-0000