SAMSUNG FIIP



Meet anywhere. Capture anything. Simplify everything.

Portable Interactive UHD Digital Flipchart

Game-changing ideas can get lost in the shuffle to find or prepare a room. The Samsung Flip simplifies and fast tracks everything. The portable, interactive UHD digital flipchart drives more productive and efficient collaboration without the hassle of complicated set-ups. Meetings can take place anywhere, any time and on time. With the Samsung Flip, everything you need will always be ready to go.







Easy to Set Up, Easy to Learn, Easy to Train

The Flip takes only minutes to set up, and its tablet-style user interface is intuitive. Portability makes any space a meeting room. Sensors activate the Flip automatically, while 4K UHD and landscape and portrait modes add engagement.

ს)) N

Meetings Start on Time

Skip the lengthy boot-up. Embedded sensors activate Flip as you approach, remove the pen from the holder or rotate the display.

Seamless Collaboration

Capture and share, wired or wirelessly. Connect, view and manage Flip from a mobile device. And up to four people can write simultaneously.

Document Viewer*

Open and annotate Microsoft PowerPoint, Word and Adobe PDF files directly on the Flip.

Share on the Big Screen for Everyone to See

You can wirelessly mirror everything you're doing on the Flip to another screen in the room. Everyone can have a front-row view.

Write and Draw

Premium Multi-Touch Collaboration makes writing smooth and fast, with a pen-and-paper feel. And meeting participants can use virtually any writing tool, such as the blunt end of a pen.



<u>_</u>

կոլ

Save and Instantly Share Meeting Notes

All your notes are automatically saved as you work. And after the meeting, it's easy to instantly share those notes via email (now with LDAP support), network, printer or by saving them to a USB drive.

Safe and Secure

Keep notes confidential by locking the display, or lock a specific note with a PIN. Enterprise WPA2 adds secure wireless connectivity.

*Available August 2018 at no cost with a firmware upgrade.

Contact Us: samsung.com/b2bdigitalsignage



Digital Display Store https://www.digitaldisplaystore.com/ 855-958-0757 Sales@DigitalDisplayStore

SAMSUNG FIIP



			WM55H
Panel	Diagonal Size		55"
	Туре		60Hz E-LED
	Resolution		3,840 x 2,160 (Landscape), 2,160 x 3,840 (Portrait)
	Brightness (Typ.)		300 (without glass), 220 (with glass)
	Contrast Ratio (Typ.)		4700:1 (without glass)
	Viewing Angle (H / V)		178 / 178
	Response Time (G-to-G)		8ms (Typ.)
			Built in Speaker (10W x 2)
Connectivity	Input	Video	HDM11
	mpar	USB	USB 2 (Ver 2.0 x 2, Side 1, Sensor Assy 1)
	Output	Touch Out	Touch Out 1 (Side, USB Upstream Type)
	Internal	Sensor	NFC, Acceleration Sensor, Proximity Sensor
	External	Control	Touch Input RJ45 (Not for User Control)
Touch			Advanced IR
	Number of Simultaneous Drawing		4 Users Drawing Simultaneously
	Touch Pen Type		Passive Pen
	Object Recognition Range		2mm / 4mm / 8mm / 50mm (0.08" / 0.16" / 0.32"/1.2")
	Touch Response Time		38ms ~ 46ms (According to number of Multi Drawings)
Power	Туре		Internal
	Power Supply		AC100-240V 50/60Hz
		Max (W/h)	165
	Power Consumption	Typical (W/h)	100
		Rating (W/h)	150
		Standby (W/h)	0.5
		BTU (W/h)	52.65
Mechanical		Display (W x H x D)	513" x 31.7" x 2.04"
ricentarieut		Package (W x H x D)	578 * 35.4 * 88.3*
		Display	6371bs
	Weight	Package	769 lbs.
	Color		Light Gray
	VESA Mount		Light Giby 400 x 400
	Protection Glass		Ves
	Stand Type		Moving Stand (STN-WM55H Sold Separately), Wall Mount (WMN-65755D Sold Separately)
	Rotation		Available with Optional Moving Stand STM-MMS5H (Rotation Cyclinder Included)
	Power Cable Length		Available with optional moving stand site messari (kotadon synthet included) 3m
Operation	Operating Temperature		32°F-104°F 32°F-104°F
operation	Humidity		
Feature	Key		Tip App
i cuture	110)	H/W	Super Clear Coating, Temperature Sensor, Pivot Display, Clock Battery (168 Hrs. Clock Keeping), Built in Speaker (10W x 2), Wi-Fi Module Embedded
	Special	S/W	File S/W
	Special	Platform	Kant-M (Tizen 3.0)
	Internal Player (Embedded H/W)	Processor	Kalteri (1261-30) (ZA2 Quady (1261+3)
		On-Chip Cache Memory	L1(D): 32KB L2 (Unified): 1MB
		Clock Speed	Tride 20 Oud
		Main Memory Interface	L/DR24F0 Quad
		Graphics	22 and 30 Graphics Engine, Up to 1920 x 1080, 32 bpp, Supports OpenGL ES
		Storage	20 and 30 draphics trajance of to 122 x 1000, 22 obje. Supports Openice CS 868 (2.4568) Occupied by 0(5, 53568 Available)
		-	Video Decoder: MPEG-1/2/4, H263, H264/AVC, UHD H.264/AVC, VC-1, AVS+, HEVC, JPEG, PNG, VP8, VP9
		Multimedia	Video Decuder, MESCO 7/2/4, FL20, FL204/AVC, UFD FL204/AVC, VC-1, AV35, FEVC, JFEO, FNO, VF5 Audio Decuder, KC3 (DD), MPEG
		IO Ports	USB 2.0
		Operating System	Samsung Proprietary OS (VD Linux)
Accessories	Included		Passive Pen (2), Power Cable, Touch Out Cable (USB Upstream)
	Optional	Stand	STN-WHS5H
			File Moving Stand (Sold Separately)
Mechanical	Dimensions		
Mechanical		Stand (W x H x D)	
		Package (W x H x D)	66.2" x 87" x 40.9" 699 lbs.
	Weight	Stand	
	Package		92.20s.
	Color VESA Mount		Light Gray
	VESA Mount		400 x 400
Co	Rotation	ina an Ellin Cat	Prot Supports (90')
	Rotation Extension Connectivity	from Flip Set	HDMI1/TouchOut1/RJ451/Power1
	Rotation Extension Connectivity Included	from Flip Set	

Connectivity

- 1. USB1 (1.0A)
- 2. LAN
- 3. RS232C In
- 4. HDMI In
- 5. Touch Out









samsung.com/business insights.samsung.com samsung.com/b2bdigitalsignage Learn More 1-866-SAM4BIZ Product Support Follow Us 🕞 youtube.com/samsungbizusa 🕥 @SamsungBizUSA

DigitalDisplayStore

SAMSUNG FIIP

©2018 Samsung Electronics America, Inc. Samsung is a registered mark of Samsung Electronics Corp., Ltd. Specifications and design are subject to change without notice. Non-metric weights and measurements are approximate. Simulated screen images. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective manufacturers and companies. See samsung.com for detailed information. Printed in USA. LFD-FLIPDSHT-JUL18T