

## Rugged Mini

MOBILE DRIVE Data Sheet

## Rugged Design. Mini Size.

- Shock-, rain-, and pressure-resistant
- USB 3.0: up to 4× faster than USB 2.0
- Works with iPad Connect your LaCie drive with USB-C
- Compatible with Thunderbolt 4
- Rescue Data Recovery Services

design by neil poulton

## **Product Overview**

The LaCie Rugged Mini drive shares features with our popular Rugged drive, like shock resistance, drop resistance, and rubber sleeve for added protection. But the LaCie Rugged Mini is also rain- and pressure-resistant—you can drive over it with a 1-ton car, and it still works!<sup>1</sup> Its small size makes it completely mobile, and its tough exterior provides protection against accidental drops, shock, or pressure. The Rugged Mini is the most compact member of the LaCie Rugged drive family and will appeal to a wide range of users.

## **Use Cases**

- Students: Store music, video, and confidential school documents on a device that fits in a backpack.
- Travelers: Protect valuable data from loss, theft, or accident while on the road.
- Photographers: Small form factor and toughness make this product perfect for use in the field or to safely deliver large files to customers and partners.
- Videographers: Perfect for shuttling dailies or other footage to the studio and transfering files quickly thanks to USB 3.0.

1 Determined by a test that approximates a real-world scenario in which the hard drive remained functional, despite aesthetic damage, after the product was driven over by an approximately 1-ton car (1000kg/2205 lbs).







# Rugged Mini



## MOBILE DRIVE

| Specifications 1-2TB      |                    |                |                          |                   |  |  |  |  |  |
|---------------------------|--------------------|----------------|--------------------------|-------------------|--|--|--|--|--|
| Retail Packaging          | Product Dimensions | Box Dimensions | Master Carton Dimensions | Pallet Dimensions |  |  |  |  |  |
| Length(in/mm)             | 5.29in/134.6mm     | 7.32in/186mm   | 10.47in/266mm            | 40.94in/1040mm    |  |  |  |  |  |
| Width(in/mm)              | 3.385in/86mm       | 5.07in/129mm   | 7.40in/188mm             | 46.85in/1190mm    |  |  |  |  |  |
| Height(in/mm)             | 073in/18.73mm      | 1.37in/35mm    | 5.31in/135mm             | 42.51in/1080mm    |  |  |  |  |  |
| Weight(lb/kg)             | 0.61lb/0.28kg      | 0.86lb/0.394kg | 5.512lb/2.5kg            | 826.7lb/375kg     |  |  |  |  |  |
| Quantities 1-2TB          |                    |                |                          |                   |  |  |  |  |  |
| Boxes per Master Carton   | 9                  |                |                          |                   |  |  |  |  |  |
| Master Cartons per Pallet | 90                 |                |                          |                   |  |  |  |  |  |
| Pallet Layers             | 6                  | 6              |                          |                   |  |  |  |  |  |
| Retail Packaging 4-5TB    | Product Dimensions | Box Dimensions | Master Carton Dimensions | Pallet Dimensions |  |  |  |  |  |
| Length(in/mm)             | 5.31in/135.1mm     | 7.32in/186mm   | 10.47in/266mm            | 41.33in/1050mm    |  |  |  |  |  |
| Width(in/mm)              | 3.385in/86mm       | 5.07in/129mm   | 7.40in/188mm             | 46.85in/1190mm    |  |  |  |  |  |
| Height(in/mm)             | 1.02in/26mm        | 2.04in/52mm    | 5.31in/135mm             | 40.94in/1040mm    |  |  |  |  |  |
| Weight(lb/kg)             | 0.72lb/0.33kg      | 1.102lb/0.5kg  | 5.512lb/2.5kg            | 722.7lb/327.8kg   |  |  |  |  |  |
| Quantities 4-5TB          |                    |                |                          | ·                 |  |  |  |  |  |
| Boxes per Master Carton   | 5                  | 5              |                          |                   |  |  |  |  |  |
| Master Cartons per Pallet | 120                | 120            |                          |                   |  |  |  |  |  |
| Pallet Layers             | 6                  |                |                          |                   |  |  |  |  |  |

## • Interface: USB 3.2 Gen 1 (up to 5Gb/s)

- Works With USB-C host: USB4, USB 3.0, Thunderbolt™ 4, Thunderbolt™ 3
- Compatible with most Windows and macOS systems. Visit lacie.com/os for details<sup>1,2</sup>

What's Included • LaCie<sup>®</sup> Rugged Mini 3.0 drive

- USB-C cable
- Quick Install Guide

Minimum free disk space: 600MB recommended

Rescue Data Recovery Services

| Region | Model Number | Capacity | Limited Warranty (years) | UPC Code     | EAN Code      | Multi-Pack UPC |
|--------|--------------|----------|--------------------------|--------------|---------------|----------------|
| WW     | LAC301558    | 1TB      | 3                        | 093053827984 | 3660619315581 | 10093053827981 |
| WW     | LAC9000298   | 2TB      | 3                        | 093053003272 | 3660619005840 | 10093053003279 |
| WW     | LAC9000633   | 4TB      | 3                        | 093053014117 | 3660619013814 | 10093053014114 |
| ww     | STJJ5000400  | 5TB      | 3                        | 763649139578 | 3660619407927 | 10763649139575 |

## LACIE.COM

© 2022 Seagate Technology LLC. All rights reserved. Seagate, Seagate Technology, LaCie, and the LaCie logo are trademarks or registered trademarks of Seagate Technology LLC or one of its affiliated companies in the United States and/or other countries. All other trademarks or registered trademarks are the property of their respective owners. When referring to drive capacity, one gigabyte, or GB, equals one billion bytes and one terabyte, or TB, equals one thousand billion bytes. Your computer's operating system may use a different standard of measurement had report a lower capacity. In addition, some of the listed capacity is used for formatting and other functions and will not be available for data storage. Complying with all applicable copyright laws is the responsibility of the user. Seagate reserves the right to change, without notice, product offerings or specifications. DS1961.5-2212 AMER