


EWS2910P-FIT



EnGenius Fit Layer 2 Plus Managed EWS2910P-FIT 8-Port Gigabit PoE Switch with 55W Budget, 2 SFP Uplink Ports

Simple • Secure • Smart



The EnGenius Fit Managed Switch EWS2910P-FIT is an 8-port Gigabit PoE Layer 2 plus switch with a 55W PoE budget and 2 SFP uplink ports.

Manage your network onsite or on-the-go through our **FitXpress** cloud-based mobile app or web portal. Additionally, **FitController** gives you greater control of your network using plug-n-play hardware with embedded network management software. Admins can easily view detailed analytics from a single pane of glass as well as monitor and troubleshoot issues instantly. With its business-class features, the EnGenius Fit Managed Switch provides secure, reliable, and high-performance switching while reducing capital and operating expenses for cost-conscious small businesses.

Features & Benefits

- 8 10/100/1000 Base-T GbE ports.
- Full-featured layer 2 plus switching.
- 802.3af PoE ready on all ports with 55W PoE budget
- 20 Gbps switching capacity.
- Setup in minutes with app-based step by step instructions.
- Quick-scan device register, emote monitoring, and troubleshooting.
- Real-time system metrics, analytics, and remote configurations.
- Manage your network onsite or on-the-go through our **FitXpress** cloud-based mobile app or web portal.
- **FitController** gives you greater control of your network using plug-n-play hardware with embedded network management software.
- Monitor a site or multiple sites with no recurring cost or licensing fee.
- Security - access control list/port security; 802.1x authentication.
- IGMP & MLD snooping provides advanced multicast filtering & network efficiency.
- 802.3ad Link Aggregation (LACP), Spanning Tree (STP), Rapid Spanning Tree (RSTP) & Multiple Spanning Tree (MSTP)
- Voice VLAN for fast, reliable deployment of VoIP services.
- Advanced QoS with IPv4/IPv6 ingress traffic filtering (ACLs) & prioritization.
- Standards-based technology ensures interoperability with existing standards-based network devices.
- Dual firmware images improve reliability & network uptime.

Technical Specifications

EWS2910P-FIT

Port Standards

802.3 10Base-T Ethernet

802.3u 100Base-TX Ethernet

802.3ab 1000Base-T Ethernet

802.3x Full-Duplex Flow Control

Network Ports

8 10/100/1000 Mbps Ports

2 10/100/1000 Mbps SFP Ports

PoE Capable Ports

1-8 (802.3af only)

All Gigabit Ethernet ports can output up to 15 Watts

Total PoE Budget

55W

SDRAM

256MB

Flash Memory

32MB

Power Source

100 ~ 240VAC, 50-60Hz

PHYSICAL INTERFACE

LED Indicators

Power LED

Fault LED

PoE Max LED

LAN Mode LED

PoE Mode LED

Ports

Link/Activity/Speed (per Ethernet port)

SOFTWARE FEATURES

Multiple IP Interface

20 IPv6 address

ARP Table

Max. 192 ARP entries

Static ARP

Static 192 ARP entries

IPv4 Static Route

Max. 59 entries

IPv6 Static Route

Max. 5 entries

SOFTWARE FEATURES (L2 FEATURE)

MAC Address Table

8K

Jumbo Frame

9K

Multicast Group

Max 256 groups

Port Security

Max. 256 Entries

SSL Certificate

Certificate/Key Update

L2 Features

802.1Q VLAN tagging

VLAN Table

Port-based VLAN

Voice VLAN

GARP VLAN Registration Protocol

802.1d Spanning tree:

RSTP

CIST

MSTP

802.3ad Link Aggregation

Loopback Detection

L3 Feature

IGMP Snooping

MLD Snooping

DHCP Snooping

DHCP Relay

Static Route

Port Settings

Multicast Filtering

EEE

Port Isolation

Port Mirror

Jumbo Frames

LLDP

Security

802. 1X Radius Authentication Protocol

Access:

Web:

HTTP Service

HTTPs Service

Command Line Interface (CLI):

Telnet Service

SSH Service

Port Security

Radius Server

DoS Prevention

System Settings

IP Settings:

IPv4 Management

IPv6 Management

IPv4 Network

ARP Table

ARP Statistics

Simple Network Time Protocol (SNTP)

Analyze

Log:

Local Logging

Remote Logging

Diagnostic

Cable Diagnostics

Ping Test

IPv6 Ping Test

Trace Route

Connection Diagnostic

Access Control List (ACL)

MAC Based ACL

MAC ACE

IPv4 ACL

IPv4 ACE

IPv6 ACL

IPv6 ACE

ACL (Port) Binding

SNMP

SNMP v1/v2c/v3 Support

RMON

RMON 1,2,3,9

QoS

CoS Mapping

DSCP Mapping

Port CoS

Bandwidth Control

Storm control

Advanced Mode:

Class Mapping

MIB/RFC Standards

RFC1213

RFC1493

RFC1757

RFC2674

RFC2863

ENVIRONMENTAL & PHYSICAL

Temperature Range

Operating: 32°F to 104°F (0°C to 40°C)

Humidity (Non-Condensing)

Operating: 5% - 95%

Package Contents

1x Fit L2+ Managed 8 Ports EWS2910P-FIT PoE Gigabit Switch

1 x Power Adapter

Quick Start Guide QR Code

FitXpress Cloud-Based Mobile App QR Code

DIMENSIONS & WEIGHTS

EWS2910P-FIT Device

Weight: 1.36 lbs. (620 g)

Length: 9.44" (240 mm)

Width: 4.13" (105 mm)

Height: 1.06" (27 mm)

Packaging

Weight: 3.3 lbs. (1495 g)

Length: 10.67" (271 mm)

Width: 6.61" (168 mm)

Height: 3.34" (85 mm)



Certifications

CE, FCC, IC

Warranty

1 year

Product Images



Power Connector

On/Off Button