



ECS2512



Cloud Managed 8-Port Multi-Gigabit 2.5G with 4 10G SFP+ Uplink Ports

Layer 2+ Switch with 4 10G SFP+ Uplink Ports for Large Businesses

Product Highlights

EnGenius Cloud Multi-Gigabit ECS2512 is an 8-Port, 2.5G per port, Layer 2+ Switch with 4 10G SFP+ uplink ports. Multi-Gig switches with enterprise-class features optimize network efficiency ensuring peak performance for large businesses. Select Cloud or on-premises management options based on network architecture, administrative permissions, technical aptitude, or budget.



Features & Benefits

- Full-Featured Layer 2+ Switching
- 8 10/100/1000/2500 Base-T GbE Ports to serve high-bandwidth devices
- 120 Gbps Switching capacity for improved performance
- 4 Dual-Speed 10G SFP+ (fiber) uplink ports
- Security - Access Control List/Port Security; 802.1X & RADIUS Authentication

Port Standards

- 802.3 10Base-T Ethernet
- 802.3u 100Base-TX Ethernet
- 802.3ab 1000Base-T Ethernet
- 802.3bz 2500/5000Base-T Ethernet
- 802.3x Full-Duplex Flow Control

Network Ports

8 10/100/1000/2500 Mbps Ports + 4x SFP+ Ports

Switching Capacity

120Gbps

SDRAM

512MB

Flash Memory

128MB

Power Source

100 ~ 240VAC, 50-60Hz

Physical Interface

LED Indicators

- Power LED
- Fault LED
- PoE Max LED
- LAN Mode LED
- PoE Mode LED

Ports

- Link/Activity/Speed (per Ethernet port)
- Link/Activity/Speed (per SFP slot)

Software Features(L3 Feature)

Multiple IP Interface

20 IPv6 address

ARP Table

Max. 192 ARP entries

Static ARP

Static 192 ARP entries

IPv4 Static Route

Max. 63 entries

IPv6 Static Route

Max. 21 entries

Software Features(L2 Feature)

Network Management

- EnGenius Cloud
- SkyKey
- ezMaster
- Local Web GUI

MAC Address Table

16K

Jumbo Frame

9K

Multicast Group

Max 256 groups

MLD Snooping

MLD Snooping: v1

QoS-Number of Priority Queues Supported

Queue 8

Trust Mode

Cos/802.1p

DSCP

CoS/802.1p-DSCP

Scheduling Mechanism

Strict / WRR/ Strict + WRR

Bandwidth Control

Port-based bandwidth control (Ingress/Egress)

Port Security

Max. 256 Entries

Access Control List (ACL)

MAC Based ACL

IPv4/IPv6 Based ACL

ACL Binding

Time base ACL

Web Graphical User Interface(GUI)

HTTP IPv4 / IPv6

HTTPS IPv4 / IPv6

SSL Certificate

Certificate/Key Import

SNMP

SNMP v1/v2c/v3 Support

RMON

RMON 1,2,3,9

System Time

Time Setting/Daylight saving

Common L2 Features

802.1d Spanning tree

Loopback Detection

Multicast Filtering

IGMP Multicast Forwarding

IGMP Snooping

MLD Multicast Forwarding

802.1Q VLAN tagging

802.3x flow control

802.3ad Link Aggregation

IPv4 DHCP Relay

IPv4 DHCP Snooping

IPv4 DHCP Snooping Source MAC Address Check-up

ARP Inspection

ARP Packet Validation (additional validation checks)

Voice VLAN

Port-based VLAN

Protocol-Based VLAN

CoS Mapping

802.1X Radius Authentication Protocol

IPv4 Settings

IPv6 Settings

IEEE 802.3az Energy Efficient Ethernet (EEE)

Command Line Interface (CLI)

SSH Server

Telnet Server

TFTP Client

Configuration Upgrade/ Backup

Simple Network Time Protocol (SNTP)

SYSLOG

802.1d Spanning tree

Environmental & Physical

Temperature Range

Operating: 32°F to 122°F (0°C to 50°C)

Humidity (Non-Condensing)

Operating: 5% - 95%

Package Contents

1x ECS Managed Multi-Gigabit Switch

1x Quick Installation Guide

1x Power Cord

1x RJ45 Console Cable

1x Rack Mount Kit

Device Dimensions & Weights

Weight: 5.7lbs (2.6 kg)

Width: 9.05" (230 mm)

Length: 12.99" (330 mm)

Height: 1.73" (44 mm)

Warranty

2 year

ECS2512

