

New dimensions on your desktop.

Dell Wyse D class cloud clients.

Dell Wyse D class cloud clients. Learn more. Here:

The new Dell Wyse D class: Strong. Compact. Affordable.

The Dell Wyse D class.

Introducing a line of advanced yet affordable dual and quad core thin clients and cloud PCs.*





Features new Dell Wyse D class.

Designed to allow your users to flourish within ever changing and demanding desktop environments, the new Dell Wyse D class offers you new dimensions in computing performance, high definition multimedia and operational flexibility in a compact affordable form.

The D class' compact frame hosts an array of display, peripheral and network connectivity plus further flexible networking, storage and I/O options; everything in fact to offer you the ideal cloud client for Citrix, Microsoft and VMware VDI environments.

Dell Wyse Device Manager supports the D class with scalable enterprise-wide management. From fast 'day one' out-of-the-box deployment, to patching and updates and on to granular desktop device management – all with secure end-to-end encrypted communications.

When it comes to energy efficiency the D class is designed to out-perform other more power hungry desktop alternatives, including other thin clients in its class. Its silent, disk and fan-less design contributes considerably to lowering an organization's carbon footprint through power usage and emissions.

Cloud clients



Software

Management



User experience

0000

acceleration

User experience

optimization

Start



SUSE Linux

Dell Wyse enhanced

Suse



Microsoft Windows

Embedded Standard 2009





Take a tour of the D class range





Your all around high performer.

Presenting high performance on your desktop.

Need to deploy a dependable platform to display, manipulate and work with high definition multimedia, voice and video in a virtualized environment? The D class' hardware acceleration engine and dual monitor support offers your users outstanding performance and display capabilities across 2D, 3D and HD video applications.

High performance processor family.

Driving the D class' high speed and performance are two powerful, energy saving processors that offer you a strong all around platform on which to support an increasingly diverse range of user, application and operating requirements: the AMD G-Series dual core T48E 1.4 GHz processor and quad core AMD G-Series SOC 1.5GHz.



Continue tour



Connectivity Fast and flexible.



Mounting options.

The Dell Wyse D class can be placed vertically on desktops or mounted to walls.







dellwyse.com

Continue tour

Energy conscientious





That's Dell Wyse EarthSmart computing.

With Dell Wyse D class and through our EarthSmart Computing initiative we are committed to helping organizations implement an energy efficient computing strategy – one that offers a more efficient and productive computing experience for your users with a positive effect on energy wastage, heat and carbon emissions.

Energy efficient.

D class cloud clients use 9 watts of power in typical use*. In comparison, a typical PC could use between 70 and 150 watts. Even in sleep mode D class units draw just 2 watts while being fully remotely managed. Then, when you include additional power requirements in the data center, a cloud computing deployment can offer significant power savings.

Dell Wyse has implemented an ISO 14001-based environmental management system and WEEE recycling processes, and all Dell Wyse products meet stringent ROHS requirements.

Learn more.

Download fact sheets and white papers from here: **www.wyse.com/green**

* Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: Under 9 watts



Operating Systems Dell Wyse enhanced SUSE Linux

Dell Wyse enhanced SUSE Linux Enterprise is a simple, secure, and easy to manage platform designed for customers looking for flexibility and support of the latest protocols (ICA, PCoIP, RDP, etc) without the need for a Windows-based thin client.

Simple "Hands-Off" Management.

Deploying, managing, and updating Dell Wyse enhanced SUSE Linux is easy. Utilizing Dell Wyse's established automatic update and configuration approach, management tasks can be handled centrally and easily without any management software required.

Updating 1 or 1,000 thin clients is as simple as dragging and dropping a file into a folder. For customers that desire a little more hands-on approach (such as asset tracking, reporting, etc) then integration with Dell Wyse Device Manager is built-in.

Security.

Dell Wyse enhanced SUSE Linux is designed with security in mind. IT Managers are able to provide a locked-down experience, smartcard login to virtual environments, VPN connectivity, and leverage a read-only file system that helps protect against data loss, theft and virus attacks.



Enterprise-quality Linux optimized by Dell Wyse

Dell Wyse enhanced SUSE Linux is the only enterprise-quality Linux platform optimized for thin computing, created by combining the security and flexibility of SUSE Linux with Dell Wyse's cloud client computing leadership and innovation in user experience and simplified management. Additionally, SUSE Linux Enterprise is the only Linux platform to protect customers from potential IP infringement suits as it is jointly indemnified by SUSE Linux and Microsoft.

Flexible, Multi-Protocol Support.

Being built from a standard enterprise-quality Linux distribution means the Dell Wyse enhanced SUSE Linux supports a wide range of protocols and infrastructures straight-out-of-the-box including Citrix, Microsoft, VMware and Ericom PowerTerm InterConnect Terminal Emulation – allowing you to mix-and-match connections from a single image.

That's Dell Wyse enhanced SUSE Linux.

The only enterprise-quality Linux platform optimized by Dell Wyse for thin client computing.



Operating Systems Microsoft Windows Embedded Standard 2009

Running Windows Embedded Standard on Dell Wyse thin clients offers IT departments the ability to deploy fully functional desktop clients with better manageability and significantly lower total cost of ownership than personal computers.

Dell Wyse Windows Embedded Standard 2009-based thin clients can run 32 bit Microsoft Windows applications, either locally or from servers, with the inbuilt flexibility to add and support a host of desktop peripherals with permission from the IT administrator.

Full support is provided for RDP 7.0, Citrix ICA 12.x, VMware View 4.6, Ericom PowerTerm WebConnect, Ericom PowerTerm InterConnect Terminal Emulation and Internet Explorer 8. In addition, all Dell Wyse Windows Embedded Standard 2009 thin clients include support of Windows Embedded Device Manager, allowing the device to be managed by Microsoft's central management system for Windows-based devices, System Center Configuration Manager*.

Secure write-protected thin client desktops

This robust and flexible operating system is further enhanced by the Dell Wyse file-based Write Filter that enables you to protect the files, folder and/or entire volumes from accidental changes or user customization. On rebooting, the thin client simply returns to its original state thus preventing any possible damaging modification either from users or malware.

Dell Wyse customized image support

Dell Wyse technicians are prepared to help you customize Windows Embedded Standard 2009 to your exact requirements in order to create custom-built images for subsequent enterprise-wide deployment, management and update through Dell Wyse Device Manager.

Contact your Dell Wyse Partner for further details





Operating Systems Microsoft Windows Embedded Standard 7

New Windows Embedded Standard 7 delivers a wealth of enhanced deployment, user experience and management benefits to Dell Wyse desktops, mobiles and thin clients deployed across an organization's virtualized network.

Rich user experience

Wherever they are – deskbound or mobile – with Microsoft Windows Embedded Standard 7 your users can benefit from the rich user experience of the Aero interface and the power, familiarity and reliability of the Windows 7 operating system in a highly customizable and componentized form.

Full support is provided for Remote Desktop Protocol (RDP) 7.1 with RemoteFX technology to provide seamless connectivity to Windows Server 2008 R2 and virtual desktop infrastructure scenarios. The Dell Wyse-enhanced Windows Embedded Standard 7 platforms include additional features supporting the latest Citrix Online Plug-in and VMware View 4.6 to fit the needs of your most sophisticated users and making it an optimum OS for organizations wanting broad support for cloud computing and desktop virtualization. Citrix Online Plug-in provides the HDX user experience and View 4.6 provides localization and Virtual Printing.

The platform also features additional Windows technology innovations to drive rich, immersive user experiences, including Internet Explorer 8. There's full support and built-in flexibility too, to add and support a host of desktop peripherals with permission from the IT administrator. In addition, all Dell Wyse Windows Embedded Standard 7 thin clients include support of Windows Embedded Device Manager, allowing the device to be managed by Microsoft's central management system for Windows-based devices, System Center Configuration Manager.

Easy to manage and deploy

Now, with Windows Embedded Standard 7, deploying 32-bit capable thin clients is easier and more manageable than ever before and reflects the direct working relationship between Dell Wyse and Microsoft. The support for Domain Join and group policies through Active Directory, help with management and integration of thin clients into existing desktop management infrastructures.

Dell Wyse Configuration Manager (WCM) offers unprecedented simplicity to the management of virtual desktops by allowing IT departments to auto-configure thin clients running Dell Wyseenhanced Windows Embedded Standard. By automating the deployment of Windows Embedded Standard thin clients throughout a private cloud WCM offers multiple benefits to organizations: reducing the need to do imaging, deploying custom images and fast configuration updates. Client devices are updated with the latest configuration settings for VDI connections (RDP, Citrix, VMware View), device settings and OS configuration automatically when devices startup.

Dell Wyse Device Manager (WDM) addresses key management requirements. With its centralized management and administration, WDM helps IT departments deliver effective remote thin client support while minimizing end user downtime. In addition, the Dell Wyse USB Firmware Tool allows IT and Customer Service staff to quickly and easily image the devices directly.

Windows Embedded Standard 7 Microsoft

Enterprise-wide consistency

Windows Embedded Standard 7 and Dell Wyse provide the ideal, cost effective opportunity to deploy a consistent, high performance operating system across Dell Wyse cloud clients.

Continue tour



 $\Theta \Theta$

Features

Technical



Thin client management Dell Wyse Device Manager

Dell Wyse Device Manager (WDM) addresses key management requirements for deploying powerful thin clients. With its centralized management and administration WDM helps IT departments deliver effective remote thin client support while minimizing end user downtime.

Security is assured with HTTPS based imaging, updates and downloads.

WDM delivers organization-wide benefits:

Operations	Centralized management.
	Collect and organize asset information.
Administration	Health status reports.
	Automated client settings.
	Update client firmware and add applications.
End User IT Costs	Easy, effective remote support.
	Create custom scripts and packages.
Minimize downtime	Restart or reset thin clients in less than a minute
	Enforce policies. Minimize user errors.



At a glance features

- Security HTTPS based imaging / updates Fully encrypted network traffic Delegated admin access (MS AD) support
- No-Hassle deployment Complete device imaging / patching / updates Bandwidth throttling for efficiency / reliability Software updates and add-ons
- Device administration and monitoring Device health status / reporting Remote shadowing / control Default device configuration
- Reduce end user IT costs Reduce energy consumption with scheduled up/down times
- Scalability Distributed architecture Microsoft SQL database support Multiple remote repository support
- Complete asset visibility Automated device discovery Detailed hardware asset information Installed software asset information

Continue tour





User experience optimization Dell Wyse TCX Suite

with Dell Wyse Collaborative Processing Architecture

Dell Wyse TCX delivers an optimal user experience in one software suite.

The TCX suite enriches the user experience by removing the limitations previously associated with thin clients. It enhances, not replaces, key protocols like ICA/HDX and RDP by adding key features to help make each more valuable.

Multi-display

Ensures application windows and dialog boxes are multi-monitor aware when using more than one monitor.

USB Virtualization

Enables plug and play peripheral support for virtual desktop environments.

- Redirect and use local USB devices in virtual desktops.
- Deploy virtual desktops to knowledge workers with special device access needs.
- Enable a broad set of USB peripherals including webcams and headsets.

Multimedia acceleration

Streamlines the delivery of video and audio content to the local client for a rich user experience within a thin client computing architecture.

- Accelerates Mpeg1, Mpeg2, WMV, Mpeg4 Part 2, AC3, AAC, MP3, WAV, WMA media types.
- Collaborative Processing Architecture enhances server scalability, and network utilization by off-loading multimedia rendering to the client.



Flash redirection

Flash redirection helps thin client users to experience excellent Flash video performance. Flash redirection allows web-based Flash video content to be fetched directly by the Dell Wyse thin client from the source where it is played locally. Users get outstanding Flash video performance while the VDI host system runs more efficiently.

Bi-directional sound

Enables bi-directional audio in virtual desktop environments, enabling solutions such as VOIP, digital dictation or voice recognition to be deployed.



Virtualization software Dell Wyse Virtual Desktop Accelerator

Removing the barriers of network latency.

Dell Wyse Virtual Desktop Accelerator (VDA) enables virtualized desktop and thin computing environments to be deployed to areas where network latency has, to date, presented operational barriers. Now, with VDA, more users can receive the full benefits of Dell cloud client computing – with outstanding PC experience over virtualized desktops.

VDA is a software-only solution for Dell Wyse thin clients and supported PCs that delivers exceptional user experience for the allocated network bandwidth by neutralizing the effects of network latency and packet loss. Making 'thin' suitable for more remote-site, branch, or field-based users.

VDA works with instead of replacing existing RDP and ICA protocols, and is designed to offer significant acceleration over certain capacity-constrained WAN links.



At a glance features

- Software-only acceleration of virtual desktops and applications
- Accelerates existing Citrix ICA and Microsoft
 RDP protocols
- Works on WANs and 'fat, long pipes'
- Accelerates connections to Citrix XenApp, Citrix XenDesktop, VMware View and Microsoft Terminal Server and Microsoft Hyper-V VDI
- Enhances Dell Wyse TCX software suite functionality across wide-area networks
- Enables Dell Wyse Collaborative Processing Architecture across wide-area networks
- Administrator console provides control of maximum bandwidth per connection
- Leverages built-in security of underlying protocols (128-bit encryption for RDP and ICA).



Technical Dell Wyse D class cloud client specifications.

The range features the D90D7 and D90Q7 for Windows Embedded Standard 7, the D90DW for Windows Embedded Standard 2009, the D50D for Dell Wyse enhanced SUSE Linux and the D00D cloud PC for Dell Wyse WSM.

Want to learn more? Simply click the icons.

Cloud clients



Learn about Dell Wyse WSM at www.wyse.com/products/software/cloud/WSM



Specifications Dell Wyse D50D, D90DW, D90D7, and D90Q7 thin clients and D00D cloud PC.

Operating system	Dell Wyse Windows [®] Embedded Standard 7, Windows [®] Embedded Standard 2009 or Dell Wyse enhanced SUSE Linux Enterprise
Processors	AMD G-Series dual core T48E 1.4GHz with AMD Radeon™ HD 6250 graphics Quad core AMD G-Series SOC 1.5GHz with integrated Radeon HD 8000 graphics
Memory	D50D 2GB Flash / 2GB DDR3 RAM; SSD storage also supported D90DW 2GB Flash / 2GB DDR3 RAM; SSD storage also supported D90D7 & D90Q7 4GB Flash / 2GB DDR3 RAM; SSD storage also supported D00D 0GB Flash / 2GB DDR3 RAM; SSD storage also supported Expandable up to 16GB Flash / 4GB DDR3 RAM / SSD storage also supported
I/O peripheral support	One DisplayPort. (Optional DisplayPort to DVI-I adapter available) One DVI-I port. DVI to VGA (DB-15) adapter included Four external USB 2.0 ports (2 front; 2 back) D90Q7: Four USB 2.0 ports and two USB 3.0 ports Serial and parallel connectivity supported through USB 2.0 adapters Enhanced USB keyboard with Windows Keys (104 keys) and PS/2 mouse port. PS/2 optical mouse included.
Networking	10/100/1000 Base-T Gigabit ethernet RJ45 or SFP module Factory options: Single and dual Band 802.11 a/b/g/n integrated wireless with external dual antenna SFP module support for Fiber NIC network connectivity Bluetooth connectivity
Display	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate DisplayPort: 2560x1600@32bpp DVI-1: 1920x1200@32bpp Dual display: 1920x1200@32bpp
Audio	Composite audio jack: 1/8-inch mini, 16-bit stereo. Internal mono speaker.

Physical characteristics	Height: 6.7 inches (170mm) Width: 1.6 inches (40mm) Depth: 7.3 inches (185mm)
Weight	2.05 lbs. / 0.93 kg
Mountings	Vertical feet standard. Optional VESA mounting bracket for mounting to flat surfaces, such as walls. Please note: D class clients cannot mount directly to the backs of monitors. Optional Ergotron mounting stand for mounting with Dell monitors.
Device Security	Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100–240 VAC, 50/60 Hz 65W, 19V DC. Energy Star V.5.0 Phase V external and EuP compliant power adapter Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: Under 9 watts
Temperature Range	Operating: 32° to 104° F (10° to 40° C), horizontal and vertical positions. Storage: 14° to 140° F (-10° to 60° C)
Humidity	20% to 80% condensing 10% to 95% non-condensing
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS compliant
Warranty	Three-year limited Dell Wyse hardware warranty



Start

Models

Features

Technical

Contact

Print

Software specifications Dell Wyse enhanced SUSE Linux

Firmware features	Dell Wyse enhanced SUSE Linux based on SLED 11 SP2 Automatic Central Configuration (text-based INI's) Automatic Upgrades (FTP, HTTP, HTTPS)	Wireless support	WPA Personal, WPA2 Personal, WPA Enterprise WPA Enterprise Authentication support PEAP/TLS: PAP/MSCHAP/MSCHAPV2 support
	Secure, read-only file system with lockdown abilities Dell Wyse RDP client (RDP7 Compatible) Citrix Online Plugin 11.2 client (ICA 12.1) w/ HDX Mediastream, Plug-n-Play, Realtime, etc. VMware View Client 1.6 support Ericom PowerTerm InterConnect Terminal Emulation Ericom PowerTerm WebConnect Cisco, Juniper, Nortel, IPSEC VPN Support (Add-ons) Local/Remote Printing support (CUPS, LPR/LPD, Samba, ThinPrint,etc) Web-based applications (Firefox, Flash, JAVA,etc) XDMCP / SSH	Dell Wyse TCX Suite	 Advanced support for innovative Dell Wyse TCX Suite virtualization software that both works with and enhances ICA and RDP (instead of replacing them) featuring: Multimedia acceleration - the power to run rich multimedia files formats utilizing Dell Wyse Collaborative Processing Architecture (CPA) that intelligently redirects the necessary processing tasks between the thin client and the server. Multi-display - ensures that windows and dialogue boxes behave the way users expect when using more than one monitor. USB Virtualization - makes thin client-attached USB devices visible to virtual desktops and applications, with full IT control. Bi-directional sound - enables virtual desktops and applications to
Server OS Infrastructure support	Citrix XenApp / Citrix Presentation Server Citrix XenDesktop VMware View Microsoft Windows Terminal Server 2003 & 2008		 receive and transmit high quality audio without compromise. Flash acceleration - helps users of thin clients to experience improved Flash performance.
Keyboard language support	100+ Keyboard Layouts supported locally (English, German, Spanish, French, Italian, Dutch, Chinese, Japanese, Turkish)	Dell Wyse Virtual Desktop Accelerator	Dell Wyse VDA works with instead of replacing existing RDP and ICA protocols, and is designed to offer significant acceleration over certain capacity-constrained WAN links.
Management	Automatic, "hands-off" configuration and upgrading of thin clients without the need for device management software. Optionally, administrators can choose to integrate with Dell Wyse Device Manager (WDM) for more hands-on control: - Complete image upgrade - Wake terminal remotely (Wake-on LAN) - Remote screen shadowing of entire desktop (VNC) - Asset management and reporting		



```
Contact
```

Print

Software specifications Microsoft Windows Embedded Standard 2009

Firmware features	Microsoft Windows Embedded Standard 2009 Microsoft Internet Explorer 8.0 resident: HTML, JavaScript, XML, Active X Sun JRE, Media Player, Citrix Web Interface RDP 7.0 resident Citrix Online Plugin 12.x resident VMware View 4.6 client resident Ericom PowerTerm InterConnect Terminal Emulation Ericom PowerTerm WebConnect client Windows Media Player 11, .NET 3.5
Server OS Infrastructure Support	Citrix XenApp / Citrix Presentation Server / Citrix XenDesktop VMware View Ericom PowerTerm WebConnect Microsoft Windows Terminal Server 2003 & 2008
Application Framework	.Net 3.5
Security	File Based Write Filter (FBWF) Microsoft Baseline Security Analyzer (MBSA)
Set-up and Configuration	Boot from local flash Microsoft Windows Embedded Standard 7 user interface languages: U.S, Optional add-ons
Keyboard language support	U.S. English (standard), French, German, Spanish, U.K. English, 40 other languages included
Protocol Support	TCP/IP, DNS, DHCP, PXE
Management	Remote management, configuration, and upgrades through Dell Wyse Device Manager Complete image upgrade Wake terminal remotely (Wake-on LAN) Terminal configuration (IP information, name, etc.) Remote screen shadowing of entire desktop (Dell Wyse Remote Shadow) Reporting, Asset management / SMS / Altiris Native Windows Embedded Device Manager support for management via System Center Configuration Manager

Models

Features

Start





Software specifications Microsoft Windows Embedded Standard 7

Firmware features	Microsoft Windows Embedded Standard 7 Microsoft Internet Explorer 8.0 resident: HTML, JavaScript, XML, Citrix Web Interface Microsoft RDP 6.1 client (Protocol 7.1 Supported) with RemoteFX technology Citrix Online Plugin 12 resident (ICA 12) with HDX Citrix XenDesktop VMware View 4.6 client resident Ericom PowerTerm InterConnect Terminal Emulation Windows Media Player 12
Server OS Infrastructure support	Citrix XenApp / Citrix Presentation Server Citrix XenDesktop VMware View Microsoft Windows Terminal Server 2003 & 2008 R2 MSFT VDI
Security	File Based Write Filter (FBWF)
Set-up and configuration	Boot from local flash Microsoft Windows Embedded Standard 7 user interface languages: U.S, Optional add-ons
Keyboard language support	U.S. English (standard), French, German, Spanish, U.K. English, 40 other languages included
Protocol support	TCP/IP, DNS, DHCP, PXE
Management	Auto-configuration with Dell Wyse Configuration Manager Remote management, configuration, and upgrades through Dell Wyse Device Manager Complete image upgrade Terminal configuration (IP information, name, etc.) Reporting, Asset management Simple USB imaging solution with Dell Wyse USB Firmware Tool Native Windows Embedded Device Manager support for management via System Center Configuration Manager

Wireless support	802.11 a/b/g/n support with dual band external wireless adapter or single band internal wireless adapter option WPA-2, WEP, WPA wireless authentication PEAP-GTC wireless authentication protocol with optional Juniper Odyssey Client Supports PC-Card wireless adapters* from: Cisco, D-Link, Netgear, US Robotics, Trendware
Plug-ins	Adobe Flash Player Microsoft Silverlight
Dell Wyse TCX Suite	 Advanced support for innovative Dell Wyse TCX Suite virtualization software that both works with and enhances ICA and RDP (instead of replacing them) featuring: Multimedia acceleration - the power to run rich multimedia files formats utilizing Dell Wyse Collaborative Processing Architecture (CPA) that intelligently redirects the necessary processing tasks between the thin client and the server. Multi-display - ensures that windows and dialogue boxes behave the way users expect when using more than one monitor. USB Virtualization - makes thin client-attached USB devices visible to virtual desktops and applications, with full IT control. Bi-directional sound - enables virtual desktops and applications to receive and transmit high quality audio without compromise. Flash acceleration - helps users of thin clients to experience improved Flash performance.
Dell Wyse Virtual Desktop Accelerator	Dell Wyse VDA works with instead of replacing existing RDP and ICA protocols, and is designed to offer significant acceleration over certain capacity-constrained WAN links.
	*requires hardware support



Start

Models

Features

Technical

Print

Contact

Contact Dell Wyse.

Dell Wyse

3471 North First Street, San Jose, CA 95134-1801

Visit our website at:

http://www.dellwyse.com or send email to: sales@wyse.com

Dell Wyse Sales 1-800-438-9973

International customers please dial:

00 1 408 473 1200

Dell Wyse Support Portal

Dell Wyse Support Portal provides a fast and accurate way to communicate interactively with Dell Wyse Customer Support, and helps us respond to your requests more quickly.

http://support.wyse.com/selfservice.html



Dell Wyse offers cloud client computing sales, service and support expertise around the globe. Click for contact details.

About Dell

Dell Inc. (NASDAQ: DELL) listens to customers and delivers innovative technology and services that give them the power to do more. For more information, visit www.dell.com ©2013 The Dell Wyse logo and references are trademarks of Dell Wyse. Other product names mentioned herein are for identification purposes only and may be trademarks and/or registered trademarks of their respective companies. All specifications are subject to change without notice. Whilst we make every effort to ensure the accuracy of the details, specifications, models, images and benefits featured in this datasheet, we cannot be held responsible for any errors and/or omissions. If you have any queries regarding Dell Wyse products please contact your authorized regional Dell Wyse Partner. Some features require support by server operating system and protocol. Approved final 290513.





Dell Wyse D class cloud clients.

The new Dell Wyse D class: strong, compact, affordable.

The range features dual and quad core processors in a line of advanced yet affordable thin clients and cloud PCs: D90D7 & D90Q7 for Windows Embedded Standard 7, the D90DW for Windows Embedded Standard 2009, the D50D for Dell Wyse enhanced SUSE Linux and the D00D for Dell Wyse WSM.*

Designed to allow your users to flourish within ever changing and demanding desktop environments, the new D class offers you new dimensions in computing performance, high definition multimedia and operational flexibility in a compact affordable form.

The D class' compact frame hosts an array of display, peripheral and network connectivity plus further flexible networking, storage and I/O options; everything in fact to offer you the ideal cloud client for Citrix, Microsoft and VMware VDI environments.

Dell Wyse Device Manager supports the D class with scalable enterprisewide management. From fast 'day one' out-of-the-box deployment, to patching and updates and on to granular desktop device management – all with secure end-to-end encrypted communications. When it comes to energy efficiency the D class is designed to out-perform other more power hungry desktop alternatives, including other thin clients in its class. Its silent, disk and fan-less design contributes considerably to lowering an organization's carbon footprint through power usage and emissions.

High performance processor.

Need to deploy a dependable platform to display, manipulate and work with high definition multimedia, voice and video in a virtualized environment? The D class' hardware acceleration engine and dual monitor support offers your users outstanding performance and display capabilities across 2D, 3D and HD video applications.



At a glance

Performance

Driving the D class' high speed and performance are two powerful, energy saving processors that offer you a strong all around platform on which to support an increasingly diverse range of user, application and operating requirements: the AMD G-Series dual core T48E 1.4 GHz processor and the Quad core AMD G-Series SOC 1.5GHz.

Connectivity

DVI-I interface with optional splitter cable enabling use of 2 monitors. Four USB 2.0 ports, Gigabit ethernet connectivity and optional WiFi 802.11 a/b/g/n and Fiber NIC support.

Management

Features Dell Wyse management software found on premium thin and zero clients. For customers that desire a little more hands-on approach (such as asset tracking, reporting, etc) then integration with Dell Wyse Device Manager is built-in.

Multimedia performance

The D class offers your users outstanding performance and display capabilities across 2D, 3D and HD video applications.

Energy efficient

D class cloud clients use 9 watts of power in typical use**. In comparison, a typical PC could use between 70 and 150 watts. Even in sleep mode D class units draw just 2 watts while being fully remotely managed.

- * Check with wyse.com for availability of models.
- ** Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: under 9 watts

Specification Dell Wyse D class cloud clients

Operating System	Dell Wyse Windows® Embedded Standard 7, Windows® Embedded Standard 2009 or Dell Wyse enhanced SUSE Linux Enterprise
Processors	AMD G-Series dual core T48E 1.4GHz with AMD Radeon [™] HD 6250 graphics Quad core AMD G-Series SOC 1.5GHz with integrated Radeon HD 8000 graphics
Memory	D50D 2GB Flash / 2GB DDR3 RAM; SSD storage also supported D90DW 2GB Flash / 2GB DDR3 RAM; SSD storage also supported D90D7 & D90Q7 4GB Flash / 2GB DDR3 RAM; SSD storage also supported D00D 0GB Flash / 2GB DDR3 RAM; SSD storage also supported Expandable up to 16GB Flash / 4GB DDR3 RAM / SSD storage also supported
I/O peripheral support	One DisplayPort. (Optional DisplayPort to DVI-I adapter available) One DVI-I port. DVI to VGA (DB-15) adapter included Four External USB 2.0 ports (2 front; 2 back) D90Q7: Four USB 2.0 ports and two USB 3.0 ports Serial and parallel connectivity supported through USB 2.0 adapters Enhanced USB keyboard with Windows Keys (104 keys) and PS/2 mouse port. PS/2 optical mouse included.
Networking	10/100/1000 Base-T Gigabit ethernet RJ45 or SFP module Factory options: Single and dual band 802.11 a/b/g/n integrated wireless with external dual antenna SFP module support for Fiber NIC network connectivity Bluetooth connectivity
Display	VESA monitor support with Display Data Control (DDC) for automatic setting of resolution and refresh rate DisplayPort: 2560x1600@32bpp DVI-I: 1920x1200@32bpp Dual display: 1920x1200@32bpp
Audio	Composite audio jack: 1/8-inch mini, 16-bit stereo. Internal mono speaker.
Physical characteristics	Height: 6.7 inches (170mm) Width: 1.6 inches (40mm) Depth: 7.3 inches (185mm)
Weight	2.05 lbs. / 0.93 kg
Mountings	Vertical feet standard. Optional VESA mounting bracket for mounting to flat surfaces, such as walls. Please note: D class clients cannot mount directly to the backs of monitors. Optional Ergotron mounting stand for mounting with Dell monitors.
Device Security	Built-in Kensington security slot (cable sold separately)
Power	Worldwide auto-sensing 100–240 VAC, 50/60 Hz 65W, 19V DC. Energy Star V.5.0 Phase V external and EuP compliant power adapter Average power usage with device connected to 1 keyboard with 1 PS/2 mouse and 1 monitor: under 9 watts
Temperature Range	Operating: 32° to 104° F (10° to 40° C), horizontal and vertical positions. Storage: 14° to 140° F (-10° to 60° C)
Humidity	20% to 80% condensing / 10% to 95% non-condensing
Safety Certifications	German EKI-ITB 2000, ISO 9241-3/-8 cULus 60950, TÜV-GS, EN 60950 FCC Class B, CE, VCCI, C-Tick WEEE, RoHS compliant
Warranty	Three-year limited Wyse hardware warranty



Learn more: Contact Dell Wyse at sales@wyse.com or call 1-800-438-9973

dellwyse.com

Dell Wyse 3471 North First Street San Jose, CA 95134-1801 Visit our website at: http://www.dellwyse.com Or send email to: sales@wyse.com **Dell Wyse Sales** 1-800-438-9973

