Dell EMC PowerEdge MX750c

D&LLTechnologies

Spec Sheet

High-performance modular compute sled with exceptional scale

The Dell EMC PowerEdge MX750c is the latest addition to the PowerEdge MX kinetic infrastructure ecosystem, is a fully featured, high-performance, modular compute sled for exceptional scalability.



Innovate at scale enabling sophisticated and emerging workloads for a transformational experience

A fully configurable single-width compute sled powered by up to two-40 core 3rd Generation Intel® Xeon® Scalable processors. Each PowerEdge MX750c supports 32 DDR4 DIMM slots and up to six 2.5-inch SAS/SATA (HDD/SDD) or Express Flash NVMe PCIe SSDs drives. A maximum of eight MX750c servers can be installed in the PowerEdge MX7000 chassis.

- · Flexible memory configurations from capacities of up to 4 TB
- Supports up to 16 slots for Second Generation Intel[®] Optane[™] DC persistent memory DCPMM
- Choice of optional M.2 Boot Optimized Storage Solution (BOSS) or Internal Dual microSD Module (IDSDM), to streamline operating system and data storage
- · Option of Express Flash NVMe PCIe SSD for high performing direct attached storage requirements

This makes the PowerEdge MX750 an ideal server for organizations:

- looking for leading-edge performance for virtualization, containers, software-defined storage and software-defined networking and database analytics
- seeking to commit to Dell EMC's vision that leads toward Composable Disaggregated Infrastructure (CDI)
- invested in PowerEdge MX who desire leading-edge compute, memory and I/O capabilities that include an end-to-end uniquely managed experience

Increase efficiency and accelerate operations with autonomous collaboration

The Dell EMC OpenManage systems management portfolio tames the complexity of managing and securing IT infrastructure. OpenManage Enterprise – Modular is specifically designed to enable customers that enjoy the benefits of a multi-chassis management approach found uniquely in the MX solution. Using Dell Technologies' intuitive end-to-end tools, IT can deliver a secure, integrated experience by reducing process and information silos in order to focus on growing the business. The Dell EMC OpenManage portfolio is the key to your innovation engine, unlocking the tools and automation that help you scale, manage, and protect your technology environment.

- Built-in telemetry streaming, thermal management, and RESTful API with Redfish offer streamlined visibility and control for better server management
- Intelligent automation lets you enable cooperation between human actions and system capabilities for added productivity
- Integrated change management capabilities for update planning and seamless, zero-touch configuration and implementation
- Full-stack management integration with Microsoft, VMware, ServiceNow, Ansible and many other tools

Protect your data assets and infrastructure with proactive resilience

The Dell EMC PowerEdge MX750c server is designed with a cyber-resilient architecture, integrating security deeply into every phase in the lifecycle, from design to retirement.

- Operate your workloads on a secure platform anchored by cryptographically trusted booting and silicon root of trust
- · Maintain server firmware safety with digitally signed firmware packages
- Prevent unauthorized configuration or firmware change with system lockdown
- Securely and quickly wipe all data from storage media, including hard drives, SSDs and system memory with System Erase

PowerEdge MX750c

The Dell EMC PowerEdge MX750c offers compelling compute-density, improved performance and value for:

- General purpose IT, virtualization, containerization,
- Software-defined storage and networking
- · Database analytics

Feature	Technical Specifications	
Processor	Up to two 3rd Generation Intel Xeon Scalable processors, with up to 40 cores per processor	
	Intel C620 series chipset with optional Intel QuickAssist Technology	
Memory	32 DDR4 DIMM slots, supports RDIMM max 2 TB or LRDIMM max 4 TB, speeds up to 3200 MT/s	
Persistent Memory	Supports up to 16 Intel Persistent Memory 200 series (BPS) slots with a maximum total capacity of 7.68 TB per sled	
Availability	Supports registered ECC DDR4 DIMMs only	
Controllers	 Internal controllers: PERC H755 MX, PERC H745P MX, HBA350i MX, S150 Boot Optimized Storage Subsystem (BOSS-S1): HWRAID 2 x M.2 SSDs 240 GB or 480 GB or Internal Dual SD Module (IDSDM) or USB External PERC (RAID): PERC H745P MX External HBAs (non-RAID): HBA330 MMZ 	
Drive Bays	 Front bays: Up to 4 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) 7.68 TB per drive Up to 6 x 2.5-inch SAS/SATA/NVMe (HDD/SSD) 7.68 TB per drive 	
Power Supplies	MX7000 chassis: Up to six 3000 W AC Platinum PSU and grid redundancy support	
Fans	MX7000 chassis: 5 rear and 4 front-accessible hot-swap fans with full redundancy	
Dimensions	Height: 42.15 mm (1.65 inches) Width: 250.2 mm (9.85 inches) Depth: 594.99 mm (23.42 inches)	
Form Factor Embedded Management	Up to 8 independent hot-swappable, 1U single-width compute sled in a MX7000 chassis MX7000 chassis: OpenManage Enterprise Modular Edition (OME-Modular);	
5	 Up to 2 redundant MX9002m management modules Unified control: single management point for server, storage, and networking Intelligent automation: Operational template methodology and comprehensive RESTful API Quick Sync 2 Bluetooth Low Energy (BLE)/wireless module On compute sled: iDRAC9 iDRAC Direct iDRAC Service Module 	
OpenManage Software	OpenManage Enterprise OpenManage Power Manager plugin OpenManage SupportAssist plugin OpenManage Update Manager plugin OpenManage Enterprise Modular Edition	
Integrations and Connections	OpenManage Integrations BMC Truesight Microsoft System Center Red Hat Ansible Modules VMware vCenter and vRealize Operations Manager 	OpenManage Connections IBM Tivoli Netcool/OMNIbus IBM Tivoli Network Manager IP Edition Micro Focus Operations Manager i Nagios Core Nagios XI
Integrated Security	 TPM 1.2/2.0 FIPS, CC-TCG certified, TPM 2.0 China NationZ Digitally Signed Firmware Chassis Intrusion Alert Secure Boot Secure Erase Silicon Root of Trust System Lockdown (requires iDRAC Enterprise or Datacenter) 	
Networking_Options (NDC)	MX7000 chassis Fabric options: up to 2 pairs redundant general purpose switch or passthrough modular bays (Fabrics A and B); redundant pair of storage specific switch bays (Fabric C) Up to 25 Gb CNA/NIC per port for Mezz A/B, 32 Gb Fibre Channel, 12 Gbps SAS for Mezz C	
Ports	Front ports 1 x iDRAC Direct port (Micro-AB USB) 1 x USB 3.0 	Internal port • 1 x USB 3.0
PCle	 One x16 PCIe Gen4 slot for Mezz A – connected to processor 1 One x16 PCIe Gen4 slot for Mezz B – connected to processor 2 One x16 PCIe Gen4 slot for Mini Mezz card – connected to processor 2 One x16 PCIe Gen4 slot for PERC – connected to processor 1 Two x8 PCIe Gen4 connectors for NVMe drive – connected to processor 1 One x8 PCIe Gen4 connectors for NVMe drive – connected to processor 2 Two x4 PCIe Gen3 slot for BOSS M.2 HW RAID card – connected to Platform Controller Hub (PCH) 	
Operating Systems and Hypervisors	Canonical Ubuntu Server LTS Citrix Hypervisor Microsoft Windows Server with Hyper-V Red Hat Enterprise Linux SUSE Linux Enterprise Server VMware ESXi/vSAN For specifications and interoperability details, see dell.com/OSsupport.	

Recommended support and services

Choose Dell ProSupport Plus or Dell ProSupport for premium hardware and software support. Consulting and deployment offerings are also available. Contact your Dell representative today for more information. Availability and terms of Dell Services vary by region. For more information, visit www.delltechnologies.com/Services.

Dell Technologies on Demand

Consume technology, infrastructure and services any way you want with Dell Technologies on Demand, the industry's broadest end-to-end portfolio of flexible consumption and as-a-Service solutions. For more information, visit www. delltechnologies.com/ondemand.

Discover more about PowerEdge servers



Learn more about our

PowerEdge servers



Learn more about our systems management solutions



Search our Resource Library



Follow PowerEdge servers on Twitter



Contact a Dell Technologies Expert for Sales or Support

© 2021 Dell Inc. or its subsidiaries. All Rights Reserved. Dell, EMC and other trademarks are trademarks of Dell Inc. or its subsidiaries. Other trademarks may be trademarks of their respective owners. February 2021

D&LLTechnologies