

T640 SPEC SHEET



POWEREDGE T640

Maximum performance and scalability

The PowerEdge T640 delivers ultimate two-socket performance and massive internal storage capacity in a rack or tower platform. The scalable T640 drives a wide range of workloads for mid-sized offices, remote sites and data centers.

Adapt and scale to your dynamic business needs

The PowerEdge T640 balances cost-effective, in-server expansion with powerful performance to provide a scalable business architecture. The versatile T640 allows you to address data-heavy, diverse workloads including virtualization, databases, analytics, imaging applications and SDS. Meet dynamic performance and capacity demands with flexible storage and I/O options.

- Deliver fast insights with up to 8 NVMe drives, up to 2x more than the previous generation.¹
- · Meet changing business requirements with a dual port 10GbE network.
- Future-proof data growth with up to 18 x 3.5" or 32 x 2.5" drives and 8 PCIe slots.
- Provide advanced imaging and VDI with up to 4 x 300W GPU accelerators.

Intuitive systems management with intelligent automation

Dell EMC PowerEdge servers increase efficiency by leveraging the power and simplicity of the embedded iDRAC for smart automation of routine tasks. With agent-free management, the T640 is managed with ease and frees up time for your business priorities.

- Simplify and automate management of your Dell EMC infrastructure with OpenManage Enterprise.
- Take advantage of the OpenManage Mobile app and Quick Sync 2 capabilities to easily and effectively manage PowerEdge servers at the server, or wherever you are.
- Streamline management in virtualized environments with OpenManage Integrations for VMware vCenter or Microsoft System Center.

Safeguard data with integrated security

Every PowerEdge server is made with a cyber-resilient architecture, delivering security into all parts of a server's life cycle. The T640 uses these new security features so you can reliably and securely deliver the right data to where your customers are, no matter where they are. Dell EMC considers each part of system security, from design to end of life, to ensure trust and deliver worry-free systems.

- Rely on a secure supply chain that protects servers from the factory to thedata center.
- · Maintain data safety with cryptographically signed firmware packages and Secure Boot.
- Protect your server from malicious malware with iDRAC9 Server Lockdown mode (requires Enterprise or Datacenter license).
- Wipe all data from storage media including hard drives, SSDs and systemmemory quickly and securely with System Erase.

¹ Dell internal analysis in July 2017 comparing the previous generation T630 specifications vs T640 specifications.

PowerEdge T640

- Accelerate and consolidate data-intensive workloads in a 5U rack-capable tower platform.
- Scale effortlessly with maximum internal capacity and optimizedperformance.
- Mix and matchNVMe, HDD and SSD drives tocreate your idealconfiguration.

PowerEdge T640		
Features	Technical Specification	
Processor	Up to two 2 nd Generation Intel® Xeon® Scalable processors, up to 28 cores per processor	
Memory	24 DDR4 DIMM slots, Supports RDIMMS/ LRDIMMS, speeds up to 2993MT/s, 3TB max Up to 12 NVDIMM, 192GB max Supports registered ECC DDR4 DIMMs only	
Storage controllers	Internal controllers: PERC H330, H730P, H740P, HBA330, Software RAID (SWRAID) S140 Boot Optimized Storage Subsystem: HWRAID 2 x M.2 SSDs 120GB, 240 GB External PERC (RAID): H840 External HBAs (non-RAID): 12 Gbps SAS HBA	
Drive bays	Up to 8 or 18 x 3.5" SAS/SATA (HDD/SSD) max 288TB or up to 16 x 2.5" SAS/SATA (HDD/SSD) max 61TB or up to 32 x 2.5" SAS/SATA (HDD/SSD) max 122TB or up to 16 x 2.5" with up to 8 NVMe, SAS/SATA /NVMe (HDD/SSD) max 112TB	
Power supplies	Titanium 750W, Platinum 495W, 750W, 1100W, 1600W, 2000W and 2400W	48VDC 1100W, 240HVDC 750W Hot plug power supplies with full redundancy Up to 8 fans with N+1 redundancy (6 hot-pluggable internal fans plus 2 external fans) ¹
Sizing	Form factor: Tower or rack, 5U	Chassis max depth: 708.7 mm
Bezel	Optional security bezel	
Embedded / At-Server	iDRAC9 iDRAC Direct	Quick Sync 2 BLE/wireless module
Consoles & Mobile	OpenManage Enterprise	OpenManage Mobile OpenManage Power Manager
Integrations	Microsoft® System Center, VMware® vCenter™, BMC Software	
Connections	Nagios & Nagios XI, HP Operations Manager (OMi)	
Tools	Dell EMC Repository Manager Dell EMC Update Package Dell EMC System Update Dell EMC Server Update Utility	iDRAC Service Module iDRAC REST API with Redfish OpenManage Server Administrator OpenManage Storage Services
Security	TPM 1.2/2.0 optional Cryptographically signed firmware Silicon Root of Trust	Secure Boot System Lockdown (requires iDRAC Enterprise or Datacenter) System Erase
I/O & Ports	2 x 10GbE LOM (1GbE/10GbE) 8 x USB (1 x USB 2.0, 1 x USB 3.0, 6 x USB 2.0/3.0) dedicated IDRAC Direct Micro-USB Video card: VGA Up to 8 PCIe Gen3 slots	
GPU options ²	GPU options: 4 x DW or 8 x SW Nvidia Tesla P100, K80M, M60, M10, P40, AMD S7150, S7150X22	See Dell.com/GPU for latest information.
Supported operating systems	Canonical® Ubuntu® LTS Citrix® Hypervisor Microsoft Windows Server® LTSC with Hyper-V Red Hat® Enterprise Linux	SUSE [®] Linux Enterprise Server VMware [®] ESXI [®] For specifications and interoperability details, see <u>Dell.com/OSsupport</u>
OEM-ready version available	From bezel to BIOS to packaging, your servers can look and feel as if they were designed and built by you. For more information, visit <u>Dell.com/OEM</u> .	
Recommended support and services	Choose Dell EMC ProSupport Plus for critical systems or Dell EMC ProSupport for premium hardware and software support for your PowerEdge solution. Consulting and deployment offerings are also available. Contact your Dell EMC representative today for more information. Availability and terms of Dell EMC Services vary by region. For more information, visit <u>dell.com/itilfecycleservices</u> .	
Dell EMC Financial Services	Deliver results with easy financing. Explore financial options that move at the speed of business. For more information, visit https://www.emc.com/products/how-to-buy/global-financial-services/index.htm	

¹ Please note the N+1 redundancy is available in certain configurations and operating systems.
² GPU capability available in a rack form factor. Must be ordered at the time of initial purchase. Two 300W GPU are supported within NVMe drive configurations.

Learn more at Dell.com/PowerEdge

End-to-end technology solutions

Reduce IT complexity, lower costs and eliminate inefficiencies by making IT and business solutions work harder for you. You can count on Dell EMC for end-to-end solutions to maximize your performance and uptime. A proven leader in Servers, Storage and Networking, Dell EMC Services deliver innovation at any scale. And if you're looking to preserve cash or increase operational efficiency, Dell EMC Financial Services M has a wide range of options to make technology acquisition easy and affordable. Contact your Dell EMC Sales Representative for more information.*

*Payment solutions provided and serviced by Dell Financial Services L.L.C. or its affiliate or designee ("DFS") for qualified customers. Offers may not be available or may vary in certain countries. Where available, offers may be changed without notice and are subject to product availability, credit approval, execution of documentation provided by and acceptable to DFS, and may be subject to minimum transaction size. Offers not available for personal, family or household use. Dell EMC and the Dell EMC logo are trademarks of Dell Inc. Restrictions and additional requirements may apply to transactions with governmental or public entities.

