



- Economical yet innovative fanless design runs cool and quiet
- Gigabit ports allow you to connect all your devices for fast file transfers and smooth media streaming
- Reduced energy consumption without sacrificing performance EEE compliance

5/8 Port Gigabit Unmanaged Metal Desktop Switch

Product Highlights

- Five or Eight 10/100/1000Mbps Ports
- Up to 1 Gbps of Dedicated Bandwidth per Port and up to 2Gbps Bandwidth in Full-Duplex mode
- Compatible with All Popular Operating Systems
- Plug & Play Installation
- Conserves energy with D-Link Green Technology
- Supports MAC address learning
- Limited 3 Year Warranty¹

Think Green

The GO-SW-5GE/8GE 5-Port and 8-Port Gigabit Unmanaged Metal Desktop Switch is part of D-Link's new series of SOHO devices that make use of D-Link's Green Technology, providing energy savings, reduced heat, and a longer product life without sacrificing performance or functionality. An energy-efficient power adapter (EnergyStar Level V qualified), minimized use of harmful substances (RoHS compliant), and recyclable packaging make this switch truly environmentally friendly.

Conserves Energy

The GO-SW-5GE/GO-SW-8GE five and eight port Gigabit Unmanaged Metal Desktop Switch helps you conserve energy automatically. The switch saves substantial amounts of power by cutting power usage for unused ports or ports connected to computers that have been shut down.



5/8 Port Gigabit Unmanaged Metal Desktop Switch

Features

- Built-in D-Link Green Technology
- Inexpensive Gigabit solution for Home/SOHO
- 5/8 10/100/1000 Mbps Gigabit ports
- 10/16 Gbps switching fabric
- Auto MDI/MDIX crossover for all ports
- Secure store-and-forward switching scheme
- Full/half-duplex for Ethernet/Fast Ethernet speeds
- IEEE 802.3x Flow Control
- Supports 9,216 Byte Jumbo Frames
- RoHS compliant
- Plug-and-play installation

Environmentally Friendly

The GO-SW-5GE/GO-SW-8GE five and eight port Gigabit Unmanaged Metal Desktop Switch was designed with the environment in mind, and is compliant with Energy Star Level V, as well as with the stringent CEC and MEPS regulations that require the use of energy efficient power adapters. The switch is also built to follow RoHS standards to minimize use of hazardous materials, and uses recyclable packaging that helps reduce waste, complying with the WEEE directive.

Gigabit Connection for Home and SOHO

The GO-SW-5GE/GO-SW-8GE offers an economical way for SOHO and small to medium businesses (SMB) to benefit from the increased bandwidth of Gigabit Ethernet. It provides five/eight Gigabit ports for easy expansion of your network and a quick way to upgrade your network to Gigabit connectivity.

Package Contents

- 5/8 port Gigabit Unmanaged Metal Desktop Switch (GO-SW-5GE/GO-SW-8GE)
- Power Adapter
- Quick Install Guide

Minimum System Requirements

- Devices Supporting 802.3 Ethernet, 802.u Faster Ethernet, or 802.3ab Gigabit Ethernet
- Cat5 or better Ethernet Cable
- · Network Interface Card for each computer





5/8 Port Gigabit Unmanaged Metal Desktop Switch

	GO-SW-5GE	GO-SW-8GE
	GO-SW-SGE GIGABIT SWITCH " " " " " " " " " " " " " " " " " " "	60-3W-866 GIGARIT SWITCH * * * * * * * * * * * * * * * * * * *
Switching Fabric	•10Gbps	•16Gbps
Standards	IEEE 802.3 10BASE-T Ethernet (twisted-pair copper) IEEE 802.3u 100BASE-TX Fast Ethernet (twisted-pair copper) IEEE 802.3ab 1000BASE-T Gigabit Ethernet (twisted-pair copper)	ANSI/IEEE 802.3 NWay auto-negotiation IEEE 802.3x Flow Control IEEE 802.1p QoS IEEE 802.3az Energy-Efficient Ethernet (EEE)
Data Transfer Rates	 Ethernet: 10 Mbps (half duplex), 20 Mbps (full duplex) Fast Ethernet: 100 Mbps (half duplex), 200 Mbps (full duplex) 	Gigabit Ethernet: -2000 Mbps (full duplex)
Packet Filtering/Forwarding Rates	• Ethernet: 14,880 pps • Fast Ethernet: 148,800 pps	Gigabit Ethernet: 1,488,000 pps
Network Cables	• 10BASE-T: - UTP CAT 3, 4, 5/5e (100 m max.) - EIA/TIA-586 100-ohm STP (100 m max.)	• 100BASE-TX, 1000BASE-T: - UTP CAT 5/5e (100 m max.) - EIA/TIA-568 100-ohm STP (100 m max.)
Media Interface Exchange	Auto MDI/MDIX adjustment for all ports	
LED Indicators	Per port: Link/Activity/Speed	Per device: Power
Switching Method	Store-and-forward	
MAC Address Table	• 2K entries	8K entries
RAM Buffer	• 128KB per device	
Jumbo Frames	• 9,216 Bytes	
QoS	• 4 Queues, strict mode	
General Specifications		
DC Input	• External 5 V/1 A Level "V" Power Adapter	
Power Consumption	 Power On (Standby): DC input: 0.45 watts AC input: 1.4 watts Maximum: DC input: 2.37 watts AC input: 3.9 watts 	Power On (Standby): DC input: 0.59 watts AC input: 1.5 watts Maximum: DC input: 3.48 watts AC input: 5.4 watts
Heat Dissipation	 Power On (Standby) AC input: 4.77 BTU/h Maximum DC input: 13.30 BTU/h 	Power On (Standby) AC input: 5.22 BTU/hMaximum DC input: 18.25 BTU/h
MTBF	• 1,261,786.896 hours	• 522,270 hours
Operating Temperature	• 32 to 130 °F (0 to 50 °C)	

GO-SW-5GE & GO-SW-8GE

5/8 Port Gigabit Unmanaged Metal Desktop Switch

Storage Temperature	• 14 to 158 °F (-10 to 70 °C)		
Operating Humidity	• 10% to 90% RH non-condensing		
Storage Humidity	• 5% to 90% RH non-condensing		
Dimensions	• 3.54x 2.83 x 1.06 inches (90 x 72 x 27 mm)	• 5.03 x 3.14 x 1.10 inches (128 x 80 x 28 mm)	
Weight	• 10.08 ounces (286 grams)	• 15.52 ounces (440 grams)	
Certifications	FCC Class B ICES-003 Class B CE Class B C-Tick Class B	VCCI Class B CUL CB LVD	
Warranty			
Warranty	• Three Year Warranty ¹		
Order Information			
Part Number	Description		
GO-SW-5GE	5-Port Gigabit Unmanaged Metal Desktop Switch		
GO-SW-8GE	8-Port Gigabit Unmanaged Metal Desktop Switch		

¹3 Year Limited Warranty available only in the USA and Canada. All references to speed are for comparison purposes only. Product specifications, size and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

For more information

U.S.A. | 17595 Mt. Herrmann Street | Fountain Valley, CA 92708 | 800.326.1688 | dlink.com

All references to speed and range are for comparison purposes only. Product specifications, size, and shape are subject to change without notice, and actual product appearance may differ from that depicted herein.

©2013 D-Link Corporation/D-Link Systems, Inc. All rights reserved. D-Link, the D-Link logo, the D-Link RoHS logo are trademarks or registered trademarks of D-Link Corporation or its subsidiaries in the United States and/or other countries. Other trademarks or registered trademarks are the property of their respective owners.

Updated 08/13

