# QuickSpecs

#### **Overview**

Shape the Future of QuickSpecs - Your Input Matters

## **HPE Storage LTO Ultrium Tape Drives**

The family of HPE Storage LTO Ultrium Tape Drives (formerly known as HPE Storage LTO Ultrium Tape Drives) is the Hewlett Packard Enterprise premier line of backup and archive devices. Based on the LTO (Linear Tape-Open) Ultrium format, an open standard with a well-defined fourteen-generation roadmap, HPE Storage LTO Ultrium tape drives offer customers the best choice for investment protection. With ultimate reliability and ease of use in mind, even at 100% duty cycles, the HPE rugged design builds on superior LTO technology and adds advanced features like hardware data encryption to create a new level of data protection. The tape drives employ dynamic data rate matching to adjust to the speed of the host, reducing wear and tear on both drive and media and increasing performance, even on slower hosts. The family of tape drives also features support for HPE Library and Tape Tools which provides diagnostics, and performance optimization. If data is critical to your business, protect it with an HPE Storage LTO Ultrium tape drive.

## **HPE Storage LTO Ultrium Half-Height Tape Drives**





HPE Storage LTO Ultrium External Tape Drive

**HPE Storage LTO Ultrium Internal Tape Drive** 

## HPE Storage LTO-9 Ultrium 45000 Tape Drive

The HPE LTO-9 Ultrium 45000 tape drive represents HPE's ninth generation of LTO tape drive technology capable of storing up to 45 TB (compressed 2.5:1) per cartridge while providing ease of use with support for linear tape file system (LTFS) and AES 256-bit hardware data encryption easy-to-enable security to protect the most sensitive data and prevent unauthorized access of tape cartridges. Capable of data transfer rates up to 300 MB/sec (native), its Speed Matching feature further optimizes performance by matching speed of host to keep drives streaming and increase the reliability of the drive and media. HPE LTO Ultrium half-height drives are designed for server customers in direct attached storage (DAS) environments. The Ultrium 45000 tape drives provide investment protection with full read and write backward support with LTO-8 media. By increasing the capacity of the previous generation Ultrium drive by 50%, HPE customers now require fewer data cartridges to meet their storage needs, significantly reducing their IT costs and increasing their ROI.

## What's New

• HPE Smart Choice purchase program; for our most popular tape drives, smartly configured and ready to ship now!



#### **Overview**

## HPE Storage LTO-8 Ultrium 30750 Tape Drive

The HPE LTO-8 Ultrium 30750 tape drive represents HPEs eighth-generation of LTO tape drive technology capable of storing up to 30 TB (compressed 2.5:1) per cartridge while providing ease of use with support for LTFS and AES 256-bit hardware data encryption easy-to-enable security to protect the most sensitive data and prevent unauthorized access of tape cartridges. Capable of data transfer rates up to 300 MB/sec (native), its Speed Matching feature further optimizes performance by matching speed of host to keep drives streaming and increase the reliability of the drive and media. HPE LTO Ultrium half-height drives are designed for server customers in direct attached storage (DAS) environments. For IT organizations with stringent, long-term data retention requirements, the Ultrium 30750's WORM (Write-Once, Read-Many) data protection feature offers a simple and secure method for archiving records as part of a compliance solution to meet the toughest of industry regulations. The Ultrium 30750 tape drives provide investment protection with full read and write backward support with LTO-7 media. By doubling the native capacity of previous generation Ultrium drives, HPE customers now require fewer data cartridges to meet their storage needs, significantly reducing their IT costs and increasing their ROI.

## HPE Storage LTO-7 Ultrium 15000 Tape Drive

The HPE LTO-7 Ultrium 15000 tape drive represents HPE's seventh-generation of LTO tape drive technology capable of storing up to 15 TB (compressed 2.5:1) per cartridge while providing ease of use with support for LTFS and AES 256-bit hardware data encryption easy-to-enable security to protect the most sensitive data and prevent unauthorized access of tape cartridges. Capable of data transfer rates up to 300 MB/sec (native), its Speed Matching feature further optimizes performance by matching speed of host to keep drives streaming and increase the reliability of the drive and media. HPE LTO Ultrium half-height drives are designed for server customers in direct attached storage (DAS) environments. For IT organizations with stringent, long-term data retention requirements, the Ultrium 15000's WORM (Write-Once, Read-Many) data protection feature offers a simple and secure method for archiving records as part of a compliance solution to meet the toughest of industry regulations. The Ultrium 15000 tape drives provide investment protection with full read and write backward support with LTO-6 media, and the ability to read LTO-5 cartridges.

## LTO Ultrium Technology

Linear Tape-Open (LTO) technology was developed by three leaders in the storage industry - HPE, IBM, and Quantum - who brought together their combined expertise in tape technology to develop an entirely new format based on the best of existing technologies. Because LTO Ultrium technology was a new format, it required no cumbersome support of legacy formats, so it could be designed without compromising on reliability or performance. The LTO Program, a consortium of the three technology provider companies, has developed a well-defined fourteen-generation roadmap.

Ultrium LTO-7, LTO-8 and LTO-9 tape drives feature a breakthrough in recording technology by writing thirty-two tracks simultaneously on a linear format of 3,584 tracks, 6,656 tracks and 8,960 tracks respectively. The data is written in a serpentine pattern; the tape reverses direction after each set of tracks is written. This provides higher density recording, enabling customers to lower costs and increase efficiency by storing more data on a single tape in an industry standard format.

The LTO standard for backward compatibility up to generation seven is to write back one generation and read back two generations; therefore:

- First-generation LTO Ultrium drives (HPE Ultrium 230, HPE Ultrium 232) read and write LTO-1 media
- Second-generation LTO Ultrium drives (HPE Ultrium 460, HPE Ultrium 448) read and write LTO-1 and LTO-2 media.
- Third-generation LTO Ultrium drives (HPE Ultrium 920, Ultrium 960) read and write LTO-2 and LTO-3 media and also read LTO-1 media.
- Fourth-generation LTO Ultrium drives (Ultrium 1840, Ultrium 1760) read and write LTO-3 and LTO-4 media and also read LTO-2 media.
- Fifth-generation LTO Ultrium drives (Ultrium 3280, Ultrium 3000) read and write LTO-4 and LTO-5 media and also read LTO-3 media.
- Sixth-generation LTO Ultrium drives (Ultrium 6650, Ultrium 6250) read and write LTO-5 and LTO-6 media and also read LTO-4 media.
- Seventh-generation LTO Ultrium drives (Ultrium 15000) read and write LTO-6 and LTO-7 media and also read LTO-5 media
- Eighth-generation LTO Ultrium drives (Ultrium 30750) read and write LTO-7, LTO-7 Type M and LTO-8 media
- Ninth-generation LTO Ultrium drives (Ultrium 45000) read and write LTO-8 and LTO-9 media

As part of the LTO open standard, all HPE tape drives and media offer the same standards of compatibility with tape drives and media manufactured by other LTO vendors.

LTO data compression (LTO-DC) is an enhanced version of Advanced Lossless Data Compression (ALDC) hardware compression. Compression is automatically turned off if the compressed data would cause an overall expansion in data size, hence optimizing the available capacity on the media. Data compression is also turned off if data is found to be uncompressible; thus, allowing for better data scans. The system is used in all LTO Ultrium tape drives.

The decision about which tape technology you should buy next should be based on your future, not your past, investment. Choose the LTO Ultrium format when you need the following advantages:

- Maximum reliability, capacity and performance
- Compatibility with a broad range of operating systems and servers (e.g., a mixed system environment)
- A legacy-free technology that uses the best attributes from a wide range of tape technologies without any compromises for backward compatibility requirements
- A solid roadmap for future generations of the technology
- An open format available from multiple vendors
- Lowest media cost of any 'superdrive' tape technology

## **Hardware Based Encryption**

Since LTO generation 4, HPE LTO Ultrium tape drives support hardware-based encryption to enable greater levels of security:

- AES 256-bit Encryption
  - Easy-to-enable encryption for a secure backup
  - Helps prevent unauthorized accessed of tape media if cartridges are lost or stolen
  - Eliminates the need to purchase and manage additional h/w
- No loss in performance of backup

## **Linear Tape File System (LTFS)**

LTFS makes tape self-describing, file-based, and easy-to-use, it also provides users with the ability to use standard file operations on tape media for accessing, managing and sharing files with an interface that behaves just like a hard disk. In addition, LTFS provides the ability to share data across platforms, as you would with a USB drive or memory stick. Simply load a tape into the drive, mount it into the file system, and it becomes visible as a disk.

For more information, including user guide, downloads and compatibility, visit:

HPE StoreOpen and Linear Tape File System (LTFS) Software | HPE Store US

## **HPE StoreOpen Software**

HPE StoreOpen Software is a free software application that helps LTFS users to use and manage single tape drives, autoloaders and tape libraries

Available for Windows, Linux and Mac environments for LTO Ultrium Drives, it provides a native GUI with a familiar look and feel. It is installed automatically as part of the LTFS package, and it completely removes the need for low-level terminal commands by guiding users through the full process of select, prepare and mount an LTFS cartridge.

For more information, including user guide, downloads and compatibility, visit:

HPE StoreOpen and Linear Tape File System (LTFS) Software | HPE Store US

## **Data Rate Matching**

Data Rate Matching combines sophisticated buffer management with the HPE exclusive Variable Tape Speed technology to allow the tape drive to match its transfer rate to the host speed dynamically and continuously across the wide range of transfer rates. This feature ensures that the tape drive continues to stream data regardless of the environment, and brings two big advantages:

- It optimizes backup performance, regardless of the speed of the host or the network
- It minimizes rewinding and repositioning of the tape, reducing wear and increasing reliability

## WORM (Write-Once, Read-Many) Drive and Media Support

Critical to the success of data retention policies in highly regulated environments is the ability to store and manage data in an unalterable state. Following stringent guidelines set forth by regulatory agencies such as the SEC and HIPPA, IT organizations must now integrate new solutions and policies that can verify the integrity of stored data for periods that can extend well beyond seven years.

LTO tape drives feature the ability to archive and store data in a non-rewriteable format that meets the most stringent regulatory guidelines. Using a combination of integrated fail-safe features in the drive firmware, cartridge memory, and tape formatting, LTO Ultrium drives can archive large amounts of data for periods of up to 30 years in a secure, untampered state. Since all LTO tape drives include support for both rewritable and WORM media, IT organizations can now easily integrate a secure, long-term archiving solution into their current data protection strategy. As compared to other technologies that feature support for WORM storage, LTO tape drives offers the advantages of:

- A single drive to support all backup and archiving needs
- Two distinctive tape cartridges to easily distinguish and manage both rewriteable and WORM data cartridges
- A specially designed WORM data cartridge with multiple integrated fail-safe features to prevent accidental or intentional overwriting of data
- High-capacity, low-cost HPE WORM media that can store up to 45TB (LTO-9) of data on a single data cartridge
- Support from many backup and archiving software vendors, providing the most comprehensive and mainstream support in the industry
- The LTO open standard that offers greater choice and compatibility across all third to eighth generation Ultrium products

## **HPE Ultrium Storage Media**

HPE branded Linear Tape-Open (LTO) Ultrium cartridges are designed, manufactured and tested to provide outstanding reliability for backing up, archiving and restoring your data. We continuously monitor the quality of our branded tapes using what we believe is the industry's most comprehensive and forensic specification for quality and reliability. Using real life conditions and both HPE and non-HPE drives, we supplement extensive in-process QA parametric testing with ongoing drive-based scrutiny, to make sure performance is excellent for any combination of device duty cycle and environment.

Because HPE is a leading supplier of both LTO tape devices and media, we have the ability to re-create many different scenarios mirroring how customers use their cartridges. And many of the HPE protocols are either unique in nature or scale, such as the HPE 'Green Tape', and HPE 'Environmental Interchange' tests, or far surpass industry standards, for example, The HPE 'Locate/Rewind/Append' test. Since the beginning of 2016, almost 700 million meters of media have been pulled and over 40 million gigabytes of data have been written in the HPE demanding Green Tape Test (GTT) protocol. These ongoing tests are intended to ensure HPE LTO Ultrium media is the most reliable you can find. Your best choice for ease of support and maximum dependability is to always use HPE-branded Ultrium cartridges.

## LTO-9 Media Initialization

Media initialization has been implemented in LTO-9 technology to optimize data placement according to the characteristics of each LTO-9 cartridge. Each new LTO-9 cartridge requires this one-time initialization prior to starting read/write operations, this is only required for the first use of a new LTO-9 cartridge, subsequent loads do not require additional initialization. The initialization process varies in time depending on the environmental conditions of tape and drive. Most initializations will complete within an hour; however, in some cases it can take up to 2 hours.

For standalone drives, the "Ready" LED and the "Tape" LED on the front panel of the drive will flash together rapidly to indicate that the media initialization is taking place. This will continue until the cartridge is ready to use.

Notes: LTO-9 WORM media is now supported on HPE Ultrium LTO-9 Drives with the latest firmware.

## **Diagnostics**

HPE LTO Ultrium tape drives and automation are supported by HPE Library and Tape Tools (LTT). This tool is intended to help in the installation and maintenance of HPE tape drives and devices, including:

- Verifies installation of the drive
- Test/verify the health of the drive and media
- Provides HPE support with detailed device information
- Multiple options for finding and upgrading new firmware
- Performance optimization and recommendations
- Included with each Ultrium tape drive and available via free download supporting all HPE tape products

Instructions and downloads of HPE Library and Tape Tools are available at: HPE Library and Tape Tools | HPE Store US

## Compatibility

HPE's extensive compatibility testing program assures that your HPE LTO Ultrium tape drive works with leading servers, operating systems, and backup applications - and not just those sold by HPE. HPE LTO Ultrium tape drives work seamlessly on many platforms, making them especially suitable if you have a mixed system environment. For the latest list of servers, workstations, operating systems, and backup software that support HPE Ultrium tape drives, check the tape backup compatibility pages on our Web site at: **HPE Storage Single Point of Connectivity Knowledge - SPOCK** 

#### **Server Compatibility**

HPE Ultrium tape drives are supported on the following classes of HPE systems:

- HPE ProLiant DL servers
- HPE ProLiant ML servers
- HPE Integrity servers
- HPE 9000 servers
- HPE Apollo
- HP Inc. workstations

HPE Ultrium tape drives are also supported on server platforms from third-party manufacturers including:

- Dell
- IBM
- Oracle

For details of which tape drive models work with which systems, including third-party systems, visit: **HPE Storage Single Point of Connectivity Knowledge - SPOCK** for the latest hardware compatibility information.

## **OS Support**

Microsoft® Windows, HPE-UX, Tru64, Red Hat Linux, SUSE Linux, IBM-AIX, Oracle Solaris and other operating systems.

Notes: Please visit: HPE Storage Single Point of Connectivity Knowledge - SPOCK for the latest compatibility information.

#### **Backup Software Support**

Supported with ARCserve Backup, EMC NetWorker, EMC Retrospect, IBM Tivoli Storage Manager, Veritas NetBackup, Veritas Backup Exec., BakBone NetVault, Commvault Simpana, Tolis Group BRU, Archiware P5, QStar Archive Manager and others.

Notes: Please visit: HPE Storage Single Point of Connectivity Knowledge - SPOCK for the latest compatibility information.

#### **Cables and Termination**

All cables required for a typical internal and external connection to Hewlett Packard Enterprise servers are provided with your tape drive. For non-HPE servers, please consult your manufacturers' server specifications to determine if the cable provided with your LTO Ultrium tape drive is appropriate for use with that server.

SAS-based HPE LTO Ultrium models ship with SAS cable which allows direct attach from embedded SAS controller.

Notes: Visit: HPE Storage Single Point of Connectivity Knowledge - SPOCK for the latest compatibility information.

## **Performance Tuning**

Use HPE Library and Tape tools to assist in this area at: **HPE Library and Tape Tools | HPE Store US**Device performance test - will run data to an LTO drive direct from memory to prove the drive is capable of high performance if the data supply rate is fast enough.

System performance test for backup will read data from your primary storage device e.g. EVA disk array, and tell you how fast the array can supply multiple streams of data

System performance test for restore; this tool generates data of a known size and compressibility for benchmarking purposes.

## Service and Support

## Warranty and Services Included with the Product

Hewlett Packard Enterprise provides a 3-year, next-day, product exchange, limited warranty for all the Ultrium Tape Drives, plus 9x5 phone support for the duration of the warranty.

For more information about Hewlett Packard Enterprise's Global Limited Warranty and Technical Support, visit:

## **HPE Storage Warranty | Product Support**

#### **HPE Services**

No matter where you are in your digital transformation journey, you can count on HPE Services to deliver the expertise you need when, where and how you need it. From planning to deployment, ongoing operations and beyond, our experts can help you realize your digital ambitions.

#### Services | HPE

## **Consulting Services**

No matter where you are in your journey to hybrid cloud, experts can help you map out your next steps. From determining what workloads should live where, to handling governance and compliance, to managing costs, our experts can help you optimize your operations. **Advisory and Professional Services | HPE** 

## **HPE Managed Services**

HPE runs your IT operations, providing services that monitor, operate, and optimize your infrastructure and applications, delivered consistently and globally to give you unified control and let you focus on innovation.

## Managed services | HPE

#### Operational services

Optimize your entire IT environment and drive innovation. Manage day-to-day IT operational tasks while freeing up valuable time and resources. Meet service-level targets and business objectives with features designed to drive better business outcomes.

### Operational Support Services - Technology & IT Support | HPE

## **HPE Complete Care Service**

HPE Complete Care Service is a modular, edge-to-cloud IT environment service designed to help optimize your entire IT environment and achieve agreed upon IT outcomes and business goals through a personalized experience. All delivered by an assigned team of HPE Services experts. HPE Complete Care Service provides:

- A complete coverage approach -- edge to cloud
- An assigned HPE team
- Modular and fully personalized engagement
- Enhanced Incident Management experience with priority access
- Digitally enabled and AI driven customer experience

#### Complete Care Service | HPE

## Service and Support

#### **HPE Tech Care Service**

HPE Tech Care Service is the operational support service experience for HPE products. The service goes beyond traditional support by providing access to product specific experts, an Al driven digital experience, and general technical guidance to not only reduce risk but constantly search for ways to do things better. HPE Tech Care Service delivers a customer-centric, Al driven, and digitally enabled customer experience to move your business forward. HPE Tech Care Service is available in three response levels. Basic, which provides 9x5 business hour availability and a 2-hour response time. Essential which provides a 15-minute response time 24x7 for most enterprise level customers, and Critical which includes a 6-hour repair commitment where available and outage management response for severity 1 incidents.

#### **Tech Care Service | HPE**

## **HPE Lifecycle Services**

HPE Lifecycle Services provide a variety of options to help maintain your HPE systems and solutions at all stages of the product lifecycle. A few popular examples include:

- Lifecycle Install and Startup Services: Various levels for physical installation and power on, remote access setup, installation and startup, and enhanced installation services with the operating system.
- HPE Firmware Update Analysis Service: Recommendations for firmware revision levels for selected HPE products, taking into account the relevant revision dependencies within your IT environment.
- HPE Firmware Update Implementation Service: Implementation of firmware updates for selected HPE server, storage, and solution products, taking into account the relevant revision dependencies within your IT environment.
- Implementation assistance services: Highly trained technical service specialists to assist you with a variety of activities, ranging from design, implementation, and platform deployment to consolidation, migration, project management, and onsite technical forums.
- HPE Service Credits: Access to prepaid services for flexibility to choose from a variety of specialized service activities, including assessments, performance maintenance reviews, firmware management, professional services, and operational best practices.

For a list of Lifecycle Services available for your product go to :Lifecycle Services | HPE

For a list of the most frequently purchased services using service credits, see the HPE Service Credits Menu

#### Other Related Services from HPE Services:

#### **HPE Education Services**

Training and certification designed for IT and business professionals across all industries. Broad catalogue of course offerings to expand skills and proficiencies in topics ranging from cloud and cybersecurity to AI and DevOps. Create learning paths to expand proficiency in a specific subject. Schedule training in a way that works best for your business with flexible continuous learning options.

### IT training & certification | HPE Services

#### **Defective Media Retention**

An option available with HPE Complete Care Service and HPE Tech Care Service and applies only to Disk or eligible SSD/Flash Drives replaced by HPE due to malfunction.

Consult your HPE Sales Representative or Authorized Channel Partner of choice for any additional questions and services options.

#### Parts and Materials

HPE will provide HPE-supported replacement parts and materials necessary to maintain the covered hardware product in operating condition, including parts and materials for available and recommended engineering improvements.

Parts and components that have reached their maximum supported lifetime and/or the maximum usage limitations as set forth in the manufacturer's operating manual, product QuickSpecs, or the technical product data sheet will not be provided, repaired, or replaced as part of these services.

## Service and Support

#### **How to Purchase Services**

Services are sold by Hewlett Packard Enterprise and Hewlett Packard Enterprise Authorized Service Partners:

- Services for customers purchasing from HPE or an enterprise reseller are quoted using HPE order configuration tools.
- Customers purchasing from a commercial reseller can find services at <u>Support Services Central (hpe.com)</u>

## Al Powered and Digitally Enabled Support Experience

Achieve faster time to resolution with access to product-specific resources and expertise through a digital and data driven customer experience

Sign into the HPE Support Center experience, featuring streamlined self-serve case creation and management capabilities with inline knowledge recommendations. You will also find personalized task alerts and powerful troubleshooting support through an intelligent virtual agent with seamless transition when needed to a live support agent.

## Support Services Central (hpe.com)

#### Consume IT On Your Terms

**HPE GreenLake** edge-to-cloud platform brings the cloud experience directly to your apps and data wherever they are—the edge, colocations, or your data center. It delivers cloud services for on-premises IT infrastructure specifically tailored to your most demanding workloads. With a pay-per-use, scalable, point-and-click self-service experience that is managed for you, HPE GreenLake edge-to-cloud platform accelerates digital transformation in a distributed, edge-to-cloud world.

- Get faster time to market
- Save on TCO, align costs to business
- Scale guickly, meet unpredictable demand
- Simplify IT operations across your data centers and clouds

To learn more about HPE Services, please contact your Hewlett Packard Enterprise sales representative or Hewlett Packard Enterprise Authorized Channel Partner. Contact information for a representative in your area can be found at "Contact HPE"

## Contact Us - Hewlett Packard Enterprise - HPE - Contact Sales and Support | HPE

For more information

## Services | HPE

## **HPE Storage LTO Ultrium Half-Height Tape Drives**

### **Model Name/Kit Contents**

Description SKU

#### LTO-9 Ultrium 45000 tape drives

HPE StoreEver LTO-9 Ultrium 45000 Internal Tape Drive

BC040A

- HPE StoreEver LTO-9 Ultrium 45000 Internal Tape Drive
- HPE LTO-9 Ultrium 45 TB RW Data Cartridge
- SFF8087 Mini SAS 4i to SFF8087 Mini SAS 3i cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-9 Ultrium 45000 Internal TAA-compliant Tape Drive

BCO41A

- HPE StoreEver LTO-9 Ultrium 45000 TAA Internal Tape Drive
- HPE LTO-9 Ultrium 45 TB RW Data Cartridge
- SFF8087 Mini SAS 4i to SFF8087 Mini SAS 3i cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-9 Ultrium 45000 External Tape Drive

BC042A

- HPE StoreEver LTO-9 Ultrium 45000 External Tape Drive
- HPE LTO-9 Ultrium 45 TB RW Data Cartridge
- mini-SAS HD SFF8644 to mini-SAS HD SFF8644 cable
- Documentation

#### **Notes:**

- OD1 will appear after this part number on your sales order if factory integration is indicated.
- For US-English Localization please select BC042A#ABA
- This product is TAA (Trade Agreements Act) compliant

## LTO-8 Ultrium 30750 tape drives

HPE StoreEver LTO-8 Ultrium 30750 Internal Tape Drive

BC022A

- HPE StoreEver LTO-8 Ultrium 30750 Internal Tape Drive
- HPE LTO-8 Ultrium 30 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-8 Ultrium 30750 TAA-compliant SAS Internal Tape Drive

BC024A

- HPE StoreEver LTO-8 Ultrium 30750 Internal Tape Drive
- HPE LTO-8 Ultrium 30 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

Description SKU

HPE StoreEver LTO-8 Ultrium 30750 External Tape Drive

BC023A

- HPE StoreEver LTO-8 Ultrium 30750 External Tape Drive
- HPE LTO-8 Ultrium 30 TB RW Data Cartridge
- mini-SAS High Density SFF8644 to mini-SAS SFF8088 cable
- Documentation

#### **Notes:**

- OD1 will appear after this part number on your sales order if factory integration is indicated.
- For US-English Localization please select BC023A#ABA
- This product is TAA (Trade Agreements Act) compliant

#### LTO-7 Ultrium 15000 tape drives

HPE LTO-7 Ultrium 15000 Internal Tape Drive

BB873A

- HPE LTO-7 Ultrium 15 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-7 Ultrium 15000 TAA-compliant Internal Tape Drive

BB953A

- HPE StoreEver LTO-7 Ultrium 15000 Internal Tape Drive
- HPE LTO-7 Ultrium 15 TB RW Data Cartridge
- mini-SAS SFF8482 to SFF8087 cable
- Documentation

Notes: OD1 will appear after this part number on your sales order if factory integration is indicated.

HPE StoreEver LTO-7 Ultrium 15000 External Tape Drive

BB874A

- HPE StoreEver LTO-7 Ultrium 15000 External Tape Drive
- HPE LTO-7 Ultrium 15 TB RW Data Cartridge
- mini-SAS High Density SFF8644 to mini-SAS SFF8088 cable
- Documentation

#### **Notes:**

Description

- 0D1 will appear after this part number on your sales order if factory integration is indicated.
- For US-English Localization please select BB874A#ABA
- This product is TAA (Trade Agreements Act) compliant

## Host Bus Adapters, Controllers, and Accessories for ProLiant Servers

HPE Smart Array E208e-p SR Gen10 (8 External Lanes/No Cache) 12G SAS PCIe Plug-in Controller 8043

804398-B21

SKU

Notes: Recommended SAS HBA for connecting External LTO Ultrium tape drives to Gen10 ProLiant servers.

HPE Smart Array E208i-p SR Gen10 (8 Internal Lanes/No Cache) 12G SAS PCIe Plug-in Controller

804394-B21

A1100-8E

Notes: Recommended SAS HBA for connecting Internal LTO Ultrium tape drives to Gen10 ProLiant servers.

Microsemi Adaptec HBA 1100-8e

**Notes:** Recommended SAS HBA for DL & ML Gen9 servers only. HPE does not provide official support for this adapter, however the configuration is supported.

Media

**Description** SKU

HPE LTO-5 Ultrium 3TB RW Data Cartridge C7975A

**Notes:** Write and read support for LTO-5 Ultrium 3280 and Ultrium 3000.

HPE LTO-6 Ultrium 6.25TB RW Data Cartridge C7976A

Notes: Write and read support for LTO-6 Ultrium 6650 and Ultrium 6250.

HPE LTO-6 Ultrium 6.25TB BaFe RW Data Cartridge C7976B

Notes: Write and read support for LTO-6 Ultrium 6650 and Ultrium 6250.

HPE LTO-6 Ultrium 6.25TB WORM Data Cartridge C7976W

**Notes:** This data cartridge only supports Write-Once Read-Many recording format for LTO-6 drives. Data recorded to this data cartridge cannot be overwritten.

HPE LTO-6 Ultrium 6.25TB BaFe WORM Data Cartridge

C7976BW

**Notes:** This data cartridge only supports Write-Once Read-Many recording format for LTO-6 drives. Data recorded to this data cartridge cannot be overwritten.

HPE LTO-7 Ultrium 15TB RW Data Cartridge

C7977A

Notes: Write and read support for LTO-7 Ultrium 15000.

HPE LTO-7 Ultrium WORM Data Cartridge

C7977W

**Notes:** This data cartridge only supports Write-Once Read-Many recording format for LTO-7 drives. Data recorded to this data cartridge cannot be overwritten.

HPE LTO-8 Ultrium 30TB RW Data Cartridge

Q2078A

**Notes:** Write and read support for LTO-8 Ultrium 30750.

HPE LTO-8 Ultrium 30TB WORM Data Cartridge

Q2078W

**Notes:** This data cartridge only supports Write-Once Read-Many recording format for LTO-8 drives. Data recorded to this data cartridge cannot be overwritten.

HPE LTO-9 Ultrium 45TB RW Data Cartridge

Q2079A

Notes: Write and read support for LTO-9 Ultrium 45000.

HPE LTO-9 Ultrium 45TB WORM Data Cartridge

Q2079W

**Notes:** This data cartridge only supports Write-Once Read-Many recording format for LTO-9 drives. Data recorded to this data cartridge cannot be overwritten.

HPE Ultrium Universal Cleaning Cartridge

C7978A

## **Rack-mount Options**

Description SKU

HPE StoreEver 1U Generic Rack Mount Kit

BC029A

#### Notes

- For racked servers. No drives included. Accommodates up to two internal SAS half-height drives (such as LTO-7 Ultrium 15000, LTO-8 Ultrium 30750 or LTO-9 Ultrium 45000).
- Please refer to the 1U Rack-mount Kit web page for further information

## **Cables and Adapters**

Description SKU

HPE 12Gb Mini SAS High Density (SFF-8644) to LTO Drive 4m Cable for 1U Rack Mount Kit P35174-B21

Notes: Use this cable to connect HPE LTO-9 SAS internal tape drives to Mini SAS HD (SFF-8644) connectors

HPE StoreEver 4m Mini SAS HD (SFF-8644) LTO Drive Cable for 1U Rack Mount Kit

876805-B21

Notes: Use this cable to connect HPE LTO-5, 6, 7 and 8 SAS internal tape drives to Mini SAS HD (SFF-8644) connectors.

HPE StoreEver 4m Mini SAS (SFF-8088) LTO Drive Cable for 1U Rack Mount Kit

876804-B21

Notes: Use this cable to connect HPE LTO-5, 6, 7 and 8 SAS internal tape drives to SAS (SFF-8088) connectors.

HPE 2.0m External Mini SAS High Density to Mini SAS Cable

716191-B21

**Notes:** Use this cable to connect HPE SAS external LTO-5, LTO-6, LTO-7, LTO-8 tape devices to HPE SAS controllers with external Mini-SAS high density connectors as used by HPE E208e-p or H241 Host Bus Adapters.

HPE External 2.0m (6ft) Mini-SAS HD 4x to Mini-SAS HD 4x Cable

716197-B21

**Notes:** Use this cable to connect HPE SAS external LTO-9 tape devices to HPE SAS controllers with external Mini-SAS high density connectors as used by HPE E208e-p or H241 Host Bus Adapters.

## **Pre-Configured Models**

## **HPE Smart Choice purchase program**

The HPE Smart Choice purchase program features popular fully configured products that can be quoted in minutes and shipped quickly through HPE Authorized Partners. Products are configured and tested in an HPE factory and stocked at HPE Authorized Distributors and Partners. The products arrive in a single box, making onsite integration easier and more efficient for partners and customers. Additionally, there are aggressively priced HPE Tech Care Services available only through the HPE Smart Choice program when you purchase an HPE Smart Choice product.

For HPE Smart Choice configuration and product details, please visit the Smart Choice Supplemental QuickSpecs: HPE Smart Choice Purchase Program – Supplemental QuickSpecs

## Pre-Configured models ship with the configurations below.

- Pre-Configured models ship with the configurations below. Options can be selected from the Core or Additional options section of this QuickSpecs.
- Hewlett Packard Enterprise does not allow factory integration of options into pre-configured models. Any additional options purchased will not be shipped inside the server.

| Sku Number | Model Name  | Part Description   |
|------------|---|--|
| P84140-B25 | HPE Storage LTO-7 Ultrium External Tape Drive 5x LTO-7 15TB Data Cartridges | (1) HPE StoreEver LTO-7 Ultrium 15000 External Tape Drive  |
|            |   | (5) HPE LTO-7 Ultrium 15TB RW Data Cartridge   |
| P84141-B25 | HPE Storage LTO-8 Ultrium External Tape Drive 5x LTO-8 30TB Data Cartridges | <ul><li>(1) HPE StoreEver LTO-8 Ultrium 30750 External Tape Drive</li><li>(5) HPE LTO-8 Ultrium 30TB RW Data Cartridge</li></ul> |
| P84142-B25 | HPE Storage LTO-9 Ultrium External Tape Drive 5x LTO-9 45TB Data Cartridges | (1) HPE StoreEver LTO-9 Ultrium 45000 External Tape Drive  |
|            |   | (5) HPE LTO-9 Ultrium 45TB RW Data Cartridge   |

## **Technical Specifications**

## **Family Information**

|   | LTO-7 Ultrium 15000                        | LTO-8 Ultrium 30750                       | LTO-9 Ultrium 45000                    |  |
|---|--|---|--|--|
| Dimensions                              |  |   |  |  |
| Form Factor                             |  | 5¼-inch half-height                       |  |  |
| Physical (HxWxD)Internal                |  | 1.6 x 5.7 x 8.1 in                        |  |  |
|   |  | (4.1 x 14.5 x 20.6 cm)                    |  |  |
| Physical (HxWxD) External               |  | 3 x 8.8 x 11.7 in                         |  |  |
|   |  | (7.7 x 22.3 x 29.5 cm)                    |  |  |
| Shipping (HxWxD) Internal               |  | 7.9 x 9.4 x 11.4 in                       |  |  |
|   |  | (24 x 31 x 39 cm)                         |  |  |
| Shipping (HxWxD)External                |  | 9.4 x 12.2 x 15.4 in<br>(24 x 31 x 39 cm) |  |  |
| Weight                                  |  | (24 x 31 x 39 (III)                       |  |  |
| Out of boxInternal                      |  | 3.2 lb (1.45 kg)                          |  |  |
| Out of boxExternal                      |  | 10.3 lb (4.65 kg)                         |  |  |
| Shipping Internal                       |  | 5.1 lb (2.3kg)                            |  |  |
| Shipping External                       | 5.1 lb (2.3kg)<br>11 lb (5 kg)             |   |  |  |
| Capacity                                |  | 11 10 (3 kg)                              |  |  |
| Native                                  | 6 TB                                       | 12 TB                                     | 18 TB                                  |  |
| Compressed                              | 15 TB                                      | 30 TB                                     | 45 TB                                  |  |
| 2.5:1 compression for LTO-7 and higher) | 13 15                                      | 30 13                                     |  |  |
| Buffer Size                             | 1024 MB                                    | 1024 MB                                   | 1024 MB                                |  |
| Sustained transfer rate, native         | 300 MB/s                                   | 300 MB/s                                  | 300 MB/s                               |  |
| Burst transfer rate                     | 600 MB/s (with 6G                          |   | with 12Gb/s SAS)                       |  |
| Data rate matching range                | 100-300 MB/s (native)                      | 100-300 MB/s (native)                     | 100-300 MB/s (native)                  |  |
| Average locate time (BOT - MOT)         |  | a 60 seconds for LTO-8 media              | 1 1 1                                  |  |
| Average load time                       | 12s  | 15s                                       | 17s                                    |  |
| Average load fille Average unload time  | 17s  | 24s                                       | 28s – 275s                             |  |
| Rewind time from EOT                    | 114s (6TB tape)                            | 114s                                      | 123s                                   |  |
| Rewind tape speed                       | 1143 (01b lape)                            | 9.0 m/s                                   | 1233                                   |  |
| Reliability                             |  | 7.0 111/3                                 |  |  |
| MTBF                                    |  | 250,000 hours                             |  |  |
| MIIDF                                   |  | at 100% duty cycle                        |  |  |
| Uncorrected Error Rate                  |  | 1 in 1x10 <sup>19</sup> bits              |  |  |
| oncorrected Error Rate                  | LTO Ultrium 5                              | LTO Ultrium 7                             | LTO Liltrium 9                         |  |
|   | (Read only);                               | (Read and Write); LTO                     | LTO Ultrium 8<br>(Read and Write); LTO |  |
|   | LTO Ultrium 6                              | Ultrium 8 (Read and Write)                | Ultrium 9 (Read and Write)             |  |
|   | (Read and Write);                          | Official of Read and Wille)               | Officially (Read and Wille)            |  |
|   | LTO Ultrium 7                              |   |  |  |
|   | (Read and write)                           |   |  |  |
| Recording method                        | (Read and Wille)                           | 32-channel linear serpentin               | 0                                      |  |
| Recording format                        | LTO Ultrium 7                              | LTO Ultrium 8                             | LTO Ultrium 9                          |  |
| Recording format                        | LTO Ultrium 6 (for 2.5 TB                  | LTO Ultrium 7 (for 6 TB                   | LTO Ultrium 8 (for 12 TB               |  |
|   | tape)                                      | tape)                                     | tape)                                  |  |
| Data compression                        |  | node compression (an enhance              |  |  |
| Error detection/ correction             | 2.02034411                                 | Reed-Solomon                              | · · · · · · · · · · · · · · · · · · ·  |  |
| Read channel technology                 | Partial Response Maximum Likelihood (PRML) |   |  |  |
| Data encoding method                    | RLL 32/33                                  |   |  |  |

## **Technical Specifications**

| Interface                     |  |   |  |
|-------------------------------|--|---|--|
|                               | LTO-7 Ultrium 15000  | LTO-8 Ultrium 30750   | LTO-9 Ultrium 45000  |
| Interface type                | 6Gb/sec  | : Dual Port SAS   | 12Gb/sec Dual Port SAS   |
| SAS connector                 | SAS Internal: mini-SAS SFF8482<br>SAS External: mini-SAS SFF8088         |   | SAS Internal: mini-SAS<br>SFF8482<br>SAS External: mini-SAS HD<br>SFF8644  |
| Power Specifications          |  |   |  |
| Power requirements Internal   | 5V@4.0A (typical)  | 5V@4.0A (typical)   | 5V@4.0A (typical)  |
| (including rack-mount model)  | +5V@4.5A (max)   | +5V@4.5A (max)  | +5V@4.0A (max)   |
| _                             | +12V@1.0A (typical)<br>+12V@3.5A (max)                                   | +12V@1.2A (typical)<br>+12V@4.0A (max)                                | +12V@1.2A (typical)<br>+12V@3.5A (max)   |
| Power requirements            | 100 to 240 VAC,  | 100 to 240 VAC,   | 100 to 240 VAC,  |
| External                      | 50-60 Hz, auto-ranging,<br>0.8A max                                      | 50-60 Hz, auto-ranging,<br>0.8A max                                   | 50-60 Hz, auto-ranging,<br>0.8A max  |
| Power consumption             | 11 Watts idle  | 11 Watts idle   | 17 Watts idle  |
|                               | 31Watts typical  | 31Watts typical   | 33 Watts typical   |
| Environmental Specifications  |  |   |  |
| Temperature range             | Allowable Operating:   | 5° C) if 3 CFM airflow is provided 0° C) if 3 CFM airflow is provided | Recommended Operating:<br>59° F to 77° F (15° C to 25°<br>C) if 3 CFM airflow is<br>provided  Allowable Operating:<br>59° F to 95° F (15° C to 35°<br>C) if 3 CFM airflow is<br>provided |
|                               | Non-Operating: -40° F to 1<br>60° C for LTO-7)                           | 51° F (-40° C to 66° C, -40° C to                                     | 1  |
| Non-condensing humidity range | Operating: 20 to 80% RH (Non-condensing, max wet bulb temperature = 26C) |   | Recommended Operating: 20 to 50%  Allowable Operating: 20 to 80% (Non-condensing, max wet bulb temperature = 22C)  |
|                               | Non-Operating: 10 to 95% condensing, max wet bulb                        | (90% for LTO-8) RH (Non-<br>temperature = 26C)                        | 5 to 80% for LTO-9  (Non-condensing, max wet bulb temperature = 26C)   |

## **Technical Specifications**

## **Standards Compliance**

- CSA Certification to C22.2, No.60950 (cCSAus)
- TÜV EN60950 (IEC 60950 and EN60950)
- CE Declaration of Conformity
- FCC 47 CFR Parts 15
- NOM
- VCCI
- C-TICK
- RRL
- BSMI
- GOSH
- CB Certificate and Report (IEC 60950)

## **Front Panel LED Indicators**

HPE LTO Ultrium 7, 8 and 9 tape drives have five LED indicators on the front panel:

- Ready
- Drive
- Tape
- Clean
- Encryption

Please consult your HPE Ultrium Tape Drive "Getting Started Guide" for more information on how to use these LED indicators for ascertaining drive status and for help in troubleshooting your HPE LTO Ultrium tape drive.

## **Summary of Changes**


| Date        | Version History | Action  | Description of Change  |
|-------------|-----------------|---------|--|
| 02-Sep-2025 | Version 51      | Changed | Pre-Configured Models section was updated - HPE Smart Choice purchase  |
|             |                 |         | program information was added  |
| 28-Jul-2025 | Version 50      | Changed | Survey link updated.   |
| 05-May-2025 | Version 49      | Changed | Overview, Standard Features and Configuration Information sections were updated. Branding updates  |
| 02-Dec-2024 | Version 48      | Changed | Overview, Standard Features, Configuration Information and Technical Specifications section were updated.                                  |
| 15-Jul-2024 | Version 47      | Changed | Overview, Standard Features, Service and Support, Configuration Information and Technical Specifications section were updated.             |
| 06-May-2024 | Version 46      | Changed | Standard Features, Service and Support, Configuration Information and Technical Specifications section were updated.  Obsolete SKU removed |
| 04-Dec-2023 | Version 45      | Changed | HPE Service Rebranding Obsolete SKU removed  |
| 13-Jun-2022 | Version 44      | Changed | Standard Features section was updated.   |
| 07-Feb-2022 | Version 43      | Changed | Overview and Configuration Information sections were updated.  |
| 10-Jan-2022 | Version 42      | Changed | Changes made throughout the QuickSpecs   |
| 01-Nov-2021 | Version 41      | Changed | Service and Support section was updated.   |
| 17-May-2021 | Version 40      | Changed | Configuration Information section was updated.   |
| 06-Apr-2021 | Version 39      | Changed | Configuration Information section was updated.   |
| 07-Dec-2020 | Version 38      | Changed | Configuration Information section was updated.   |
| 05-Oct-2020 | Version 37      | Changed | Configuration Information section was updated.   |
| 08-Sep-2020 | Version 36      | Changed | Configuration Information section was updated.   |
| 17-Aug-2020 | Version 35      | Changed | QuickSpecs layout was updated, and Branding Refresh was applied.   |
| 06-Apr-2020 | Version 34      | Changed | QuickSpecs layout was updated and Obso SKUs were removed   |
| 15-Apr-2019 | Version 33      | Changed | Overview, Product Highlights and Options sections were updated   |
| 04-Mar-2019 | Version 32      | Changed | Options section was updated.   |
| 02-Apr-2018 | Version 31      | Changed | Service and Support section and Options were revised.  |
| 05-Feb-2018 | Version 30      | Changed | Overview, Product Highlights, Compatibility, Options, and Technical Specifications were revised.   |
| 04-Dec-2017 | Version 29      | Changed | Overview, Product Highlights, Compatibility, Options, and Technical Specifications were revised.   |
| 04-Sep-2017 | Version 28      | Changed | Changes made throughout the QuickSpecs   |
| 07-Aug-2017 | Version 27      | Changed | Changes made throughout the QuickSpecs   |
| 11-Jul-2017 | Version 26      | Changed | Removed LTO-3 Ultrium 920 Tape Drives & Ultrium Full-Height Drives   |
| 11-Mar-2016 | Version 25      | Changed | Changes made to the options section  |
| 19-Feb-2016 | Version 24      | Changed | Changed a reference in the Option Section, Descriptions updated.   |
| 17-Dec-2015 | Version 23      | Changed | Changes made in the Overview and standard features sections  |
| 01-Dec-2015 | Version 22      | Changed | Changes made throughout the QuickSpecs   |
| 03-Apr-2015 | Version 21      | Changed | Remove OD1 for internal drives into rackmount kits, SKUs descriptions were updated.  |
| 07-Nov-2014 | Version 20      | Changed | Changes made throughout the QuickSpecs.  |
| 09-May-2014 | Version 19      | Removed | LTO-4 Ultrium 1840 Tape Drives were removed.   |
| 02-May-2014 | Version 18      | Changed | Recommended Support was revised and Optional HPE Support Services was removed.   |
| 07-Mar-2014 | Version 17      | Changed | Image correction.  |
| 21-Feb-2014 | Version 16      | Changed | Added images.  |

## **Summary of Changes**

| Date           | Version History | Action       | Description of Change  |  |
|----------------|-----------------|--------------|--|--|
| 23-Dec-2013    | Version 15      | Changed      | HPE StoreEver LTO-2 Ultrium 448 Tape Drives were removed   |  |
|                |                 |              | Performance was revised for LTO-6 Ultrium 6650   |  |
| 13-Sep-2013    | Version 14      | Changed      | Changes were made to the following sections:   |  |
|                |                 |              | Product Highlights   |  |
|                |                 |              | Service and Support  |  |
|                |                 |              | Options The contract of the co |  |
| 21 D - 2012    |                 | Clara and al | Technical Specifications   |  |
| 21-Dec-2012    | Version 13      | Changed      | Changes were made to the following sections:   |  |
|                |                 |              | Options: updated part # COL98A in HPE LTO Ultrium Full Height Tape Drives Technical Specifications: updated Capacity section   |  |
| 04-Dec-2012    | Version 12      | Changed      | Changes made throughout the QuickSpecs.  |  |
| 19-Oct-2012    | Version 11      | Changed      | Change was made to URL in Service and Support, HPE Support, and Warranty   |  |
| 19-001-2012    | version II      | Changed      | Information section.   |  |
| 13-Aug-2012    | Version 10      | Changed      | Changes were made in Overview, Features, Product Highlights, Compatibility   |  |
|                |                 |              | and Options sections.  |  |
| 28-Oct-2011    | Version 9       | Added        | HPE StoreOpen Standalone was added to Product Highlights.  |  |
| 23-Sep-2011    | Version 8       | Changed      | Updated the following: Linear Tape File Systems (LTFS) updated URL   |  |
| 8-Jun-2011     | Version 7       | Removed      | Removed StorageWorks throughout the document.  |  |
| 27-May-2011    | Version 6       | Removed      | HPE StorageWorks Ultrium 232 Tape Drive was removed.   |  |
| 29-Apr-2011    | Version 5       | Changed      | Updated the following: replaced "Go Connect" link with the "SPOCK" link throughout the entire document.  |  |
| 29-Oct-2010    | Version 4       | Removed      | Tape Array 5300 and Redundant, hot-swap power supply and fan for Tape  |  |
|                |                 |              | Array 5300 were removed from Rack-mount Options.   |  |
| 27-Sep-2010    | Version 3       | Changed      | Key Features and Customer Benefits were moved into Features  |  |
|                |                 |              | Software in the Box was changed to Included Software in Product Highlights   |  |
|                |                 |              | Related was changed to Optional for the HPE Support Services that will   |  |
|                |                 |              | enhance your HPE product experience descriptions and Customer Technical  |  |
|                |                 |              | Training, HPE Service Awards and Additional Services Information were  |  |
|                |                 |              | completely revised in Service and Support, HPE Support and Warranty  |  |
|                |                 |              | Information  |  |
|                |                 |              | Software was changed to Upgrade included software to Data Protector  |  |
|                |                 |              | Express in Options Value was added to Customer Benefits  |  |
|                |                 |              | HPE Data Protector Express Basic was added to Backup Software Support  |  |
|                |                 |              | Part numbers were removed from Models  |  |
| 18-Jun-2010    | Version 2       | Changed      | Changes made within the Media section of Options.  |  |
| 29-Mar-2010    | Version 1       | New          | New QuickSpecs   |  |
| _ / I IGI ZOTO | 7 CI 31011 I    | 1 10 11      | Ten daletopeed   |  |

## Copyright

Make the right purchase decision. Contact our presales specialists.



Get updates





© Copyright 2025 Hewlett Packard Enterprise Development LP. The information contained herein is subject to change without notice. The only warranties for Hewlett Packard Enterprise products and services are set forth in the express warranty statements accompanying such products and services. Nothing herein should be construed as constituting an additional warranty. Hewlett Packard Enterprise shall not be liable for technical or editorial errors or omissions contained herein.

Microsoft and Windows NT are US registered trademarks of Microsoft Corporation. Intel is a US registered trademark of Intel Corporation.

For tape drives and media, 1 GB = 1 billion bytes. Actual formatted capacity is less.

c04123270 - 13572 - Worldwide - V51 - 02-September-2025